

A Relational Logic for Higher-Order Programs

ALEJANDRO AGUIRRE, IMDEA Software Institute

GILLES BARTHE, IMDEA Software Institute

MARCO GABOARDI, University at Buffalo, SUNY

DEEPAK GARG, MPI-SWS

PIERRE-YVES STRUB, École Polytechnique

Relational program verification is a variant of program verification where one can reason about two programs and as a special case about two executions of a single program on different inputs. Relational program verification can be used for reasoning about a broad range of properties, including equivalence and refinement, and specialized notions such as continuity, information flow security or relative cost. In a higher-order setting, relational program verification can be achieved using relational refinement type systems, a form of refinement types where assertions have a relational interpretation. Relational refinement type systems excel at relating structurally equivalent terms but provide limited support for relating terms with very different structures.

We present a logic, called Relational Higher Order Logic (RHOL), for proving relational properties of a simply typed λ -calculus with inductive types and recursive definitions. RHOL retains the type-directed flavour of relational refinement type systems but achieves greater expressivity through rules which simultaneously reason about the two terms as well as rules which only contemplate one of the two terms. We show that RHOL has strong foundations, by proving an equivalence with higher-order logic (HOL), and leverage this equivalence to derive key meta-theoretical properties: subject reduction, admissibility of a transitivity rule and set-theoretical soundness. Moreover, we define sound embeddings for several existing relational type systems such as relational refinement types and type systems for dependency analysis and relative cost, and we verify examples that were out of reach of prior work.

ACM Reference format:

Alejandro Aguirre, Gilles Barthe, Marco Gaboardi, Deepak Garg, and Pierre-Yves Strub. 2017. A Relational Logic for Higher-Order Programs. 1, 1, Article 1 (February 2017), 57 pages.

DOI: 10.1145/nnnnnnn.nnnnnnn

1 INTRODUCTION

Many important aspects of program behavior go beyond the traditional characterization of program properties as sets of traces (Alpern and Schneider 1985). Hyperproperties (Clarkson and Schneider 2008) generalize properties and capture a larger class of program behaviors, by focusing on sets of sets of traces. As an intermediate point in this space, relational properties are sets of pairs of traces. Relational properties encompass many properties of interest, including program equivalence and refinement, as well as more specific notions such as non-interference and continuity.

Relational verification is an instance of program verification that targets relational properties. Expectedly, standard verification methods such as type systems, program logics, and program analyses can be lifted to a relational setting. However, it remains a challenge to devise sufficiently powerful methods that can be used to verify a broad range of examples. In effect, most existing relational verification methods are limited in the examples that they can naturally verify, due to the fundamental tension between the syntax-directed nature of program verification, and the need to relate structurally different programs. Moreover, approaches to resolve this tension highly depend on the programming paradigm, on the class of program properties considered, and on the

2017. XXXX-XXXX/2017/2-ART1 \$15.00

DOI: 10.1145/nnnnnnn.nnnnnnn

verification method. In the (arguably simplest) case of deductive verification of general properties of imperative programs, one approach to reduce this tension is to use self-composition (Barthe et al. 2004), which reduces relational verification to standard verification. However, reasoning about self-composed programs might be cumbersome. Alternatively, there exist expressive relational program logics that rely on an intricate set of rules to reason about a pair of programs. These logics combine two-sided rules, in which the two programs have the same top-level structure, and one-sided rules, which operate on a single program. Rules for loops are further divided into synchronous, in which both programs perform the same number of iterations, and asynchronous rules, that do not have this restriction but introduce more complexity (Barthe et al. 2017; Benton 2004).

In contrast, deductive verification of general properties of (pure) higher-order programs is less developed. One potential approach to solve the tension between the syntax-directedness, and the need to relate structurally different programs, is to reduce relational verification of pure higher-order programs to proofs in higher-order logic. There are strong similarities between this approach and self-composition: it reduces relational verification to standard verification, but this approach is very difficult to use in practice. A better alternative is to use relational refinement types such as rF^* (Barthe et al. 2014), $HOARE^2$ (Barthe et al. 2015), $DFuzz$ (Gaboardi et al. 2013) or $RelCost$ (Çiçek et al. 2017). Informally, relational refinement type systems use assertions to capture relationships between inputs and outputs of two higher-order programs. They are appealing for two reasons:

- They capture many important properties of programs in a direct and intuitive manner. For instance, the type $\{x :: \mathbb{N} \mid x_1 \leq x_2\} \rightarrow \{y :: \mathbb{N} \mid y_1 \leq y_2\}$ captures the set of pairs of functions that preserve the natural order on natural numbers, i.e. pairs of functions $f_1, f_2 : \mathbb{N} \rightarrow \mathbb{N}$ such that for every $x_1, x_2 \in \mathbb{N}$, $x_1 \leq x_2$ implies $f_1(x_1) \leq f_2(x_2)$. (The subscripts 1 and 2 on a variable refer to its values in the two runs.)
- They can potentially benefit from a long and successful line of foundational (Dunfield and Pfenning 2004; Freeman and Pfenning 1991; Melliès and Zeilberger 2015; Xi and Pfenning 1999) and practical (Swamy et al. 2016; Vazou et al. 2014) research on refinement types.

Unfortunately, existing relational refinement type systems fail to support the verification of several examples. Broadly speaking, the two programs in a relational judgment may be required to have the same type and the same control flow; moreover, this requirement must be satisfied by their subprograms: if the two programs are applications, then the two sub-programs in argument position (resp. in function position) must have the same type and the same control flow; if the two programs are case expressions, they must enter the same branch, and their branches must themselves have the same control flow; if the two programs are recursive definitions, then their bodies must perform the same sequence of recursive calls; etc. This restriction, which can be found in more or less strict forms in the different relational type systems, limits the ability to carry fine-grained reasoning about terms that are structurally different. This raises the question whether the type-directed form of reasoning purported by refinement types can be reconciled with an expressive relational verification of higher-order programs. We provide a positive answer for pure higher-order programs; extending our results to effectful programs is an important goal, but we leave it for future work.

Our starting point is the observation that relational refinement type systems are inherently restricted to reasoning about two structurally similar programs, because relational assertions are embedded into types. In order to provide broad support for one-sided rules (i.e., rules that contemplate only one of the two expressions), it is therefore necessary to consider relational assertions at the top-level, since one-sided rules have a natural formulation in this setting. Considering relational assertions at the top-level can be done in two different ways: either by supporting a rich theory of subtyping for relational refinement types, in such a way that each type admits a normal form where refinements only arise at the top-level, or simply by adapting the definitions and rules of refinement type systems so that only the top-level refinements are considered. Although both approaches are feasible, we believe that the second approach is more streamlined and leads to friendlier verification environments.

Contributions. We present a new logic, called Relational Higher Order Logic (RHOL, § 5), for reasoning about relational properties of higher-order programs written in a variant of Plotkin’s PCF (§ 2). The logic manipulates judgments of the form:

$$\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$$

where Γ is a simply typed context, σ_1 and σ_2 are (possibly different) simple types, t_1 and t_2 are terms, Ψ is a set of assertions, and ϕ is an assertion. Our logic retains the type-directed nature of (relational) refinement type systems, and features typing rules for reasoning about structurally similar terms. However, disentangling types from assertions also makes it possible to define type-directed rules operating on a single term (left or right) of the judgment. This confers great expressivity to the logic, without significantly affecting its type-directed nature, and opens the possibility to alternate freely between two-sided and one-sided reasoning, as done in first-order imperative languages.

The validity of judgments is expressed relative to a set-theoretical semantics—our variant of PCF is restricted to terms which admit a set-theoretical semantics, including strongly normalizing terms. More precisely, a judgment $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$ is valid if for every valuation ρ (mapping variables in the context Γ to elements in the interpretation of their types), the interpretation of ϕ is true whenever the interpretation of (all the assertions in) Ψ is true. Soundness of the logic can be proved through a standard model-theoretic argument; however, we provide an alternative proof based on a sound and complete embedding into Higher-Order Logic (HOL, § 3). We leverage this equivalence to establish several meta-theoretical properties of the logic, notably subject reduction.

Moreover, we demonstrate that RHOL can be used as a general framework, by defining sound embedding for several relational type systems: relational refinement types (§ 6.2), the Dependency Core Calculus (DCC) for many dependency analyses, including those for information flow security (§ 6.3), and the RelCost (§ 6.4) type system for relative cost. The embedding of RelCost is particularly interesting, since it exercises the ability of our logic to alternate between synchronous and asynchronous reasoning. Finally, we verify several examples that go beyond the capabilities of previous systems (§ 7).

Related work. While dependent type theory is the prevailing approach to reason about (pure) higher-order programs, several authors have explored another approach, which is crisply summarized by Jacobs (1999): “A logic is always a logic over a type theory”. Formalisms following this approach are defined in two stages; the first stage introduces a (dependent) type theory for writing programs, and the second stage introduces a predicate logic to reason about programs. This approach has been pursued independently in a series of works on logic-enriched type theories (Aczel and Gambino 2000, 2006; Adams and Luo 2010; Belo 2007; Dybjer 1985), and on refinement types Pfenning (2008); Zeilberger (2016). In the latter line of work, programs are written in an intrinsically typed λ -calculus à la Church; then, a system of sorts (a.k.a. refinements) is used to establish properties of programs typable in the first system. Our approach is similar; however, these works are developed in a unary setting, and do not consider the problem of relational verification.

Moreover, there is a large body of work on relational verification; we focus on type-based methods and deductive methods. Relational Hoare Logic (Benton 2004) and Relational Separation Logic (Yang 2007) are two program logics, respectively based on Hoare Logic and Separation Logic, for reasoning about relational properties of (first-order) imperative programs. These logics have been used for a broad range of examples and applications, ranging from program equivalence to compiler verification and information flow analysis. Moreover, they have been extended in several directions. For example, Probabilistic Relational Hoare Logic (Barthe et al. 2009) and approximate probabilistic Relational Hoare Logic (Barthe et al. 2012) are generalizations of Relational Hoare logic for reasoning about relational properties of (first-order) probabilistic programs. These logics have been used for a broad range of applications, including probabilistic information flow, side-channel security, proofs of cryptographic strength (reductionist security) and differential privacy. Cartesian Hoare Logic (Sousa and Dillig 2016) is also a recent generalization of Relational Hoare Logic for reasoning about bounded safety (i.e. k -safety

for arbitrary but fixed k) properties of (first-order) imperative programs. This logic has been used for analyzing standard libraries. Experiments have demonstrated that such logics can be very effective in practice. Our formalism can be seen as a proposal to adapt their flexibility to pure higher-order programs.

Product programs (Barthe et al. 2011, 2004; Terauchi and Aiken 2005; Zaks and Pnueli 2008) are a general class of constructions that emulate the behavior of two programs and can be used for reducing relational verification to standard verification. While product programs naturally achieve (relative) completeness, they are often difficult to use since they require global reasoning on the obtained program—however recent works (Blatter et al. 2017) show how this approach can be automated in specific settings. Building product programs for (pure) higher-order languages is an intriguing possibility, and it might be possible to instrument RHOL using ideas from Barthe et al. (2017) to this effect; however, the product programs constructed in (Barthe et al. 2017) are a consequence, rather than a means, of relational verification.

Several type systems have been designed to support formal reasoning about relational properties for functional programs. Some of the earlier works in this direction have focused on the semantics foundations of parametricity, like the work by Abadi et al. (1993) on System R, a relational version of System F. The recent work by Ghani et al. (2016a) has further extended this approach to give better foundations to a combination of relational parametricity and impredicative polymorphism. Interestingly, similarly to RHOL, System R also supports relations between expressions at different types, although, since System R does not support refinement types, the only relations that System R can support are the parametric ones on polymorphic terms. In RHOL, we do not support parametric polymorphism à la System F currently but the relations that we support are more general. Adding parametric polymorphism will require foregoing the set-theoretical semantics, but it should still be possible to prove equivalence with a polymorphic variant of higher-order logic.

Several type systems have been proposed to reason about information flow security, a prime example of a relational property. Some examples include SLAM (Heintze and Riecke 1998), the type system underlying Flow Caml (Pottier and Simonet 2002) and DCC (Abadi et al. 1999). Most of these type systems consider only one expression but they allow the use of information flow labels to specify relations between two different executions of the expression. As we show in this paper, this approach can also be implemented in RHOL. We show how to translate DCC since it is one of the most general type systems; however, similar translations can also be provided for the other type systems.

Relational Hoare Type Theory (RHTT) (Nanevski et al. 2013; Stewart et al. 2013) is a formalism for relational reasoning about stateful higher-order programs. RHTT was designed to verify security properties like authorization and information flow policies but was used for the verification of heterogeneous pointer data structures as well. RHTT uses a monad to separate stateful computations and relational refinements on the monadic type express relational pre- and post-conditions. RHTT supports reasoning about two different programs but the programs must have the same types at the top-level. RHTT's rules support both two- and one-sided reasoning similar to RHOL, but the focus of RHTT is on verifying properties of the program state. In particular, examples such as those in §7 or embeddings such as those in §6 were not considered in RHTT. RHTT is proved sound over a domain-theoretic model and continuity must be proven explicitly during the verification of recursive functions (rules are provided to prove continuity in many cases). In contrast, RHOL's set-theoretic model is simpler, but admits only those recursive functions that have a unique interpretation in set-theory.

Logical relations (Plotkin 1973; Statman 1985; Tait 1967) provide a fundamental tool for reasoning about programs. They have been used for a broad range of purposes, including proving unary properties (for instance strong normalization or complexity) and relational properties (for instance equivalence or information flow security). Our work can be understood as an attempt to internalize the versatility of relational logical relations in a syntactic framework. There is a large body of works on logic for logical relations, from the early works by Plotkin and Abadi (1993) to more recent works on logics for reasoning about states and concurrency by Ahmed, Birkedal, Dreyer, and collaborators among others (Dreyer et al. 2011, 2010; Jung et al. 2015;

Krogh-Jespersen et al. 2017). In particular, the IRIS logic (Jung et al. 2015) can be seen as a powerful reasoning framework for logical relations, as shown recently by Krogh-Jespersen et al. (2017). Even if we also aim at internalize the logical relations, the goal of RHOL differ from the one of IRIS in the fact that we aim for syntax-driven relational verification.

We have already mentioned the works on relational refinement type systems for verifying cryptographic constructions (Barthe et al. 2014), for differential privacy (Barthe et al. 2015; Gaboardi et al. 2013) and for relational cost analysis (Çiçek et al. 2017). This line of works is probably the most related to our work, however RHOL improves over all of them, as also shown by some of the embedding we give in Section 6. Another work related to this direction is the one by Asada et al. (2016). This work proposes a technique to reduce relational refinement to standard first order refinements. Their technique is incomplete but it works well on some concrete examples. As we discussed before, we believe that some technique of this kind can be applied also to RHOL however this is orthogonal to our goal and we leave it for future investigations.

2 (A VARIANT OF) PCF

We consider a variant of PCF (Plotkin 1977) with booleans, natural numbers, lists and recursion, and recursive definitions. For the latter, we require that all recursive calls are performed on strictly smaller elements—as a consequence, the fixpoint equation derived from the definition has a unique set-theoretical solution. The precise method to enforce this requirement is orthogonal to our purposes, and could for instance be based on a syntactic guard predicate, or on sized types.

Types are defined by the grammar:

$$\tau, \sigma ::= \mathbb{B} \mid \mathbb{N} \mid \text{list}_\tau \mid \tau \times \tau \mid \tau \rightarrow \tau$$

We let I range over inductive types.

Terms of the language are defined by the grammar:

$$\begin{aligned} t ::= & x \mid \langle t, t \rangle \mid \pi_1 t \mid \pi_2 t \mid t t \mid \lambda x : \tau. t \mid c \mid S t \mid t :: t \mid \text{case } t \text{ of } 0 \mapsto t; S \mapsto t \mid \text{case } t \text{ of } \text{tt} \mapsto t; \text{ff} \mapsto t \\ & \mid \text{case } t \text{ of } [] \mapsto t; _ :: _ \mapsto t \mid \text{letrec } f x = t \end{aligned}$$

where x ranges over a set V of variables, c ranges over the set $\{\text{tt}, \text{ff}, 0, []\}$ of constants, and λ -abstractions are à la Church. The operational behavior of terms is captured by $\beta\iota\mu$ -reduction $\rightarrow_{\beta\iota\mu} = \rightarrow_\beta \cup \rightarrow_\iota \cup \rightarrow_\mu$, where β -reduction, ι -reduction and μ -reduction are defined as the contextual closure of:

$$\begin{array}{lll} (\lambda x. t) u & \rightarrow_\beta & t[u/x] & \text{case ff of tt} \mapsto u; \text{ff} \mapsto v & \rightarrow_\iota & v \\ \pi_i \langle t_1, t_2 \rangle & \rightarrow_\beta & t_i & \text{case } [] \text{ of } [] \mapsto u; _ :: _ \mapsto v & \rightarrow_\iota & u \\ \text{case } 0 \text{ of } 0 \mapsto u; S \mapsto v & \rightarrow_\iota & u & \text{case } h :: t \text{ of } [] \mapsto u; _ :: _ \mapsto v & \rightarrow_\iota & (v h t) \\ \text{case } S t \text{ of } 0 \mapsto u; S \mapsto v & \rightarrow_\iota & (v t) & (\text{letrec } f x = t) (C \vec{t}) & \rightarrow_\mu & t[C \vec{t}/x][\text{letrec } f x = t/f] \\ \text{case } \text{tt} \text{ of } \text{tt} \mapsto u; \text{ff} \mapsto v & \rightarrow_\iota & u & & & \end{array}$$

where $t[u/x]$ denotes the usual (capture-free) notion of substitution on terms (replace x by u in t). As usual, we let $=_{\beta\iota\mu}$ denote the reflexive-symmetric-transitive closure of $\rightarrow_{\beta\iota\mu}$. In particular, we only allow reduction of `letrec` when the argument has a constructor $C \in \{\text{tt}, \text{ff}, 0, S, [], ::\}$ in head position.

Judgments are of the form $\Gamma \vdash t : \tau$, where Γ is a set of typing declarations of the form $x : \sigma$, such that variables are declared at most once. The typing rules are standard, except for recursive functions. In this case, the typing rule requires that the domain of the recursive function is an inductive type (booleans, naturals, or lists here) and that the body of the recursive definition `letrec f x = e` satisfies a predicate $\mathcal{D}ef(f, x, e)$ which ensures that all recursive calls are performed on smaller arguments. The typing rule for recursive definitions is thus:

$$\frac{\Gamma, f : I \rightarrow \sigma, x : I \vdash e : \sigma \quad \mathcal{D}ef(f, x, e) \quad I \in \{\mathbb{N}, \text{list}_\tau\}}{\Gamma \vdash \text{letrec } f x = e : I \rightarrow \sigma}$$

The other rules are standard. We give set-theoretical semantics to this system. For each type τ , its interpretation $\llbracket \tau \rrbracket$ is the set of its values:

$$\llbracket \mathbb{B} \rrbracket \triangleq \mathbb{B} \quad \llbracket \mathbb{N} \rrbracket \triangleq \mathbb{N} \quad \llbracket \text{list}_\tau \rrbracket \triangleq \text{list}_{\llbracket \tau \rrbracket} \quad \llbracket \sigma \rightarrow \tau \rrbracket \triangleq \llbracket \sigma \rrbracket \rightarrow \llbracket \tau \rrbracket$$

where $\llbracket \sigma \rrbracket \rightarrow \llbracket \tau \rrbracket$ is the set of total functions with domain $\llbracket \sigma \rrbracket$ and codomain $\llbracket \tau \rrbracket$.

A valuation ρ for a context Γ (written $\rho \models \Gamma$) is a partial map such that $\rho(x) \in \llbracket \tau \rrbracket$ whenever $(x : \tau) \in \Gamma$. Given a valuation ρ for Γ , every term t such that $\Gamma \vdash t : \tau$ has an interpretation $\langle t \rangle_\rho$:

$$\begin{aligned} \langle x \rangle_\rho &\triangleq \rho(x) & \langle \langle t, u \rangle \rangle_\rho &\triangleq \langle \langle t \rangle_\rho, \langle u \rangle_\rho \rangle & \langle \pi_i t \rangle_\rho &\triangleq \pi_i(\langle t \rangle_\rho) & \langle \lambda x : \tau. t \rangle_\rho &\triangleq \lambda v : \llbracket \tau \rrbracket. \langle x \rangle_\rho[\langle v \rangle_\rho / v] \\ \langle c \rangle_\rho &\triangleq c & \langle S t \rangle_\rho &\triangleq S \langle t \rangle_\rho & \langle t :: u \rangle_\rho &\triangleq \langle t \rangle_\rho :: \langle u \rangle_\rho \\ \langle \text{case } t \text{ of } [] \mapsto u; - :: - \mapsto v \rangle_\rho &\triangleq \text{case } \langle t \rangle_\rho \text{ of } [] \mapsto \langle u \rangle_\rho; - :: - \mapsto \langle v \rangle_\rho & \langle \text{letrec } f \ x = t \rangle_\rho &\triangleq F \end{aligned}$$

In the case of $\text{letrec } f \ x = e$, we require that F is the unique solution of the fixpoint equation extracted from the recursive definition—existence and unicity of the solution follows from the validity of the $\text{Def}(f, x, e)$ predicate.

The interpretation of well-typed terms is sound. Moreover, the interpretation equates convertible terms. (This extends to η -conversion.)

THEOREM 2.1 (SOUNDNESS OF SET-THEORETIC SEMANTICS).

- If $\Gamma \vdash t : \tau$ and $\rho \models \Gamma$, then $\langle t \rangle_\rho \in \llbracket \tau \rrbracket$.
- If $\Gamma \vdash t : \tau$ and $\Gamma \vdash u : \tau$ and $t =_{\beta\mu} u$ and $\rho \models \Gamma$, then $\langle t \rangle_\rho = \langle u \rangle_\rho$.

3 HIGHER-ORDER LOGIC

Higher-Order Logic is defined as a calculus in natural deduction for a predicate logic over simply-typed terms. More specifically, its assertions are formulae over typed terms, and are defined by the following grammar:

$$\phi ::= P(t_1, \dots, t_n) \mid \top \mid \perp \mid \phi \wedge \phi \mid \phi \vee \phi \mid \phi \Rightarrow \phi \mid \forall x : \tau. \phi \mid \exists x : \tau. \phi$$

where P ranges over basic predicates (as usual, we will often omit the types of bound variables, when clear from the context). We assume that predicates come equipped with an axiomatization. For instance, the predicate $\text{All}(l, \lambda x. \phi)$ is defined to capture lists whose elements satisfies ϕ . This can be defined axiomatically:

$$\text{All}([], \lambda x. \phi) \quad \forall h t. \text{All}(t, \lambda x. \phi) \Rightarrow \phi(h) \Rightarrow \text{All}(h :: t, \lambda x. \phi)$$

We use the notation $\lambda x. \phi$ for simplicity, although we have not introduced formally a type for propositions—adding such a type is straightforward and orthogonal to our work: another alternative would be to use axiom scheme.

We define well-typed assertions using a judgment of the form $\Gamma \vdash \phi$. The typing rules are standard. A HOL judgment is then of the form $\Gamma \mid \Psi \vdash \phi$, where Γ is a simply typed context, Ψ is a set of assertions, and ϕ is an assertion, and such that $\Gamma \vdash \psi$ for every $\psi \in \Psi$, and $\Gamma \vdash \phi$. The rules of the logic are given in Figure 1, where the notation $\phi[t/x]$ denotes the (capture-free) substitution of x by t in ϕ . In addition to the usual rules for equality, implication and universal quantification, there are rules for inductive types (only the rules for lists are displayed; similar rules exist for booleans and natural numbers): the rule [LIST] models the induction principle for lists; the rules [NC] and [CONS] formalise injectivity and non overlap of constructors. A rule for strong induction [SLIST] can be considered as well, and is in fact derivable from simple induction.

Higher-Order Logic inherits a set-theoretical interpretation from its underlying simply-typed λ -calculus. We assume given for each predicate P an interpretation $\llbracket P \rrbracket$ which is compatible with the type of P and its axioms.

$\frac{\phi \in \Psi}{\Gamma \mid \Psi \vdash \phi}$ AX	$\frac{\Gamma \vdash t : \tau \quad \Gamma \vdash t' : \tau \quad t =_{\beta\mu} t'}{\Gamma \mid \Psi \vdash t = t'}$ CONV	$\frac{\Gamma \mid \Psi \vdash \phi[t/x] \quad \Gamma \mid \Psi \vdash t = u}{\Gamma \mid \Psi \vdash \phi[u/x]}$ SUBST
$\frac{\Gamma \mid \Psi, \psi \vdash \phi}{\Gamma \mid \Psi \vdash \psi \Rightarrow \phi} \Rightarrow_1$	$\frac{\Gamma \mid \Psi \vdash \psi \Rightarrow \phi \quad \Gamma \mid \Psi \vdash \psi}{\Gamma \mid \Psi \vdash \phi} \Rightarrow_E$	$\frac{\Gamma, x : \sigma \mid \Psi \vdash \phi}{\Gamma \mid \Psi \vdash \forall x : \sigma. \phi} \forall_1$
$\frac{\Gamma \mid \Psi \vdash \forall x : \sigma. \phi \quad \Gamma \vdash t : \sigma}{\Gamma \mid \Psi \vdash \phi[t/x]} \forall_E$	$\frac{}{\Gamma \mid \Psi \vdash \top} \top_1$	$\frac{\Gamma \mid \Psi \vdash \perp \quad \Gamma \vdash \phi}{\Gamma \mid \Psi \vdash \phi} \perp_E$
$\frac{\Gamma \mid \Psi \vdash \phi[\langle \rangle / l] \quad \Gamma, h : \tau, t : \text{list}_\tau \mid \Psi, \phi \vdash \phi[h :: t/t]}{\Gamma \mid \Psi \vdash \forall t : \text{list}_\sigma. \phi}$ LIST		$\frac{\Gamma \vdash h :: t : \text{list}_\tau}{\Gamma \mid \emptyset \vdash \langle \rangle \neq h :: t} \text{NC}$
$\frac{\Gamma \mid \Psi \vdash t_1 :: t_2 = t'_1 :: t'_2}{\Gamma \mid \Psi \vdash t_i = t'_i} \text{CONS}_i$	$\frac{\Gamma, t : \text{list}_\tau \mid \Psi, \forall u : \text{list}_\tau. u < t \Rightarrow \phi[u/t] \vdash \phi}{\Gamma \mid \Psi \vdash \forall t : \text{list}_\tau. \phi}$ SLIST	

Fig. 1. Selected rules for HOL

The interpretation of assertions is then defined in the usual way. Specifically, the interpretation $\langle \phi \rangle_\rho$ of an assertion ϕ w.r.t. a valuation ρ includes the clauses:

$$\begin{aligned} \langle P(t_1, \dots, t_n) \rangle_\rho &\triangleq (\llbracket t_1 \rrbracket_\rho, \dots, \llbracket t_n \rrbracket_\rho) \in \llbracket P \rrbracket & \langle \top \rangle_\rho &\triangleq \tilde{\top} & \langle \perp \rangle_\rho &\triangleq \tilde{\perp} & \langle \phi_1 \wedge \phi_2 \rangle_\rho &\triangleq \langle \phi_1 \rangle_\rho \tilde{\wedge} \langle \phi_2 \rangle_\rho \\ \langle \phi_1 \Rightarrow \phi_2 \rangle_\rho &\triangleq \langle \phi_1 \rangle_\rho \tilde{\Rightarrow} \langle \phi_2 \rangle_\rho & \langle \forall x : \tau. \phi \rangle_\rho &\triangleq \tilde{\forall} v. v \in \llbracket \tau \rrbracket \Rightarrow \langle \phi \rangle_{\rho[v/x]} \end{aligned}$$

Higher-order logic is sound with respect to this semantics.

THEOREM 3.1 (SOUNDNESS OF SET-THEORETICAL SEMANTICS). *If $\Gamma \mid \Psi \vdash \phi$, then for every valuation $\rho \models \Gamma$, $\bigwedge_{\psi \in \Psi} \langle \psi \rangle_\rho$ implies $\langle \phi \rangle_\rho$.*

In particular, higher-order logic is consistent, i.e. there is no derivation of $\Gamma \mid \emptyset \vdash \perp$ for any Γ .

4 UNARY HIGHER-ORDER LOGIC

As a stepping stone towards Relational Higher-Order Logic, we define Unary Higher-Order Logic (UHOL). UHOL retains the flavor of refinement types, but dissociates typing from assertions; judgments of UHOL are of the form:

$$\Gamma \mid \Psi \vdash t : \tau \mid \phi$$

where a distinguished variable r , which doesn't appear in Γ , may appear (free) in ϕ as a synonym of t . A judgment is well-formed if t has type τ , Ψ is a valid set of assertions in the context Γ , and ϕ is a valid assertion in the context $\Gamma, r : \tau$. Figure 2 presents selected typing rules. The [ABS] rule allows proving formulas that refer to λ -abstractions, expressing that if the argument satisfies a precondition ϕ' , then the result satisfies a postcondition ϕ . The [APP] rule, dually, proves a condition ϕ on an application $t u$ provided that the argument u satisfies the precondition ϕ' of the function t . The [VAR] rule introduces a variable from the context with a formula proven in HOL. Rules for constants (e.g. [NIL]) work in the same way. Rule [CONS] proves a formula ϕ for a non-empty list, provided that ϕ is a consequence of some conditions ϕ', ϕ'' on its head and its tail. Rule [PAIR] allows the construction of judgments about pairs in a similar manner. The rules [PROJ]_i prove judgments about the projections of a pair. The rule [SUB] (subsumption) allows strengthening the assumed assertions Ψ and weakening the concluding assertion ϕ . It generates a HOL proof obligation. The rule [CASE] can be used

$\frac{\Gamma \vdash x : \sigma \quad \Gamma \mid \Psi \vdash \phi[x/\mathbf{r}]}{\Gamma \mid \Psi \vdash x : \sigma \mid \phi} \text{ VAR}$	$\frac{\Gamma, x : \tau \mid \Psi, \phi' \vdash t : \sigma \mid \phi}{\Gamma \mid \Psi \vdash \lambda x : \tau. t : \tau \rightarrow \sigma \mid \forall x. \phi' \Rightarrow \phi[\mathbf{r} x/\mathbf{r}]} \text{ ABS}$
$\frac{\Gamma \mid \Psi \vdash t : \tau \rightarrow \sigma \mid \forall x. \phi'[x/\mathbf{r}] \Rightarrow \phi[\mathbf{r} x/\mathbf{r}] \quad \Gamma \mid \Psi \vdash u : \tau \mid \phi'}{\Gamma \mid \Psi \vdash t u : \sigma \mid \phi[u/x]} \text{ APP}$	$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\square/\mathbf{r}]}{\Gamma \mid \Psi \vdash \square : \text{list}_\sigma \mid \phi} \text{ NIL}$
$\frac{\Gamma \mid \Psi \vdash h : \sigma \mid \phi' \quad \Gamma \mid \Psi \vdash t : \text{list}_\sigma \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall xy. \phi'[x/\mathbf{r}] \Rightarrow \phi''[y/\mathbf{r}] \Rightarrow \phi[x :: y/\mathbf{r}]}{\Gamma \mid \Psi \vdash h :: t : \text{list}_\sigma \mid \phi} \text{ CONS}$	$\frac{\Gamma \mid \Psi \vdash t : \sigma \times \tau \mid \phi[\pi_i(\mathbf{r})/\mathbf{r}]}{\Gamma \mid \Psi \vdash \pi_i(t) : \sigma \mid \phi} \text{ PROJ}_i$
$\frac{\Gamma \mid \Psi \vdash t : \sigma \mid \phi' \quad \Gamma \mid \Psi \vdash u : \tau \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall xy. \phi'[x/\mathbf{r}] \Rightarrow \phi''[y/\mathbf{r}] \Rightarrow \phi[\langle x, y \rangle/\mathbf{r}]}{\Gamma \mid \Psi \vdash \langle t, u \rangle : \sigma \times \tau \mid \phi} \text{ PAIR}$	$\frac{\Gamma \mid \Psi \vdash t : \sigma \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \phi'[t/\mathbf{r}] \Rightarrow \phi[t/\mathbf{r}]}{\Gamma \mid \Psi \vdash t : \sigma \mid \phi} \text{ SUB}$
$\frac{\Gamma \vdash l : \text{list}_\tau \quad \Gamma \mid \Psi, l = [] \vdash u : \sigma \mid \phi \quad \Gamma \mid \Psi \vdash v : \tau \rightarrow \text{list}_\tau \rightarrow \sigma \mid \forall ht. l = h :: t \Rightarrow \phi[\mathbf{r} h t/\mathbf{r}]}{\Gamma \mid \Psi \vdash \text{case } l \text{ of } [] \mapsto u; _ :: _ \mapsto v : \sigma \mid \phi} \text{ LISTCASE}$	
$\frac{\mathcal{D}ef(f, x, e) \quad \Gamma, x : I, f : I \rightarrow \sigma \mid \Psi, \phi', \forall m. m < x \Rightarrow \phi'[m/x] \Rightarrow \phi[m/x][f m/\mathbf{r}] \vdash e : \sigma \mid \phi}{\Gamma \mid \Psi \vdash \text{letrec } f x = e : I \rightarrow \sigma \mid \forall x. \phi' \Rightarrow \phi[\mathbf{r} x/\mathbf{r}]} \text{ LETREC}$	
where $I \in \{\mathbb{N}, \text{list}_\tau\}$	

Fig. 2. Unary Higher-Order Logic rules

for a case analysis over the constructor of a term. Finally, the rule [LETREC] supports inductive reasoning about recursive definitions. Recall that the domain of a recursive definition is an inductive type, for which a natural notion of size exists. If, assuming that a proposition holds for all elements smaller than the argument, we can prove that the proposition holds for the body, then the proposition must hold as well for the function. Furthermore, we require that the function we are verifying satisfies the predicate $\mathcal{D}ef(f, x, i)$, as was the case in HOL. The induction is performed over the $<$ order, which varies depending on the type of the argument.

We now discuss the main meta-theoretic results of UHOL. The following result establishes that every HOL judgment can be proven in UHOL and viceversa.

Theorem 1 (Equivalence with HOL). For every context Γ , simple type σ , term t , set of assertions Ψ and assertion ϕ , the following are equivalent:

- $\Gamma \mid \Psi \vdash t : \sigma \mid \phi$
- $\Gamma \mid \Psi \vdash \phi[t/\mathbf{r}]$

The forward implication follows by induction on the derivation of $\Gamma \mid \Psi \vdash t : \sigma \mid \phi$. The reverse implication is immediate from the rule [SUB] and the observation that $\Gamma \mid \Psi \vdash t : \sigma \mid \top$ whenever t is a term of type σ .

We lift the HOL semantics to UHOL. Terms, types and formulas are interpreted as before. Additionally, for every valuation ρ let $\rho[v/x]$ denote its unique extension ρ' such that $\rho'(y) = v$ if $x = y$ and $\rho'(y) = \rho(y)$ otherwise. The following corollary states the soundness of UHOL.

Corollary 2 (Set-theoretical soundness and consistency). If $\Gamma \mid \Psi \vdash t : \sigma \mid \phi$, then for every valuation $\rho \models \Gamma, \bigwedge_{\psi \in \Psi} (\psi)_\rho$ implies $(\phi)_\rho[\langle t \rangle_\rho/\mathbf{r}]$. In particular, there is no proof of $\Gamma \mid \emptyset \vdash t : \sigma \mid \perp$ in UHOL.

Next, we prove subject conversion for UHOL. The result follows immediately from Theorem 1 and subject conversion of HOL, which is itself a direct consequence of the [CONV] and [SUBST] rules.

Corollary 3 (Subject conversion). Assume that $t =_{\beta, \mu} t'$ and $\Gamma \mid \Psi \vdash t : \sigma \mid \phi$. If $\Gamma \vdash t' : \sigma$ then $\Gamma \mid \Psi \vdash t' : \sigma \mid \phi$.

5 RELATIONAL HIGHER-ORDER LOGIC

Relational Higher-Order Logic (RHOL) extends UHOL's separation of assertions from types to a relational setting. Formally, RHOL is a relational type system which manipulates judgments of the form

$$\Gamma \mid \Psi \vdash t_1 : \tau_1 \sim t_2 : \tau_2 \mid \phi$$

which combine a typing judgment for a pair of PCF terms and permit reasoning about the relation between them. We therefore require that t_1 and t_2 respectively have types τ_1 and τ_2 in Γ . Well-formedness of the judgment requires Ψ to be a valid set of assertions in Γ and ϕ to be a valid assertion in $\Gamma, \mathbf{r}_1 : \tau_1, \mathbf{r}_2 : \tau_2$, where the special variables \mathbf{r}_1 and \mathbf{r}_2 are used as synonyms for t_1 and t_2 in ϕ . The informal meaning of the judgment is the expected one: If the variables in Γ are related by the assertions in Ψ , then the terms t_1 and t_2 are related by the assertion ϕ .

5.1 Proof rules

The type system combines two-sided rules (Figure 3), which apply when the two terms have the same top-level constructors and one-sided rules (Figure 5), which analyze either one of the two terms. For instance, the [APP] rule applies when the two terms are applications, and requires that the functions t_1 and t_2 relate and the arguments u_1 and u_2 relate. Specifically, t_1 and t_2 must map values related by ϕ' to values related by ϕ , and u_1 and u_2 must be related by ϕ' . The [ABS] rule is dual. The [PAIR] rule requires that the left and right components of a pair relate independently (a stronger rule is discussed at the end of the section). The [PROJ]_i rules require in their premise an assertion that only refers to the first or the second component of the pair. The rules for lists require that the two lists are either both empty, or both non-empty. The rule [CONS] requires that the two heads and the two tails relate independently. The [CASE] rule derives judgements about two case constructs when the terms over which the matching happens reduce to the same branch (i.e. have the same constructor) on both sides.

In contrast, one-sided typing rules only analyze one term; therefore, they come in two flavours: left rules (shown in Figure 5) and right rules (omitted but similar). Rule [ABS-L] considers the case where the left term is a λ -abstraction, and requires the body of the abstraction to be related to the right term u_2 whenever the argument (on the left side) satisfies a non-relational assertion ϕ' . Dually, rule [APP-L] considers the case where the left term is of the form $t_1 u_1$, and t_1 is related to the right term u_2 ; specifically, t_1 should map every value satisfying ϕ' to a value satisfying ϕ . Moreover, u_1 should satisfy ϕ' . Since ϕ' is a non-relational assertion, we demand that it can be established using UHOL, not RHOL. One-sided rules for pairs and lists follow a similar pattern.

In addition, RHOL has structural rules (Figure 4). The rule [SUB] can be used for strengthening the assumed assertions and for weakening the concluding assertion; the ensuing side-conditions are discharged in HOL. Other structural rules assimilate rules of HOL. For instance, if we can prove two different assertions for the same terms we can prove the conjunction of the assertions ([\wedge_I]). Other logical connectives have similar rules. Finally, the rule [UHOL-L] (and a dual rule [UHOL-R]) allow falling back to UHOL in a RHOL proof.

Rules [LETREC] and [LETREC-L] introduce recursive function definitions (Figure 6). These rules allow for a style of reasoning very similar to strong induction. If, assuming that the function's specification holds for all smaller arguments, we can prove that the functions specification holds, then the specification must hold for all arguments. We require that the two functions we are relating satisfy the predicates $\mathcal{D}ef(f_i, x_i, e_i)$, as was the

$\frac{\Gamma, x_1 : \tau_1, x_2 : \tau_2 \mid \Psi, \phi' \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \lambda x_1 : \tau_1. t_1 : \tau_1 \rightarrow \sigma_1 \sim \lambda x_2 : \tau_2. t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1][\mathbf{r}_2 \ x_2 / \mathbf{r}_2]}$	ABS
$\frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1][\mathbf{r}_2 \ x_2 / \mathbf{r}_2] \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi'}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi[u_1 / x_1][u_2 / x_2]}$	APP
$\frac{\Gamma \vdash x_1 : \sigma_1 \quad \Gamma \vdash x_2 : \sigma_2 \quad \Gamma \mid \Psi \vdash \phi[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash x_1 : \sigma_1 \sim x_2 : \sigma_2 \mid \phi} \text{ VAR}$	TRUE
$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\mathbf{tt} / \mathbf{r}_1][\mathbf{tt} / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \mathbf{tt} : \mathbb{B} \sim \mathbf{tt} : \mathbb{B} \mid \phi}$	TRUE
$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\mathbf{[]} / \mathbf{r}_1][\mathbf{[]} / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \mathbf{[]} : \text{list}_{\sigma_1} \sim \mathbf{[]} : \text{list}_{\sigma_2} \mid \phi} \text{ NIL}$	NIL
$\frac{\Gamma \mid \Psi \vdash h_1 : \sigma_1 \sim h_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash t_1 : \text{list}_{\sigma_1} \sim t_2 : \text{list}_{\sigma_2} \mid \phi''}{\Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1 y_2. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi''[y_1 / \mathbf{r}_1][y_2 / \mathbf{r}_2] \Rightarrow \phi[x_1 :: y_1 / \mathbf{r}_1][x_2 :: y_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash h_1 :: t_1 : \text{list}_{\sigma_1} \sim h_2 :: t_2 : \text{list}_{\sigma_2} \mid \phi}$	CONS
$\frac{\Gamma \mid \Psi \vdash l_1 : \text{list}_{\tau_1} \sim l_2 : \text{list}_{\tau_2} \mid \mathbf{r}_1 = \mathbf{[]} \Leftrightarrow \mathbf{r}_2 = \mathbf{[]} \quad \Gamma \mid \Psi, l_1 = \mathbf{[]}, l_2 = \mathbf{[]} \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \quad \Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \forall h_1 h_2 t_1 t_2. l_1 = h_1 :: t_1 \Rightarrow l_2 = h_2 :: t_2 \Rightarrow \phi[\mathbf{r}_1 \ h_1 \ t_1 / \mathbf{r}_1][\mathbf{r}_2 \ h_2 \ t_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \text{case } l_1 \text{ of } \mathbf{[]} \mapsto u_1; _ :: _ \mapsto v_1 : \sigma_1 \sim \text{case } l_2 \text{ of } \mathbf{[]} \mapsto u_2; _ :: _ \mapsto v_2 : \sigma_2 \mid \phi}$	LISTCASE
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi''}{\Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1 y_2. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi''[y_1 / \mathbf{r}_1][y_2 / \mathbf{r}_2] \Rightarrow \phi[\langle x_1, y_1 \rangle / \mathbf{r}_1][\langle x_2, y_2 \rangle / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \langle t_1, u_1 \rangle : \sigma_1 \times \tau_1 \sim \langle t_2, u_2 \rangle : \sigma_2 \times \tau_2 \mid \phi}$	PAIR
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \times \tau_2 \mid \phi[\pi_i(\mathbf{r}_1) / \mathbf{r}_1][\pi_i(\mathbf{r}_2) / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \pi_i(t_1) : \sigma_1 \sim \pi_i(t_2) : \sigma_2 \mid \phi} \text{ PROJ}_i$	PROJ _i

Fig. 3. Two-sided rules

$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \phi'[t_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2] \Rightarrow \phi[t_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{ SUB}$	SUB
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi \quad \Gamma \mid \Psi \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi'}{\Gamma \mid \Psi \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi \wedge \phi'} \wedge_1$	\Rightarrow_1
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \mid \phi[\mathbf{r} / \mathbf{r}_1][t_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_1 \mid \phi} \text{ UHOL-L}$	UHOL-L

Fig. 4. Structural rules

case in HOL and UHOL. The induction is performed over the order $(a, b) < (c, d)$, which holds whenever both $a \leq b$ and $c \leq d$, and at least one of the inequalities is strict.

$$\begin{array}{c}
 \frac{\Gamma, x_1 : \tau_1 \mid \Psi, \phi' \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \lambda x_1 : \tau_1. t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall x_1. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1]} \text{ABS-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim u_2 : \sigma_2 \mid \forall x_1. \phi'[x_1 / \mathbf{r}_1] \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1] \quad \Gamma \mid \Psi \vdash u_1 : \sigma_1 \mid \phi'[u_1 / x_1]}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi} \text{APP-L} \\
 \\
 \frac{\phi[x_1 / \mathbf{r}_1] \in \Psi \quad \mathbf{r}_2 \notin FV(\phi) \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash x_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{VAR-L} \quad \frac{\Gamma \mid \Psi \vdash \phi[\mathbf{r}_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2] \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash [] : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi} \text{NIL-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash h_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash t_1 : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi''[y_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi[x_1 :: y_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash h_1 :: t_1 : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi} \text{CONS-L} \\
 \\
 \frac{\Gamma \vdash t_1 : \text{list}_{\tau} \quad \Gamma \mid \Psi, t_1 = [] \vdash u_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \quad \Gamma \mid \Psi \vdash v_1 : \tau \rightarrow \text{list}_{\tau} \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall h_1 l_1. t_1 = h_1 :: l_1 \Rightarrow \phi[\mathbf{r}_1 \ h_1 \ l_1 / \mathbf{r}_1]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{LISTCASE-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim t_2 : \sigma_2 \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi''[y_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi[\langle x_1, y_1 \rangle / \mathbf{r}_1][x_2 / \mathbf{r}_2]}{\Gamma \mid \Psi \vdash \langle t_1, u_1 \rangle : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \mid \phi} \text{PAIR-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \mid \phi[\pi_1(\mathbf{r}_1) / \mathbf{r}_1]}{\Gamma \mid \Psi \vdash \pi_1(t_1) : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{PROJ}_1\text{-L}
 \end{array}$$

Fig. 5. One-sided rules

$$\begin{array}{c}
 \frac{\mathcal{D}ef(f_1, x_1, e_1) \quad \mathcal{D}ef(f_2, x_2, e_2) \quad \Gamma, x_1 : I_1, x_2 : I_2, f_1 : I_1 \rightarrow \sigma, f_2 : I_2 \rightarrow \sigma_2 \mid \Psi, \phi', \forall m_1 m_2. (|m_1|, |m_2|) < (|x_1|, |x_2|) \Rightarrow \phi'[m_1 / x_1][m_2 / x_2] \Rightarrow \phi[m_1 / x_1][m_2 / x_2][f_1 \ m_1 / \mathbf{r}_1][f_2 \ m_2 / \mathbf{r}_2] \vdash e_1 : \sigma_1 \sim e_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \text{letrec } f_1 \ x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim \text{letrec } f_2 \ x_2 = e_2 : I_2 \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1][\mathbf{r}_2 \ x_2 / \mathbf{r}_2]} \text{LETREC} \\
 \\
 \frac{\mathcal{D}ef(f_1, x_1, e_1) \quad \Gamma, x_1 : I_1, f_1 : I_1 \rightarrow \sigma \mid \Psi, \phi', \forall m_1. |m_1| < |x_1| \Rightarrow \phi'[m_1 / x_1] \Rightarrow \phi[m_1 / x_1][f_1 \ m_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2] \vdash e_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \text{letrec } f_1 \ x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim t_2 : \sigma_2 \mid \forall x_1. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1]} \text{LETREC-L} \\
 \\
 \text{where } I_1, I_2 \in \{\mathbb{N}, \text{list}_{\tau}\}
 \end{array}$$

Fig. 6. Recursion rules

$$\begin{array}{c}
\frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \tau_2 \rightarrow \sigma_2 \mid \phi[r_1 u_1/r_1][r_2 u_2/r_2]}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi} \text{ APP - FUN} \\
\\
\frac{\Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi[t_1 r_1/r_1][t_2 r_2/r_2]}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi} \text{ APP - ARG} \\
\\
\frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \sim t_2 : \tau_2 \mid \phi[\langle r_1, u_1 \rangle / r_1][\langle r_2, u_2 \rangle / r_2]}{\Gamma \mid \Psi \vdash \langle t_1, u_1 \rangle : \tau_1 \times \sigma_1 \sim \langle t_2, u_2 \rangle : \tau_2 \times \sigma_2 \mid \phi} \text{ PAIR - FST} \\
\\
\frac{\Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \text{list}_{\tau_2} \mid \top \\
\Gamma \mid \Psi, t_1 = [], t_2 = [] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_2 = [] \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim u_2 : \sigma_2 \mid \forall h_1 l_1. t_1 = h_1 :: l_1 \Rightarrow \phi[r_1 h_1 l_1 / r_1] \\
\Gamma \mid \Psi, t_1 = [] \vdash u_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_2. t_2 = h_2 :: l_2 \Rightarrow \phi[r_2 h_2 l_2 / r_2] \\
\Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_1 h_2 l_1 l_2. t_1 = h_1 :: l_1 \Rightarrow t_2 = h_2 :: l_2 \Rightarrow \phi[r_1 h_1 l_1 / r_1][r_2 h_2 l_2 / r_2]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : \sigma_2 \mid \phi} \text{ LLCASE - A}
\end{array}$$

Fig. 7. Some derived rules

5.2 Discussion

Our choice of the rules is guided by the practical considerations of being able to verify examples easily, without specifically aiming for minimality or exhaustiveness. In fact, many of our rules can be derived from others, or reduced to a more elementary form. For instance:

- The structural rules to reason about logical connectives, such as $[\wedge_I]$, can be derived by induction on the length of derivations with the help of $[\text{SUB}]$.
- The $[\text{VAR-L}]$ (similarly, $[\text{NIL-L}]$) rule can be weakened, without affecting the strength of the system,

$$\frac{\phi[x_1/r_1] \in \Psi \quad r_2 \notin FV(\phi)}{\Gamma \mid \Psi \vdash x_1 : \sigma_1 \sim x_2 : \sigma_2 \mid \phi} \text{ VAR-L}$$

- The premise of the $[\text{VAR}]$ rule (and similarly, $[\text{NIL}]$) can be changed to $\phi[x/r] \in \Psi$. We can recover the original rule by one application of $[\text{SUB}]$.
- The rules $[\text{APP-FUN}]$ and $[\text{APP-ARG}]$ in Figure 7 (adapted from Ghani et al. (2016b)) can be derived from the rule $[\text{APP}]$. To derive $[\text{APP-FUN}]$, instantiate ϕ' to $r_1 = u_1 \wedge r_2 = u_2$ in $[\text{APP}]$. To derive $[\text{APP-ARG}]$, we have to prove a trivial condition $\forall x_1 x_2. \phi[t_1 x_1/r_1][t_2 x_2/r_2] \Rightarrow \phi[t_1 x_1/r_1][t_2 x_2/r_2]$ on t_1, t_2 .
- The $[\text{PAIR-L}]$ and $[\text{PAIR-SND}]$ rules in Figure 7 can be derived in a similar way. These rules overcome a limitation of the original $[\text{PAIR}]$ rule, namely, that the relations for the two components of the pair must be independent. $[\text{PAIR-FST}]$ and $[\text{PAIR-SND}]$ allow relating, for instance, pairs of integers $\langle m_1, n_1 \rangle$ and $\langle m_2, n_2 \rangle$ such that $m_1 + n_1 = m_2 + n_2$.
- The $[\text{LLCASE-A}]$ rule can be used to reason about case constructs when the terms over which we discriminate do not necessarily reduce to the same branch. It is equivalent to applying $[\text{CASE-L}]$ followed by $[\text{CASE-R}]$.

5.3 Meta-theory

RHOL retains the expressiveness of HOL, as formalized in the following theorem.

Theorem 4 (Equivalence with HOL). For every context Γ , simple types σ_1 and σ_2 , terms t_1 and t_2 , set of assertions Ψ and assertion ϕ , if $\Gamma \vdash t_1 : \sigma_1$ and $\Gamma \vdash t_2 : \sigma_2$, then the following are equivalent:

- $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$
- $\Gamma \mid \Psi \vdash \phi[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2]$

The proof of the forward implication proceeds by induction on the structure of derivations. The proof of the reverse implication is immediate from the rule [SUB] and the observation that $\Gamma \mid \emptyset \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \top$ whenever t_1 and t_2 are typable terms of types σ_1 and σ_2 respectively.

This immediately entails soundness of RHOL, which is expressed in the following result:

Corollary 5 (Set-theoretical soundness and consistency). If $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$, then for every valuation $\rho \models \Gamma, \bigwedge_{\psi \in \Psi} \langle \psi \rangle_\rho$ implies $\langle \phi \rangle_{\rho[\langle t_1 \rangle_\rho/\mathbf{r}_1], [\langle t_2 \rangle_\rho/\mathbf{r}_2]}$. In particular, there is no proof of $\Gamma \mid \emptyset \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \perp$ for any Γ .

The equivalence also entails subject conversion (and as special cases subject reduction and subject expansion). This follows immediately from subject conversion of HOL (which, as stated earlier, is itself a direct consequence of the [CONV] and [SUBST] rules).

Corollary 6 (Subject conversion). Assume that $t_1 =_{\beta\eta\mu} t'_1$ and $t_2 =_{\beta\eta\mu} t'_2$ and $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$. If $\Gamma \vdash t'_1 : \sigma_1$ and $\Gamma \vdash t'_2 : \sigma_2$ then $\Gamma \mid \Psi \vdash t'_1 : \sigma_1 \sim t'_2 : \sigma_2 \mid \phi$.

Another useful consequence of the equivalence is the admissibility of the transitivity rule.

Corollary 7 (Admissibility of transitivity rule). Assume that:

- $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$
- $\Gamma \mid \Psi \vdash t_2 : \sigma_2 \sim t_3 : \sigma_3 \mid \phi'$

Then, $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_3 : \sigma_3 \mid \phi[t_2/\mathbf{r}_2] \wedge \phi'[t_2/\mathbf{r}_1]$.

Finally, we prove an embedding lemma for UHOL. The proof can be carried by induction on the structure of derivations, or using the equivalence between UHOL and HOL (Theorem 1).

Lemma 8 (Embedding lemma). Assume that:

- $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \mid \phi$
- $\Gamma \mid \Psi \vdash t_2 : \sigma_2 \mid \phi'$

Then $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi[\mathbf{r}_1/\mathbf{r}] \wedge \phi'[\mathbf{r}_2/\mathbf{r}]$.

The embedding is reminiscent of the approach of Beringer and Hofmann (2007) to encode information flow properties in Hoare logic.

6 EMBEDDINGS

In this section, we establish the expressiveness of RHOL and UHOL by embedding several existing refinement type systems (3 relational and 1 non-relational) from a variety of domains. All embeddings share the common idea of *separating* the simple typing information from the more fine-grained refinement information in the translation. We use uniform notation to represent similar ideas across the different embeddings. In particular, we use vertical bars $|\cdot|$ to denote the erasure of a type into a simple type, and floor bars $\lfloor \cdot \rfloor$ to denote the embedding of the refinement of a type in a HOL formula.

For the clarity of exposition, we often present fragments or variants of systems that appear in the literature, notably excluding recursive functions that do not satisfy our well-definedness predicate. Moreover, the embeddings are given for a version of RHOL à la Curry, in which λ -abstractions do not carry the type of their bound variable.

$\frac{\Gamma \vdash \tau}{\Gamma \vdash \tau \leq \tau}$	$\frac{\Gamma \vdash \tau_1 \leq \tau_2 \quad \Gamma \vdash \tau_2 \leq \tau_3}{\Gamma \vdash \tau_1 \leq \tau_3}$	$\frac{\Gamma \vdash \tau_1 \leq \tau_2}{\Gamma \vdash \text{list}_{\tau_1} \leq \text{list}_{\tau_2}}$	$\frac{\Gamma \vdash \{x : \tau \mid \phi\}}{\Gamma \vdash \{x : \tau \mid \phi\} \leq \tau}$
$\frac{\Gamma \vdash \tau \leq \sigma \quad \Gamma, r : \tau \vdash \phi}{\Gamma \vdash \tau \leq \{x : \sigma \mid \phi\}}$		$\frac{\Gamma \vdash \sigma_2 \leq \sigma_1 \quad \Gamma, x : \sigma_2 \vdash \tau_1 \leq \tau_2}{\Gamma \vdash \Pi(x : \sigma_1). \tau_1 \leq \Pi(x : \sigma_2). \tau_2}$	
$\frac{}{\Gamma, x : \tau \vdash x : \tau}$	$\frac{\Gamma, x : \tau \vdash t : \sigma}{\Gamma \vdash \lambda x. t : \Pi(x : \tau). \sigma}$	$\frac{\Gamma \vdash t_1 : \Pi(x : \tau). \sigma \quad \Gamma \vdash t_2 : \tau}{\Gamma \vdash t_1 t_2 : \sigma[t_2/x]}$	
$\frac{\Gamma \vdash t : \text{list}_{\tau} \quad \Gamma \vdash t_1 : \sigma \quad \Gamma \vdash t_2 : \Pi(h : \tau). \Pi(l : \text{list}_{\tau}). \sigma}{\Gamma \vdash \text{case } t \text{ of } [] \mapsto t_1; - :: - \mapsto t_2 : \sigma}$		$\frac{\Gamma \vdash \tau \leq \sigma \quad \Gamma \vdash t : \tau}{\Gamma \vdash t : \sigma}$	
$\frac{\Gamma, x : \tau, f : \Pi(\{y : \tau \mid y < x\}). \sigma[y/x] \vdash t : \sigma \quad \text{Def}(f, x, t)}{\Gamma \vdash \text{letrec } f \ x = t : \Pi(x : \tau). \sigma}$			

Fig. 8. Refinement types rules (subtyping and typing)

6.1 Refinement types

Refinement types (Freeman and Pfenning 1991; Swamy et al. 2016; Vazou et al. 2014) are a variant of simple types where for every basic type τ , there is a type $\{x : \tau \mid \phi\}$ which is inhabited by the elements t of τ that satisfy the logical assertion $\phi[t/x]$. This includes dependent refinements $\Pi(x : \tau). \sigma$, in which the variable x is also bound in the refinement formulas appearing in σ . Here we present a simplified variant of these systems. (Refined) types are defined by the grammar

$$\tau := \mathbb{B} \mid \mathbb{N} \mid \text{list}_{\tau} \mid \{x : \tau \mid \phi\} \mid \Pi(x : \tau). \tau$$

As usual, we shorten $\Pi(x : \tau). \sigma$ to $\tau \rightarrow \sigma$ if $x \notin FV(\sigma)$. We also shorten bindings of the form $x : \{x : \tau \mid \phi\}$ to $\{x : \tau \mid \phi\}$. Typing rules are presented in Figure 8; note that the [LETREC] rule requires that recursive definitions satisfy the well-definedness predicate. Judgments of the form $\Gamma \vdash \tau$ are well-formedness judgments. Judgments of the form $\Gamma \vdash \phi$ are logical judgments; we omit a formal description of the rules, but assume that the logic of assertions is consistent with HOL, i.e. $\Gamma \vdash \phi$ implies $|\Gamma| \mid [\Gamma] \vdash \phi$, where the erasure functions are defined below.

This system can be embedded into UHOL in a straightforward manner. The embedding highlights the relation between these two systems, i.e. between logical assertions embedded in the types (as in refinement types) and logical assertions at the top-level, separate from simple types (as in UHOL). The intuitive idea behind the embedding is therefore to separate refinement assertions from types. Specifically, from every refinement type we can obtain a simple type by repeatedly extracting the type τ from $\{x : \tau \mid \phi\}$. We will denote this extraction by the translation function $|\tau|$:

$$|\mathbb{B}| \triangleq \mathbb{B} \quad |\mathbb{N}| \triangleq \mathbb{N} \quad |\text{list}_{\tau}| \triangleq \text{list}_{|\tau|} \quad |\{x : \tau \mid \phi\}| \triangleq |\tau| \quad |\Pi(x : \tau). \sigma| \triangleq |\tau| \rightarrow |\sigma|$$

Since $|\tau|$ loses refinement information, we define a second translation that extracts the refinement as a logical predicate over a variable x that names the typed expression. This second translation is written $[\tau](x)$.

$$\begin{aligned}
\llbracket \mathbb{B} \rrbracket(x), \llbracket \mathbb{N} \rrbracket(x) &\triangleq \top & \llbracket \text{list}_\tau \rrbracket(x) &\triangleq \text{All}(x, \lambda y. \llbracket \tau \rrbracket(y)) & \llbracket \{y : \tau \mid \phi\} \rrbracket(x) &\triangleq \llbracket \tau \rrbracket(x) \wedge \phi[x/y] \\
&& \llbracket \Pi(x : \tau). \sigma \rrbracket(x) &\triangleq \forall y. \llbracket \tau \rrbracket(y) \Rightarrow \llbracket \sigma \rrbracket(xy)
\end{aligned}$$

The refinement of simple types is trivial. If t is an expression of type $\{x : \tau \mid \phi\}$, then t must satisfy both the refinement formula ϕ and the refinement of τ . If t is an expression of type $\Pi(x : \tau). \sigma$, then it must be the case that for every x satisfying the refinement of τ , $(t \ x)$ satisfies the refinement of σ . The refinement of a list uses the predicate `All`, which as defined in §3, means that all elements of a list satisfy a given formula.

The syntax of assertions and expressions is exactly the same as in HOL, and therefore there is no need for a translation. Embedding of types can be lifted to contexts in the natural way.

$$\llbracket x : \tau, \Gamma \rrbracket \triangleq x : \llbracket \tau \rrbracket, \llbracket \Gamma \rrbracket \qquad \llbracket x : \tau, \Gamma \rrbracket \triangleq \llbracket \tau \rrbracket(x), \llbracket \Gamma \rrbracket$$

To encode judgments, all that remains is to put the previous definitions together. The main result about embedding typing judgments is the following:

Theorem 9. If $\Gamma \vdash t : \tau$ is derivable in the refinement type system, then $\llbracket \Gamma \rrbracket \mid \llbracket \Gamma \rrbracket \vdash t : \llbracket \tau \rrbracket \mid \llbracket \tau \rrbracket(\mathbf{r})$ is derivable in UHOL.

The proof is performed by induction on the structure of derivations, using as helper result the embedding of subtyping judgments into HOL. Since it can be proven by induction that, whenever $\tau \leq \sigma$, the type extractions $\llbracket \tau \rrbracket$ and $\llbracket \sigma \rrbracket$ coincide, all that needs to be checked is that $\llbracket \sigma \rrbracket$ is a consequence of $\llbracket \tau \rrbracket$. This is captured by the following statement.

Theorem 10. If $\Gamma \vdash \tau \leq \sigma$ is derivable in a refinement type system, then $\llbracket \Gamma \rrbracket, x : \llbracket \tau \rrbracket \mid \llbracket \Gamma \rrbracket, \llbracket \tau \rrbracket(x) \vdash \llbracket \sigma \rrbracket(x)$ is derivable in HOL.

Soundness of refinement types w.r.t. the set-theoretic semantics follows immediately from Theorem 9 and the set-theoretic soundness of UHOL (Corollary 2).

6.2 Relational refinement types

Relational refinement types (Barthe et al. 2014, 2015) are a variant of refinement types that can be used to express relational properties via a syntax of the form $\{\mathbf{r} :: \tau \mid \phi\}$ where ϕ is a relational assertion—i.e. it may contain a left and right copy of \mathbf{r} , which are denoted as \mathbf{r}_1 and \mathbf{r}_2 respectively, as well as a left and a right copy of every variable in the context. In this section, we introduce a simple relational refinement type system and establish a type-preserving translation to RHOL—we compare with existing type systems at the end of the paragraph.

The syntax of relational refinement types is given by the grammar:

$$\begin{aligned}
\tau &::= \mathbb{B} \mid \mathbb{N} \mid \tau \rightarrow \tau \\
T, U &::= \tau \mid \text{list}_T \mid \Pi(x :: T). U \mid \{x :: T \mid \phi\}
\end{aligned}$$

Relational refinement types are naturally ordered by a subtyping relation $\Gamma \vdash T \leq U$, where Γ is a sequence of variables declarations of the form $x :: U$.

Typing judgments are of the form $\Gamma \vdash t_1 \sim t_2 :: T$. We present selected typing rules in Figure 9. Note that the form of judgments requires that t_1 and t_2 must have the same simple type, and the typing rules require that t_1 and t_2 have the same structure¹. In the [CASELIST] rule, we require that both terms reduce to the same branch; the case rule for natural numbers is similar. The [LETREC] rule uses (a straightforward adaptation of) the

¹The typing rules displayed in the figure will in fact force t_1 and t_2 to be the same term modulo renaming. This is not the case in existing relational refinement type systems; however, rules that introduce different terms on the right and on the left are very limited; essentially, there is a rule similar to [LLCASE-A], and a rule for reducing in the terms of a judgment.

$$\begin{array}{c}
\text{VAR-RT} \frac{(x : T) \in \Gamma}{\Gamma \vdash x_1 \sim x_2 :: T} \qquad \text{ABS-RT} \frac{\Gamma, x :: T \vdash u_1 \sim u_2 :: U}{\Gamma \vdash \lambda x_1. u_1 \sim \lambda x_2. u_2 :: \Pi(x :: T). U} \\
\text{APP-RT} \frac{\Gamma \vdash t_1 \sim t_2 :: \Pi(x :: T). U \quad \Gamma \vdash u_1 \sim u_2 :: T}{\Gamma \vdash t_1 u_1 \sim t_2 u_2 :: U[u_1/x_1][u_2/x_2]} \qquad \text{NIL} \frac{\Gamma \vdash T}{\Gamma \vdash [] \sim [] :: \text{list}_T} \\
\text{CONS} \frac{\Gamma \vdash h_1 \sim h_2 :: T \quad \Gamma \vdash t_1 \sim t_2 :: \text{list}_T}{\Gamma \vdash h_1 :: t_1 \sim h_2 :: t_2 :: \text{list}_T} \qquad \text{SUB} \frac{\Gamma \vdash t_1 \sim t_2 :: T \quad \Gamma \vdash T \leq U}{\Gamma \vdash t_1 \sim t_2 :: U} \\
\text{LETREC-RT} \frac{\Gamma, x :: T, f :: \Pi(\{y :: T \mid (y_1, y_2) < (x_1, x_2)\}). U[y/x] \vdash t_1 \sim t_2 :: U \quad \Gamma \vdash \Pi(x :: T). U \quad \text{Def}(f, x, t)}{\Gamma \vdash \text{letrec } f_1 x_1 = t_1 \sim \text{letrec } f_2 x_2 = t_2 :: \Pi(x :: T). U} \\
\text{CASELIST} \frac{\Gamma \vdash t_1 = [] \Leftrightarrow t_2 = [] \quad \Gamma \vdash u_1 \sim u_2 :: T \quad \Gamma \vdash v_1 \sim v_2 :: \Pi(h :: \tau). \Pi(t :: \text{list}_\tau). T}{\Gamma \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 :: T}
\end{array}$$

Fig. 9. Relational Typing (Selected Rules)

$\text{Def}(f, x, t)$ predicate from our simply-typed language, and requires that the two recursive definitions perform exactly the same recursive calls.

Subtyping rules are the same as in the unary case, and therefore we refer to Figure 8 for them (allowing their instantiation for relational types T, U as well as unary types σ, τ).

The embedding of refinement types into UHOL can be adapted to the relational setting. From each relational refinement type T we can extract a simple type $|T|$. On the other hand, we can erase every relational refinement type T into a relational formula $\llbracket T \rrbracket$, which is parametrized by two expressions and defined as follows:

$$\begin{aligned}
\llbracket \text{list}_\tau \rrbracket(x_1, x_2) &\triangleq \bigwedge_{i \in \{1, 2\}} \text{All}(x_i, \lambda y. \llbracket \tau \rrbracket(y)) & \llbracket \text{list}_T \rrbracket(x_1, x_2) &\triangleq \text{All2}(x_1, x_2, \lambda y_1. \lambda y_2. \llbracket T \rrbracket(y_1, y_2)) \\
\llbracket \{y : \tau \mid \phi\} \rrbracket(x_1, x_2) &\triangleq \bigwedge_{i \in \{1, 2\}} \llbracket \tau \rrbracket(x_i) \wedge \phi[x_i/y] & \llbracket \{y : T \mid \phi\} \rrbracket(x_1, x_2) &\triangleq \llbracket T \rrbracket(x_1, x_2) \wedge \phi[x_1/y_1][x_2/y_2] \\
\llbracket \Pi(y : \tau). \sigma \rrbracket(x) &\triangleq \bigwedge_{i \in \{1, 2\}} \forall y. \llbracket \tau \rrbracket(y) \Rightarrow \llbracket \sigma \rrbracket(xy) \\
\llbracket \Pi(y :: T). U \rrbracket(x_1, x_2) &\triangleq \forall y_1 y_2. \llbracket T \rrbracket(y_1, y_2) \Rightarrow \llbracket U \rrbracket(x_1 y_1, x_2 y_2)
\end{aligned}$$

The predicate All2 relates two lists elementwise and is defined axiomatically:

$$\text{All2}([], [], \lambda x_1. \lambda x_2. \phi) \quad \forall h_1 h_2 t_1 t_2. \text{All}(t_1, t_2, \lambda x_1. \lambda x_2. \phi) \Rightarrow \phi(h_1, h_2) \Rightarrow \text{All}(h_1 :: t_1, h_2 :: t_2, \lambda x_1. \lambda x_2. \phi)$$

To extend the embedding to contexts, we need to duplicate every variable in them:

$$|x :: T, \Gamma| \triangleq x_1, x_2 : |T|, |\Gamma| \qquad \llbracket x :: T, \Gamma \rrbracket \triangleq \llbracket T \rrbracket(x_1, x_2), \llbracket \Gamma \rrbracket$$

Now we state the main result:

Theorem 11 (Soundness of embedding). If $\Gamma \vdash t_1 \sim t_2 :: T$, then $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t_1 : |T| \sim t_2 : |T| \mid \llbracket T \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$. Also, if $\Gamma \vdash T \leq U$ then $|\Gamma|, x_1, x_2 : |T| \mid \llbracket \Gamma \rrbracket, \llbracket T \rrbracket(x_1, x_2) \vdash \llbracket U \rrbracket(x_1, x_2)$.

PROOF. The proof proceeds by induction on the structure of derivations. \square

Soundness of relational refinement types w.r.t. set-theoretical semantics follows immediately from Theorem 11 and the set-theoretical soundness of RHOL (Corollary 5).

Corollary 12 (Soundness of relational refinement types). If $\Gamma \vdash t_1 \sim t_2 :: T$, then for every valuation $\theta \models \Gamma$ we have $(\llbracket t_1 \rrbracket_\theta, \llbracket t_2 \rrbracket_\theta) \in (\llbracket T \rrbracket)_\theta$.

6.3 Dependency core calculus

The Dependency Core Calculus (DCC) (Abadi et al. 1999) is a higher-order calculus with a type system that tracks data dependencies. DCC was designed as a unifying framework for dependency analysis and it was shown that many other calculi for information flow analysis (Heintze and Riecke 1998; Volpano et al. 1996), binding-time analysis (Hatcliff and Danvy 1997), and program slicing, all of which track dependencies, can be embedded in DCC. Here, we show how a fragment of DCC can be embedded into RHOL. Transitively, the corresponding fragments of all the aforementioned calculi can also be embedded in RHOL. (The fragment of DCC we consider excludes recursive functions. DCC admits general recursive functions, while our definition of RHOL only admits a subset of these. Extending the embedding to recursive functions admitted by RHOL is not difficult.)

DCC is an extension of the simply typed lambda-calculus with a monadic type family $\mathbb{T}_\ell(\tau)$, indexed by *labels* ℓ , which are elements of a lattice. Unlike other uses of monads, DCC's monad does not encapsulate any effects. Instead, its only goal is to track dependence. The type system forces that the result of an expression of type $\mathbb{T}_\ell(\tau)$ can *depend* on an expression of type $\mathbb{T}_{\ell'}(\tau')$ only if $\ell' \sqsubseteq \ell$ in the lattice. Dually, if $\ell' \not\sqsubseteq \ell$, then even if an expression e of type $\mathbb{T}_\ell(\tau)$ mentions a variable x of type $\mathbb{T}_{\ell'}(\tau')$, then e 's result must be *independent* of the substitution provided for x during evaluation.

For simplicity and without any loss of generality, we consider here only a two point lattice $\{L, H\}$ with $L \sqsubset H$. The syntax of DCC's types and expressions is shown below. We use e to denote DCC expressions, to avoid confusion with HOL's expressions.

$$\begin{aligned} \tau & ::= \mathbb{B} \mid \tau \rightarrow \tau \mid \tau \times \tau \mid \mathbb{T}_\ell(\tau) \\ e & ::= x \mid \lambda x. e \mid e_1 e_2 \mid \text{tt} \mid \text{ff} \mid \text{case } e \text{ of tt} \mapsto e_t; \text{ff} \mapsto e_f \mid \langle e_1, e_2 \rangle \mid \pi_1(e) \mid \pi_2(e) \mid \eta_\ell(e) \mid \text{bind}(e_1, x. e_2) \end{aligned}$$

Here, $\eta_\ell(e)$ and $\text{bind}(e_1, x. e_2)$ are respectively the return and bind constructs for the monad $\mathbb{T}_\ell(\tau)$. Typing rules for these two constructs are shown below. Typing rules for the remaining constructs are the standard ones.

$$\frac{\Gamma \vdash e : \tau}{\Gamma \vdash \eta_\ell(e) : \mathbb{T}_\ell(\tau)} \quad \frac{\Gamma \vdash e_1 : \mathbb{T}_\ell(\tau_1) \quad \Gamma, x : \tau_1 \vdash e_2 : \tau_2 \quad \tau_2 \searrow \ell}{\Gamma \vdash \text{bind}(e_1, x. e_2) : \tau_2}$$

The crux of the dependency tracking is the relation $\tau_2 \searrow \ell$ in the premise of the rule for bind. The relation, read “ τ_2 protected at level ℓ ” and defined below, informally means that all primitive (boolean) values extractable from e_2 are protected by a monadic construct of the form $\mathbb{T}_{\ell'}(\tau)$, with $\ell \sqsubseteq \ell'$. Hence, the rule forces that the result obtained by eliminating the type $\mathbb{T}_\ell(\tau_1)$ flow only into types protected at ℓ in this sense.

$$\frac{\ell \sqsubseteq \ell'}{\mathbb{T}_{\ell'}(\tau) \searrow \ell} \quad \frac{\tau \searrow \ell}{\mathbb{T}_{\ell'}(\tau) \searrow \ell} \quad \frac{\tau_1 \searrow \ell \quad \tau_2 \searrow \ell}{\tau_1 \times \tau_2 \searrow \ell} \quad \frac{\tau_2 \searrow \ell}{\tau_1 \rightarrow \tau_2 \searrow \ell}$$

This fragment of DCC has a relational set-theoretic interpretation. For every type τ , we define a carrier set $|\tau|$:

$$|\mathbb{B}| \triangleq \mathbb{B} \quad |\tau_1 \rightarrow \tau_2| \triangleq |\tau_1| \rightarrow |\tau_2| \quad |\tau_1 \times \tau_2| \triangleq |\tau_1| \times |\tau_2| \quad |\mathbb{T}_\ell(\tau)| \triangleq |\tau|$$

Next, every type τ is interpreted as a lattice-indexed family of relations $\lfloor \tau \rfloor_a \subseteq |\tau| \times |\tau|$. The role of the lattice element a is that it defines what can be *observed* in the system. Specifically, an expression of type $\mathbb{T}_\ell(\tau)$ can be observed only if $\ell \sqsubseteq a$. When $\ell \not\sqsubseteq a$, expressions of type $\mathbb{T}_\ell(\tau)$ look like “black-boxes”. Technically, we force $\lfloor \mathbb{T}_\ell(\tau) \rfloor_a = |\tau| \times |\tau|$ when $\ell \not\sqsubseteq a$. DCC’s typing rules are sound with respect to this model. The soundness implies that if $\ell \not\sqsubseteq \ell'$ and $x : \mathbb{T}_\ell(\mathbb{B}) \vdash e : \mathbb{T}_{\ell'}(\mathbb{B})$, then for $e_1, e_2 : \mathbb{T}_\ell(\mathbb{B})$, $e[e_1/x]$ and $e[e_2/x]$ are equal booleans in the set-theoretic model. This result, called noninterference, formalizes that DCC’s dependency tracking is correct.

To translate DCC to RHOL, we actually embed this set-theoretic model in RHOL. We start by defining an erasing translation, $\lfloor \tau \rfloor$, from DCC’s types into RHOL’s simple types. This translation is exactly the same as the definition of carrier sets shown above, except that we treat \times and \rightarrow as RHOL’s syntactic type constructs instead of set-theoretic constructs. Next, we define an erasure of terms:

$$\begin{aligned} |\text{tt}| &\triangleq \text{tt} & |\text{ff}| &\triangleq \text{ff} & |\text{case } e \text{ of } \text{tt} \mapsto e_t; \text{ff} \mapsto e_f| &\triangleq \text{case } |e| \text{ of } \text{tt} \mapsto |e_t|; \text{ff} \mapsto |e_f| & |x| &\triangleq x \\ |\lambda x. e| &\triangleq \lambda x. |e| & |e_1 \ e_2| &\triangleq |e_1| \ |e_2| & |\langle e_1, e_2 \rangle| &\triangleq \langle |e_1|, |e_2| \rangle & |\pi_1(e)| &\triangleq \pi_1(|e|) & |\pi_2(e)| &\triangleq \pi_2(|e|) \\ & & |\eta_\ell(e)| &\triangleq |e| & |\text{bind}(e_1, x. e_2)| &\triangleq (\lambda x. |e_2|) |e_1| \end{aligned}$$

It is fairly easy to see that if $\vdash e : \tau$ in DCC, then $\vdash |e| : |\tau|$. Next, we define the lattice-indexed family of relations $\lfloor \tau \rfloor_a$ in HOL. For technical convenience, we write the relations as logical assertions, indexed by variables x, y representing the two terms to be related.

$$\begin{aligned} \lfloor \mathbb{B} \rfloor_a(x, y) &\triangleq (x = \text{tt} \wedge y = \text{tt}) \vee (x = \text{ff} \wedge y = \text{ff}) & \lfloor \tau_1 \rightarrow \tau_2 \rfloor_a(x, y) &\triangleq \forall v, w. \lfloor \tau_1 \rfloor_a(v, w) \Rightarrow \lfloor \tau_2 \rfloor_a(x \ v, y \ w) \\ \lfloor \tau_1 \times \tau_2 \rfloor_a(x, y) &\triangleq \lfloor \tau_1 \rfloor_a(\pi_1(x), \pi_1(y)) \wedge \lfloor \tau_2 \rfloor_a(\pi_2(x), \pi_2(y)) & \lfloor \mathbb{T}_\ell(\tau) \rfloor_a(x, y) &\triangleq \begin{cases} \lfloor \tau \rfloor_a(x, y) & \ell \sqsubseteq a \\ \top & \ell \not\sqsubseteq a \end{cases} \end{aligned}$$

The most important clause is the last one: When $\ell \not\sqsubseteq a$, any two x, y are in the relation $\lfloor \mathbb{T}_\ell(\tau) \rfloor_a$. This generalizes to all protected types in the following sense.

Lemma 13. If $\ell \not\sqsubseteq a$ and $\tau \searrow \ell$, then $\vdash \forall x, y. (\lfloor \tau \rfloor_a(x, y) \equiv \top)$ in HOL.

The translations extend to contexts as follows:

$$\begin{aligned} |x^1 : \tau_1, \dots, x^n : \tau_n| &\triangleq x_1^1 : |\tau_1|, x_2^1 : |\tau_1|, \dots, x_1^n : |\tau_n|, x_2^n : |\tau_n| \\ |x^1 : \tau_1, \dots, x^n : \tau_n|_a &\triangleq \lfloor \tau_1 \rfloor_a(x_1^1, x_2^1), \dots, \lfloor \tau_n \rfloor_a(x_1^n, x_2^n) \end{aligned}$$

The following theorem states that the whole translation is sound: It preserves well-typedness. In the statement of the theorem, $|e|_1$ and $|e|_2$ replace each variable x in $|e|$ with x_1 and x_2 , respectively.

Theorem 14 (Soundness of embedding). If $\Gamma \vdash e : \tau$ in DCC, then for all $a \in \{L, H\}$: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$.

DCC’s noninterference theorem is a corollary of this theorem and the soundness of RHOL in set theory.

6.4 Relational cost

RelCost (Çiçek et al. 2017) is a relational refinement type-and-effect system designed to reason about relative cost—the difference in the execution costs of two similar programs or of two runs of the same program on two different inputs. RelCost combines reasoning about the maximum and minimum costs of a single program with relational reasoning about the relative cost of two programs. RelCost is based on the observation that relational reasoning about structurally related expressions can improve precision in reasoning about the relative cost, but if this approach fails one can always fall back to establishing an upper bound on the relative cost the difference of the maximum cost of one program and the minimum cost of the other. Here, we show how a fragment of

RelCost can be embedded into RHOL. Similar to what we did for DCC, to just convey the main intuition, we consider a fragment of RelCost excluding recursive functions. The syntax of RelCost is based on two sorts of types:

$$\begin{aligned} A & ::= \mathbb{N} \mid \text{list}_A[n] \mid A \xrightarrow{\text{exec}(k,l)} A \mid \forall i \stackrel{\text{exec}(k,l)}{::} S. A & \text{(unary types)} \\ \tau & ::= \mathbb{N}_r \mid \text{list}_\tau[n]^\alpha \mid \tau \xrightarrow{\text{diff}(k)} \tau \mid \forall i \stackrel{\text{diff}(k)}{::} S. \tau \mid UA \mid \square \tau & \text{(relational types)} \end{aligned}$$

Unary types are used to type one program and they are mostly standard except for the effect annotation $\text{exec}(k, l)$ on arrow types and universally quantified types representing the min and max cost k and l of the body of the closure, respectively. Relational types ascribe two programs, so they are interpreted as pairs of expressions. In relational types, arrow types and universally quantified types have an effect annotation $\text{diff}(k)$ representing the relative cost k of the two closures. Besides, the superscript α refines list types with the number of elements that can differ in two lists. The type UA is the weakest relation over elements of the unary type A , i.e. it can be used to type two arbitrary terms, while the type $\square \tau$ is the diagonal subrelation of τ , i.e. it can be used to type only two terms that are equal. There are two kinds of typing judgments, unary and relational:

$$\Delta; \Phi; \Omega \vdash_k^l t : A \quad \Delta; \Phi; \Gamma \vdash t_1 \ominus t_2 \lesssim l : \tau$$

The unary judgment states that the execution cost of t is lower bounded by k and upper bounded by l , and the expression t has the unary type A . The relational judgment states that the relative cost of t_1 with respect to t_2 is upper bounded by l and the two expressions have the relational type τ . Here Ω is a unary type environment, Γ is a relational type environment, Δ is an environment for index variables and Φ for assumed constraints over the index terms. Figure 10 shows selected rules.

To embed RelCost in RHOL, we define a monadic-style cost-instrumented translation of RelCost types. The translation is given in two-steps: First, we define an erasure of cost and size information into simple types and then we define a cost-passing style translation of simple types with a value-translation and an expression-translation. The erasure function is defined as follows:

$$\begin{aligned} |\mathbb{N}| & \triangleq |\mathbb{N}_r| \triangleq \mathbb{N} & |\text{list}_A[n]| & \triangleq |\text{list}_A[n]^\alpha| \triangleq \text{list}_{|A|} & |UA| & \triangleq |\square A| \triangleq |A| \\ |\forall i \stackrel{\text{exec}(k,l)}{::} S. A| & \triangleq |\forall i \stackrel{\text{diff}(k)}{::} S. A| \triangleq \mathbb{N} \rightarrow |A| & |A \xrightarrow{\text{diff}(k)} B| & \triangleq |A \xrightarrow{\text{exec}(k,l)} B| \triangleq |A| \rightarrow |B| \end{aligned}$$

The cost-passing style translation of *simple* types is

$$(|\mathbb{N}|)_v \triangleq \mathbb{N} \quad (|\text{list}_A|)_v \triangleq \text{list}_{(|A|)_v} \quad (|A \rightarrow B|)_v \triangleq (|A|)_v \rightarrow (|B|)_e \quad (|A|)_e \triangleq (|A|)_v \times \mathbb{N}$$

Guided by the translation of types above we can provide a cost-instrumented translation of simply-typed λ -expressions (Figure 11). This translation maps an expression of the simple type τ to an expression of type $\tau \times \mathbb{N}$, where the second component is the number of reduction steps under an eager, call-by-value reduction strategy (which is the semantics of RelCost). It is fairly easy to see that this translation preserves typability and that it counts steps accurately.

However, this translation forgets the cost and size information in types. To recover these, we define a HOL formula for every unary type. But, first, we define axiomatically a predicate $\text{listU}(n, l, P)$ that captures size information about lists:

$$\forall l, P. \text{listU}(0, l, P) \equiv l = [] \quad \forall n, l, P. \text{listU}(n+1, l, P) \equiv \exists w_1, w_2. l = w_1 :: w_2 \wedge P(w_1) \wedge \text{listU}(n, w_2, P)$$

We can now define a HOL formula inductively on unary types.

$$\begin{aligned} [|\mathbb{N}|_v](x) & \triangleq \top & [|\text{list}_A[n]|_v](x) & \triangleq \text{listU}(n, x, [A]_v) & [A \xrightarrow{\text{exec}(k,l)} B]_v(x) & \triangleq \forall y. [A]_v(y) \Rightarrow [B]_e^{k,l}(xy) \\ [\forall i \stackrel{\text{exec}(k,l)}{::} S. A]_v(x) & \triangleq \forall y. \top \Rightarrow \forall i. [A]_e^{k,l}(xy) & [A]_e^{k,l}(x) & \triangleq [A]_v(\pi_1 x) \wedge k \leq \pi_2 x \leq l \end{aligned}$$

$\text{VAR} \frac{\Omega(x) = A}{\Delta; \Phi_a; \Omega \vdash_0^0 x : A}$	$\text{CONST} \frac{}{\Delta; \Phi_a; \Omega \vdash_0^0 n : \text{int}}$	$\text{LAM} \frac{\Delta; \Phi_a; x : A_1, \Omega \vdash_k^l t : A_2}{\Delta; \Phi_a; \Omega \vdash_0^0 \lambda x. t : A_1 \xrightarrow{\text{exec}(k,l)} A_2}$
$\text{APP} \frac{\Delta; \Phi_a; \Omega \vdash_{k_1}^{l_1} t_1 : A_1 \xrightarrow{\text{exec}(k,l)} A_2 \quad \Delta; \Phi_a; \Omega \vdash_{k_2}^{l_2} t_2 : A_1}{\Delta; \Phi_a; \Omega \vdash_{k_1+k_2+k+c_{app}}^{l_1+l_2+l+c_{app}} t_1 t_2 : A_2}$		
<hr/>		
$\text{R-VAR} \frac{\Gamma(x) = \tau}{\Delta; \Phi_a; \Gamma \vdash x \ominus x \lesssim 0 : \tau}$	$\text{R-CONST} \frac{}{\Delta; \Phi_a; \Gamma \vdash n \ominus n \lesssim 0 : \text{int}}$	
$\text{R-CONS1} \frac{\Delta; \Phi_a; \Gamma \vdash t_1 \ominus t'_1 \lesssim l_1 : \tau \quad \Delta; \Phi_a; \Gamma \vdash t_2 \ominus t'_2 \lesssim l_2 : \text{list}[n]^\alpha \tau}{\Delta; \Phi_a; \Gamma \vdash \text{cons}(t_1, t_2) \ominus \text{cons}(t'_1, t'_2) \lesssim l_1 + l_2 : \text{list}[n+1]^{\alpha+1} \tau}$		
$\text{R-CONS2} \frac{\Delta; \Phi_a; \Gamma \vdash t_1 \ominus t'_1 \lesssim l_1 : \square \tau \quad \Delta; \Phi_a; \Gamma \vdash t_2 \ominus t'_2 \lesssim l_2 : \text{list}[n]^\alpha \tau}{\Delta; \Phi_a; \Gamma \vdash \text{cons}(t_1, t_2) \ominus \text{cons}(t'_1, t'_2) \lesssim l_1 + l_2 : \text{list}[n+1]^\alpha \tau}$		
$\text{R-CASEL} \frac{\Delta; \Phi_a; \Gamma \vdash t \ominus t' \lesssim l : \text{list}[n]^\alpha \tau \quad \Delta; \Phi_a \wedge n = 0; \Gamma \vdash t_1 \ominus t'_1 \lesssim l' : \tau' \quad i, \Delta; \Phi_a \wedge n = i + 1; h : \square \tau, tl : \text{list}[i]^\alpha \tau, \Gamma \vdash t_2 \ominus t'_2 \lesssim l' : \tau' \quad i, \beta, \Delta; \Phi_a \wedge n = i + 1 \wedge \alpha = \beta + 1; h : \tau, tl : \text{list}[i]^\beta \tau, \Gamma \vdash t_2 \ominus t'_2 \lesssim l' : \tau'}{\Delta; \Phi_a; \Gamma \vdash \text{case } t \text{ of nil } \rightarrow t_1 \mid h :: tl \rightarrow t_2 \ominus \text{case } t' \text{ of nil } \rightarrow t'_1 \mid h :: tl \rightarrow t'_2 \lesssim l + l' : \tau'}$		
$\text{R-LAM} \frac{\Delta; \Phi_a; x : \tau_1, \Gamma \vdash t_1 \ominus t_2 \lesssim l : \tau_2}{\Delta; \Phi_a; \Gamma \vdash \lambda x. t_1 \ominus \lambda x. t_2 \lesssim 0 : \tau_1 \xrightarrow{\text{diff}(l)} \tau_2}$	$\text{R-APP} \frac{\Delta; \Phi_a; \Gamma \vdash t_1 \ominus t'_1 \lesssim l_1 : \tau_1 \xrightarrow{\text{diff}(l)} \tau_2 \quad \Delta; \Phi_a; \Gamma \vdash t_2 \ominus t'_2 \lesssim l_2 : \tau_1}{\Delta; \Phi_a; \Gamma \vdash t_1 t_2 \ominus t'_1 t'_2 \lesssim l_1 + l_2 + l : \tau_2}$	
$\text{R-ILAM} \frac{i :: S, \Delta; \Phi_a; \Gamma \vdash t \ominus t' \lesssim l : \tau \quad i \notin \text{FIV}(\Phi_a; \Gamma)}{\Delta; \Phi_a; \Gamma \vdash \Lambda t \ominus \Lambda t' \lesssim 0 : \forall i \xrightarrow{\text{diff}(l)} S. \tau}$	$\text{R-IAPP} \frac{\Delta; \Phi_a; \Gamma \vdash t \ominus t' \lesssim l : \forall i \xrightarrow{\text{diff}(l')} S. \tau \quad \Delta \vdash J : S}{\Delta; \Phi_a; \Gamma \vdash t[] \ominus t'[] \lesssim l + l' [J/i] : \tau [J/i]}$	
$\text{NOCHANGE} \frac{\Delta; \Phi_a; \Gamma \vdash t \ominus t \lesssim l : \tau \quad \forall x \in \text{dom}(\Gamma). \Delta; \Phi_a \models \Gamma(x) \sqsubseteq \square \Gamma(x)}{\Delta; \Phi_a; \Gamma, \Gamma'; \Omega \vdash t \ominus t \lesssim 0 : \square \tau}$		
$\text{SWITCH} \frac{\Delta; \Phi_a; \bar{\Gamma} \vdash_{k_1}^{l_1} t_1 : A \quad \Delta; \Phi_a; \bar{\Gamma} \vdash_{k_2}^{l_2} t_2 : A}{\Delta; \Phi_a; \Gamma \vdash t_1 \ominus t_2 \lesssim l_1 - k_2 : U A}$		

Fig. 10. RelCost Unary and Relational Typing (Selected Rules)

The type translation can also be extended to type environments: $\llbracket |x_1 : A_1, \dots, x_n : A_n| \rrbracket = x_1 : \llbracket |A_1| \rrbracket_v, \dots, x_n : \llbracket |A_n| \rrbracket_v$. Similarly, we can associate to a type environment an HOL context that we can use to recover the cost and size information: $\llbracket |x_1 : A_1, \dots, x_n : A_n| \rrbracket = \llbracket |A_1| \rrbracket_v(x_1), \dots, \llbracket |A_n| \rrbracket_v(x_n)$. Now we can provide a cost-instrumented translation of unary judgments.

Theorem 15. If $\Delta; \Phi; \Omega \vdash_k^l t : A$, then: $\llbracket |\Omega| \rrbracket, \Delta \mid \Phi, \llbracket |\Omega| \rrbracket \vdash (t) : \llbracket |A| \rrbracket_e \mid \llbracket |A| \rrbracket_e^{k,l}(\mathbf{r})$

$$\begin{array}{l}
\llbracket x \rrbracket \triangleq (x, 0) \qquad \llbracket \lambda x. t \rrbracket \triangleq (\lambda x. \llbracket t \rrbracket, 0) \qquad \llbracket \Lambda. t \rrbracket \triangleq (\lambda _ . \llbracket t \rrbracket, 0) \\
\llbracket tu \rrbracket \triangleq \text{let } x = \llbracket t \rrbracket \text{ in let } y = \llbracket u \rrbracket \text{ in let } z = \pi_1(x) \pi_1(y) \text{ in } (\pi_1(z), \pi_2(x) + \pi_2(y) + \pi_2(z) + c_{app}) \\
\llbracket t[] \rrbracket \triangleq \text{let } x = \llbracket t \rrbracket \text{ in let } y = \pi_1(x) 0 \text{ in } (\pi_1(y), \pi_2(x) + \pi_2(y) + c_{iapp}) \qquad \llbracket \text{nil} \rrbracket \triangleq (\text{nil}, 0) \\
\llbracket \text{cons}(t_1, t_2) \rrbracket \triangleq \text{let } x = \llbracket t_1 \rrbracket \text{ in let } y = \llbracket t_2 \rrbracket \text{ in } (\pi_1(x) :: \pi_1(y), \pi_2(x) + \pi_2(y)) \\
\llbracket \text{case } t' \text{ of nil} \rightarrow t'_1 \mid h :: tl \rightarrow t'_2 \rrbracket \triangleq \begin{cases} \text{let } x = \llbracket t' \rrbracket \text{ in case } \pi_1(x) \text{ of} \\ \text{nil} \rightarrow \text{let } y = \llbracket t'_1 \rrbracket \text{ in } (\pi_1(y), \pi_2(x) + \pi_2(y) + c_{case}) \\ \mid h :: tl \rightarrow \text{let } y = \llbracket t'_2 \rrbracket \text{ in } (\pi_1(y), \pi_2(x) + \pi_2(y) + c_{case}) \end{cases}
\end{array}$$

Fig. 11. Cost-instrumented translation of expressions.

For the embedding of cost and size information in the relational case we first define a predicate $\text{listR}(n, l_1, l_2, a, P)$ in HOL axiomatically:

$$\begin{aligned}
\forall l_1, l_2, a, P. \text{listR}(0, l_1, l_2, a, P) &\equiv l_1 = l_2 = [] \\
\forall n, l_1, l_2, a, P. \text{listR}(n + 1, l_1, l_2, a, P) &\equiv \exists w_1, z_1, w_2, z_2. l_1 = w_1 :: w_2 \wedge l_2 = z_1 :: z_2 \wedge P(w_1, z_1) \wedge \\
&\quad ((w_1 = z_1) \wedge \text{listR}(n, w_2, z_2, a, P)) \vee \\
&\quad (a > 0 \wedge \exists b. a = b + 1 \wedge \text{listR}(n, w_2, z_2, b, P))
\end{aligned}$$

Let $\bar{\tau}$ denote RelCost's erasure of the binary type τ to a unary type.² This erasure maps $\text{list}_\tau[n]^\alpha$ to $\text{list}_{\bar{\tau}}[n]$, $\tau \xrightarrow{\text{diff}(l)} \sigma$ to $\bar{\tau} \xrightarrow{\text{exec}(0, \infty)} \bar{\sigma}$, etc. Next, we define HOL formulas for the binary types.

$$\llbracket \mathbb{N} \rrbracket_v(x, y) \triangleq x = y \qquad \llbracket UA \rrbracket_v(x, y) \triangleq [A]_v(x) \wedge [A]_v(y) \qquad \llbracket \square \tau \rrbracket_v(x, y) \triangleq (x = y) \wedge (\llbracket \tau \rrbracket_v(x, y))$$

$$\llbracket \tau \xrightarrow{\text{diff}(l)} \sigma \rrbracket_v(x, y) \triangleq \llbracket \bar{\tau} \xrightarrow{\text{exec}(0, \infty)} \bar{\sigma} \rrbracket_v(x) \wedge \llbracket \bar{\tau} \xrightarrow{\text{exec}(0, \infty)} \bar{\sigma} \rrbracket_v(y) \wedge (\forall z_1, z_2. \llbracket \tau \rrbracket_v(z_1, z_2) \Rightarrow \llbracket \sigma \rrbracket_e^l(xz_1, yz_2))$$

$$\llbracket \forall i \stackrel{\text{diff}(l)}{::} S. \tau \rrbracket_v(x, y) \triangleq \llbracket \forall i \stackrel{\text{exec}(0, \infty)}{::} S. \bar{\tau} \rrbracket_v(x) \wedge \llbracket \forall i \stackrel{\text{exec}(0, \infty)}{::} S. \bar{\tau} \rrbracket_v(y) \wedge (\forall z_1 z_2. \top \Rightarrow \forall i. \llbracket \tau \rrbracket_e^l(xz_1, yz_2))$$

$$\llbracket \text{list}_\tau[n]^\alpha \rrbracket_v(x, y) \triangleq \text{listR}(n, x, y, \alpha, \llbracket \tau \rrbracket_v) \qquad \llbracket \tau \rrbracket_e^l(x, y) \triangleq \llbracket \tau \rrbracket_v(\pi_1 x, \pi_1 y) \wedge (\pi_2 x - \pi_2 y \leq l)$$

The type translation can also be extended to relational type environments pointwise: $\llbracket x^1 : \tau_1, \dots, x^n : \tau_n \rrbracket \triangleq x_1^1 : \llbracket \tau_1 \rrbracket_v, x_2^1 : \llbracket \tau_1 \rrbracket_v, \dots, x_1^n : \llbracket \tau_n \rrbracket_v, x_2^n : \llbracket \tau_n \rrbracket_v$. We also need to derive from a type relational environment an HOL context that remembers the cost and size information: $\llbracket x^1 : \tau_1, \dots, x^n : \tau_n \rrbracket \triangleq \llbracket \tau_1 \rrbracket_v(x_1^1, x_2^1), \dots, \llbracket \tau_n \rrbracket_v(x_1^n, x_2^n)$. Now we can provide the translation of relational judgments.

Theorem 16. If $\Delta; \Phi; \Gamma \vdash t_1 \ominus t_2 \lesssim l : \tau$, then: $\llbracket \Gamma \rrbracket, \Delta \mid \Phi, \llbracket \Gamma \rrbracket \vdash \llbracket t_1 \rrbracket_1 : \llbracket \tau \rrbracket_e \sim \llbracket t_2 \rrbracket_2 : \llbracket \tau \rrbracket_e \mid \llbracket \tau \rrbracket_e^l(\mathbf{r}_1, \mathbf{r}_2)$, where $\llbracket t_i \rrbracket_j$ is a copy of t_i where each variable x is replaced by a variable x_j for $j \in \{1, 2\}$.

RelCost's type-soundness theorem can be derived from Theorem 16 and the soundness of RHOL in set theory.

²In RelCost, this erasure is written $|\tau|$. We use a different notation to avoid confusion with our own erasure function from RelCost's types to simple types.

7 EXAMPLES

We present some illustrative examples to show how RHOL's rules work in practice. Our first example shows the functional equivalence of two recursive functions that are synchronous—they perform the same number of recursive calls. The second example shows the equivalence of two asynchronous recursive functions. Our third example illustrates reasoning about the relative cost of two programs, using an encoding similar to that of RelCost, but the example cannot be verified in RelCost itself.

7.1 First example: factorial

We show that the two following standard implementations of factorial, with and without an accumulator, are functionally equivalent:

$$\begin{aligned} \text{fact}_1 &\triangleq \text{letrec } f_1 \ n_1 = \text{case } n_1 \text{ of } 0 \mapsto 1; S \mapsto \lambda x_1. (S \ x_1) * (f_1 \ x_1) \\ \text{fact}_2 &\triangleq \text{letrec } f_2 \ n_2 = \lambda \text{acc}. \text{case } n_2 \text{ of } 0 \mapsto \text{acc}; S \mapsto \lambda x_2. f_2 \ x_2 ((S \ x_2) * \text{acc}) \end{aligned}$$

Our goal is to prove that:

$$\emptyset \mid \emptyset \vdash \text{fact}_1 : \mathbb{N} \rightarrow \mathbb{N} \sim \text{fact}_2 : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N} \mid \forall n_1 n_2. n_1 = n_2 \Rightarrow \forall \text{acc}. (\mathbf{r}_1 \ n_1) * \text{acc} = \mathbf{r}_2 \ n_2 \ \text{acc}$$

The proof starts by applying [LETREC] rule, which has its main premise:

$$\Psi \vdash \text{case } n_1 \text{ of } 0 \mapsto 1; S \mapsto \lambda x_1. (S \ x_1) * (f_1 \ x_1) \sim \lambda \text{acc}. \text{case } n_2 \text{ of } 0 \mapsto \text{acc}; S \mapsto \lambda x_2. f_2 \ x_2 ((S \ x_2) * \text{acc}) \mid \forall \text{acc}. \mathbf{r}_1 * \text{acc} = \mathbf{r}_2 \ \text{acc}$$

where $\Psi \triangleq n_1 = n_2, \forall y_1 y_2. (y_1, y_2) < (n_1, n_2) \Rightarrow y_1 = y_2 \Rightarrow \forall a. (f_1 \ y_1) * a = f_2 \ y_2 \ a$.

To prove this, we start by applying the one-sided [ABS-R] rule, with a trivial condition on *acc*. Then we can apply a two-sided [CASE] rule, which has 3 premises:

- $\Psi \vdash n_1 = 0 \Leftrightarrow n_2 = 0$
- $\Psi, n_1 = 0, n_2 = 0 \vdash 1 \sim \text{acc} \mid \mathbf{r}_1 * \text{acc} = \mathbf{r}_2$
- $\Psi \vdash \lambda x_1. (S \ x_1) * (f_1 \ x_1) \sim \lambda x_2. f_2 \ x_2 ((S \ x_2) * \text{acc}) \mid \forall x_1 x_2. n_1 = S \ x_1 \Rightarrow n_2 = S \ x_2 \Rightarrow (\mathbf{r}_1 \ x_1) * \text{acc} = \mathbf{r}_2 \ x_2$

Premise 1 is a direct consequence of the assertion $n_1 = n_2$ in Ψ . Premise 2 is a trivial arithmetic identity which can be proven in HOL (using rule SUB or by invoking Theorem 4). To prove premise 3, we first apply the (two-sided) [ABS] rule, which leaves the following proof obligation:

$$\Psi, n_1 = S \ x_1, n_2 = S \ x_2 \vdash (S \ x_1) * (f_1 \ x_1) \sim f_2 \ x_2 ((S \ x_2) * \text{acc}) \mid \mathbf{r}_1 * \text{acc} = \mathbf{r}_2$$

This is proven in HOL by instantiating the inductive hypothesis in Ψ with $y_1 \mapsto x_1, y_2 \mapsto x_2, a \mapsto (S \ x_1) * \text{acc}$.

7.2 Second example: take and map

This example establishes the equivalence of two programs that compute the same result, but using different number of recursive calls. Consider the following function *take* that takes a list l and a natural number n and returns the first n elements of the list (or the whole list if its length is less than n).

$$\begin{aligned} \text{take} &\triangleq \text{letrec } f_1 \ l_1 = \lambda n_1. \text{case } l_1 \text{ of } [] \mapsto [] \\ &\quad ; - :: - \mapsto \lambda h_1 t_1. \text{case } n_1 \text{ of } 0 \mapsto [] \\ &\quad ; S \mapsto \lambda y_1. h_1 :: (f_1 \ t_1 \ y_1) \end{aligned}$$

Next, consider the standard function *map* that applies a function g to every element of a list l pointwise.

$$\begin{aligned} \text{map} &\triangleq \text{letrec } f_2 \ l_2 = \lambda g_2. \text{case } l_2 \text{ of } [] \mapsto [] \\ &\quad ; - :: - \mapsto \lambda h_2 t_2. (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \end{aligned}$$

Intuitively, it should be clear that for all g, n, l , $\text{map } (\text{take } l \ n) \ g = \text{take } (\text{map } l \ g) \ n$ (mapping g over the first n elements of the list is the same as mapping over the whole list and then taking the first n elements). However, the computations on the two sides of the equality are very different: For a list l of length more than n , $\text{map } (\text{take } l \ n) \ g$ only examines the first n elements, whereas $\text{take } (\text{map } l \ g) \ n$ traverses the whole list. In the following we formalize this property in RHOL (Theorem 17) and outline the high-level idea of the proof. The full proof is in the appendix.

Theorem 17. $l_1, l_2 : \text{list}_{\mathbb{N}}, n_1, n_2 : \mathbb{N}, g_1, g_2 : \mathbb{N} \rightarrow \mathbb{N} \mid l_1 = l_2, n_1 = n_2, g_1 = g_2 \vdash$
 $\text{map } (\text{take } l_1 \ n_1) \ g_1 : \text{list}_{\mathbb{N}} \sim \text{take } (\text{map } l_2 \ g_2) \ n_2 : \text{list}_{\mathbb{N}} \mid \mathbf{r}_1 = \mathbf{r}_2$

PROOF IDEA. Since the two sides make an unequal number of recursive calls, we need to reason asynchronously on the two sides (specifically, we use the rule [LLCASE-A]). However, equality cannot be established inductively with asynchronous reasoning: If two function applications are to be shown equal, and a recursion step is taken in only one of them, then the induction hypothesis cannot be applied. So, we strengthen the induction hypothesis, replacing the assertion $\mathbf{r}_1 = \mathbf{r}_2$ in the theorem statement with $\mathbf{r}_1 \sqsubseteq \mathbf{r}_2 \wedge |\mathbf{r}_1| = \min(n_1, |l_1|) \wedge |\mathbf{r}_2| = \min(n_2, |l_2|)$ where \sqsubseteq denotes the prefix ordering on lists and $|\cdot|$ is the list length function. This assertion implies $\mathbf{r}_1 = \mathbf{r}_2$ and can be established inductively. The full proof is in the appendix, but at a high-level, the proof requires proving two judgments, one for the inner map-take pair and another for the outer one:

- $\Psi \vdash \text{take } l_1 \ n_1 \sim \text{map } l_2 \ g_2 \mid \mathbf{r}_1 \sqsubseteq_{g_2} \mathbf{r}_2$
- $\Psi \vdash \text{map } \sim \text{take} \mid \forall m_1 m_2. m_1 \sqsubseteq_{g_2} m_2 \Rightarrow (\forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |m_1| \Rightarrow (\mathbf{r}_1 \ m_1 \ g_1) \sqsubseteq (\mathbf{r}_2 \ m_2 \ x_2))$

where $m_1 \sqsubseteq_{g_2} m_2$ is an axiomatically defined predicate equivalent to $(\text{map } m_1 \ g) \sqsubseteq m_2$ and Ψ are the assumptions in the statement of the theorem (in particular, $l_1 = l_2$). The proof of the first premise proceeds by an analysis of map using synchronous rules. For the second premise, after applying [LETREC] we apply the asynchronous [LLCASE-A] rule, and then prove the following premises:

- (1) $\Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = [], m_2 = [] \vdash [] \sim [] \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2$
- (2) $\Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = [] \vdash [] \sim \lambda h_2 t_2. \text{case } x_2 \text{ of } 0 \mapsto []; S \mapsto \lambda y_2. h_2 :: f_2 \ t_2 \ y_2 \mid$
 $\forall h_2 t_2. m_2 = h_2 :: t_2 \Rightarrow \mathbf{r}_1 \sqsubseteq (\mathbf{r}_2 \ h_2 \ t_2)$
- (3) $\Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_2 = [] \vdash \lambda h_1 t_1. (g_1 \ h_1) :: (f_1 \ t_1 \ g_1) \sim [] \mid \forall h_1 t_1. m_1 = h_1 :: t_1 \Rightarrow (\mathbf{r}_1 \ h_1 \ t_1) \sqsubseteq \mathbf{r}_2$
- (4) $\Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2 \vdash \lambda h_1 t_1. (g_1 \ h_1) :: (f_1 \ t_1 \ g_1) \sim \lambda h_2 t_2. \text{case } x_2 \text{ of } 0 \mapsto []; S \mapsto \lambda y_2. h_2 :: f_2 \ t_2 \ y_2 \mid$
 $\forall h_1 t_1 h_2 t_2. m_1 = h_1 :: t_1 \Rightarrow m_2 = h_1 :: t_1 \Rightarrow (\mathbf{r}_1 \ h_1 \ t_1) \sqsubseteq (\mathbf{r}_2 \ h_2 \ t_2)$

where Φ is the inductive hypothesis obtained from the [LETREC] application. The first two premises follow directly from the definition of \sqsubseteq , while the third one follows from the contradictory assumptions $m_1 \sqsubseteq_{g_2} m_2$, $m_1 = h_1 :: t_1$ and $m_2 = []$. The last premise is proved by first applying the [NATCASE-R] rule and then applying the induction hypothesis. \square

7.3 Third example: insertion sort

Insertion sort is a standard sorting algorithm that sorts a list $h :: t$ by sorting the tail t recursively and then inserting h at the appropriate position in the sorted tail. Consider the following implementations of the insertion function, `insert`, and the insertion sort function, `isort`, each returning a pair, whose first element is the usual output list (inserted list for `insert` and sorted list for `isort`) and whose second element is the *number of comparisons* made during the execution (assuming an eager, call-by-value evaluation strategy).

$$\begin{aligned} \text{insert} &\triangleq \lambda x. \text{letrec } \text{insert } l = \text{case } l \text{ of } [] \mapsto ([x], 0); \\ &\quad _ :: _ \mapsto \lambda h t. \text{case } x \leq h \text{ of} \\ &\quad \text{tt} \mapsto (x :: l, 1); \\ &\quad \text{ff} \mapsto \text{let } s = \text{insert } t \text{ in } (h :: (\pi_1 \ s), 1 + (\pi_2 \ s)) \end{aligned}$$

$$\begin{aligned} \text{isort} &\triangleq \text{letrec } \text{isort } l = \text{case } l \text{ of } [] \mapsto ([], 0); \\ &\quad _ :: _ \mapsto \lambda h t. \text{ let } s = \text{isort } t \\ &\quad \quad \text{let } s' = \text{insert } h (\pi_1 s) \text{ in} \\ &\quad \quad (\pi_1 s', (\pi_2 s) + (\pi_2 s')) \end{aligned}$$

Using this implementation, we prove the following interesting fact about insertion sort: Among all lists of the same length, insertion sort computes the fastest (with fewest comparisons) on lists that are already sorted. This is a property about the relational cost of insertion sort (on two different inputs), which cannot be established in RelCost. To state the property in RHOL, we define a list predicate $\text{sorted}(l)$ in HOL axiomatically:

$$\text{sorted}([]) \equiv \top \qquad \forall h t. \text{sorted}(h :: t) \equiv (\text{sorted}(t) \wedge h \leq \text{lmin}(t))$$

where the function $\text{lmin}(l)$ returns the minimum element of l :

$$\text{lmin} \triangleq \text{letrec } f l = \text{case } l \text{ of } [] \mapsto \infty; _ :: _ \mapsto \lambda h t. \min(h, f t)$$

As in the previous example, let $|\cdot|$ be the standard list length function. The property of insertion sort mentioned above is formalized in the following theorem. In words, the theorem says that if isort is executed on lists x_1 and x_2 of the same length and x_1 is sorted, then the number of comparisons made during the sorting of x_1 is no more than the number of comparisons made during the sorting of x_2 .

Theorem 18. Let $\tau \triangleq \text{list}_{\mathbb{N}} \rightarrow \text{list}_{\mathbb{N}}$. Then, $\bullet \mid \bullet \vdash \text{isort} : \tau \sim \text{isort} : \tau \mid \forall x_1 x_2. (\text{sorted}(x_1) \wedge |x_1| = |x_2|) \Rightarrow \pi_2(\mathbf{r}_1 x_1) \leq \pi_2(\mathbf{r}_2 x_2)$.

A full proof is shown in the appendix. The proof proceeds mostly synchronously in the two sides. Following the structure of isort , we apply the rules [LETREC], [LISTCASE] and [APP] + [ABS] (for the let binding, which, as usual, is defined as a function application), followed by an application of the inductive hypothesis for the recursive call to isort . Eventually, we expose the call to insert on both sides. At this point, the observation is that since x_1 is already sorted, its head element must be no greater than all elements in its tail, so insert must return immediately with at most 1 comparison on the x_1 side. Formally, this last proof step can be completed by switching to either UHOL or HOL and using subject conversion; we switch to HOL in the appendix.

8 CONCLUSION

We have developed Relational Higher-Order Logic, a new formalism to reason about relational properties of (pure) higher-order programs written in a simply typed λ -calculus with inductive types and recursive definitions. The system is expressive, has solid foundations via an equivalence with Higher-Order Logic, and yet retains the (nice) “feel” of relational refinement type systems. An important direction for future work is to extend Relational Higher-Order Logic to effectful programs. Natural directions include integrating the state monad, and the Giry monad for probability sub-distributions. One particularly exciting perspective is to broaden the scope of relational cost analysis to probabilistic programs, and to prove relational costs for different data structures. There are also many potential applications to security, differential privacy, machine learning, and probabilistic programming.

For practical purposes, it will also be interesting to build prototype implementations of Relational Higher-Order Logic. We believe that much of the technology developed for (relational) refinement types, and in particular the automated generation of verification conditions (maybe with user hints to switch between unary and binary modes of reasoning) and the connection to SMT-solvers can be lifted without significant hurdle to Relational Higher-Order Logic.

REFERENCES

- Martín Abadi, Anindya Banerjee, Nevin Heintze, and Jon G. Riecke. 1999. A Core Calculus of Dependency. In *POPL '99, Proceedings of the 26th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, San Antonio, TX, USA, January 20-22, 1999*. 147–160. DOI : <http://dx.doi.org/10.1145/292540.292555>
- Martín Abadi, Luca Cardelli, and Pierre-Louis Curien. 1993. Formal Parametric Polymorphism. In *Conference Record of the Twentieth Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, Charleston, South Carolina, USA, January 1993*. 157–170. DOI : <http://dx.doi.org/10.1145/158511.158622>
- Peter Aczel and Nicola Gambino. 2000. Collection Principles in Dependent Type Theory. In *Types for Proofs and Programs, International Workshop, TYPES 2000, Durham, UK, December 8-12, 2000, Selected Papers (Lecture Notes in Computer Science)*, Paul Callaghan, Zhaohui Luo, James McKinna, and Robert Pollack (Eds.), Vol. 2277. Springer, 1–23. DOI : http://dx.doi.org/10.1007/3-540-45842-5_1
- Peter Aczel and Nicola Gambino. 2006. The generalised type-theoretic interpretation of constructive set theory. *J. Symb. Log.* 71, 1 (2006), 67–103. DOI : <http://dx.doi.org/10.2178/jsl/1140641163>
- Robin Adams and Zhaohui Luo. 2010. Classical predicative logic-enriched type theories. *Ann. Pure Appl. Logic* 161, 11 (2010), 1315–1345. DOI : <http://dx.doi.org/10.1016/j.apal.2010.04.005>
- Bowen Alpern and Fred B. Schneider. 1985. Defining Liveness. *Inf. Process. Lett.* 21, 4 (1985), 181–185. DOI : [http://dx.doi.org/10.1016/0020-0190\(85\)90056-0](http://dx.doi.org/10.1016/0020-0190(85)90056-0)
- Kazuyuki Asada, Ryosuke Sato, and Naoki Kobayashi. 2016. Verifying relational properties of functional programs by first-order refinement. *Science of Computer Programming* (2016).
- Gilles Barthe, Juan Manuel Crespo, and César Kunz. 2011. Relational Verification Using Product Programs. In *FM 2011: Formal Methods - 17th International Symposium on Formal Methods, Limerick, Ireland, June 20-24, 2011. Proceedings*. 200–214. DOI : http://dx.doi.org/10.1007/978-3-642-21437-0_17
- Gilles Barthe, Pedro R. D’Argenio, and Tamara Rezk. 2004. Secure Information Flow by Self-Composition. In *17th IEEE Computer Security Foundations Workshop, (CSFW-17 2004), 28-30 June 2004, Pacific Grove, CA, USA*. 100–114. DOI : <http://dx.doi.org/10.1109/CSFW.2004.17>
- Gilles Barthe, Cédric Fournet, Benjamin Grégoire, Pierre-Yves Strub, Nikhil Swamy, and Santiago Zanella Béguelin. 2014. Probabilistic relational verification for cryptographic implementations. In *Proceedings of the 41st Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL '14*, Suresh Jagannathan and Peter Sewell (Eds.), 193–206.
- Gilles Barthe, Marco Gaboardi, Emilio Jesús Gallego Arias, Justin Hsu, Aaron Roth, and Pierre-Yves Strub. 2015. Higher-order approximate relational refinement types for mechanism design and differential privacy. In *Proceedings of the 42nd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2015, Mumbai, India, January 15-17, 2015*, Sriram K. Rajamani and David Walker (Eds.), 55–68.
- Gilles Barthe, Benjamin Grégoire, and Santiago Zanella Béguelin. 2009. Formal certification of code-based cryptographic proofs. In *Proceedings of the 36th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2009, Savannah, GA, USA, January 21-23, 2009*. 90–101. DOI : <http://dx.doi.org/10.1145/1480881.1480894>
- Gilles Barthe, Benjamin Grégoire, Justin Hsu, and Pierre-Yves Strub. 2017. Coupling proofs are probabilistic product programs. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages, POPL 2017, Paris, France, January 18-20, 2017*. 161–174. <http://dl.acm.org/citation.cfm?id=3009896>
- Gilles Barthe, Boris Köpf, Federico Olmedo, and Santiago Zanella Béguelin. 2012. Probabilistic relational reasoning for differential privacy. In *Proceedings of the 39th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2012, Philadelphia, Pennsylvania, USA, January 22-28, 2012*. 97–110. DOI : <http://dx.doi.org/10.1145/2103656.2103670>
- João Filipe Belo. 2007. Dependently Sorted Logic. In *Types for Proofs and Programs, International Conference, TYPES 2007, Cividale del Friuli, Italy, May 2-5, 2007, Revised Selected Papers (Lecture Notes in Computer Science)*, Marino Miculan, Ivan Scagnetto, and Furio Honsell (Eds.), Vol. 4941. Springer, 33–50. DOI : http://dx.doi.org/10.1007/978-3-540-68103-8_3
- Nick Benton. 2004. Simple relational correctness proofs for static analyses and program transformations.. In *Proceedings of the 31th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL '04*, Neil D. Jones and Xavier Leroy (Eds.), 14–25.
- Lennart Beringer and Martin Hofmann. 2007. Secure information flow and program logics. In *20th IEEE Computer Security Foundations Symposium, CSF 2007, 6-8 July 2007, Venice, Italy*. IEEE Computer Society, 233–248. DOI : <http://dx.doi.org/10.1109/CSF.2007.30>
- Lionel Blatter, Nikolai Kosmatov, Pascale Le Gall, and Virgile Prevosto. 2017. Deductive Verification with Relational Properties. In *In Proc. of the 23th International Conference on Tools and Algorithms for the Construction and Analysis of Systems (TACAS 2017), Uppsala, Sweden*. To Appear.
- Ezgi Çiçek, Gilles Barthe, Marco Gaboardi, Deepak Garg, and Jan Hoffmann. 2017. Relational cost analysis. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages, POPL 2017, Paris, France, January 18-20, 2017*, Giuseppe Castagna and Andrew D. Gordon (Eds.). ACM, 316–329. <http://dl.acm.org/citation.cfm?id=3009858>
- Michael R. Clarkson and Fred B. Schneider. 2008. Hyperproperties. In *Proceedings of CSF'08*. 51–65.

- Derek Dreyer, Amal Ahmed, and Lars Birkedal. 2011. Logical Step-Indexed Logical Relations. *Logical Methods in Computer Science* 7, 2 (2011). DOI : [http://dx.doi.org/10.2168/LMCS-7\(2:16\)2011](http://dx.doi.org/10.2168/LMCS-7(2:16)2011)
- Derek Dreyer, Georg Neis, Andreas Rossberg, and Lars Birkedal. 2010. A relational modal logic for higher-order stateful ADTs. In *Proceedings of the 37th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2010, Madrid, Spain, January 17-23, 2010*. 185–198. DOI : <http://dx.doi.org/10.1145/1706299.1706323>
- Joshua Dunfield and Frank Pfenning. 2004. Tridirectional typechecking. In *Proceedings of the 31st ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2004, Venice, Italy, January 14-16, 2004*, Neil D. Jones and Xavier Leroy (Eds.). ACM, 281–292. DOI : <http://dx.doi.org/10.1145/964001.964025>
- Peter Dybjer. 1985. Program Verification in a Logical Theory of Constructions. In *Functional Programming Languages and Computer Architecture, FPCA 1985, Nancy, France, September 16-19, 1985, Proceedings (Lecture Notes in Computer Science)*, Jean-Pierre Jouannaud (Ed.), Vol. 201. Springer, 334–349. DOI : http://dx.doi.org/10.1007/3-540-15975-4_46
- Timothy S. Freeman and Frank Pfenning. 1991. Refinement Types for ML. In *Proceedings of the ACM SIGPLAN'91 Conference on Programming Language Design and Implementation (PLDI), Toronto, Ontario, Canada, June 26-28, 1991*, David S. Wise (Ed.). ACM, 268–277. DOI : <http://dx.doi.org/10.1145/113445.113468>
- Marco Gaboardi, Andreas Haeberlen, Justin Hsu, Arjun Narayan, and Benjamin C. Pierce. 2013. Linear dependent types for differential privacy. In *The 40th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL '13, Rome, Italy - January 23 - 25, 2013*, Roberto Giacobazzi and Radhia Cousot (Eds.). ACM, 357–370. DOI : <http://dx.doi.org/10.1145/2429069.2429113>
- Neil Ghani, Fredrik Nordvall Forsberg, and Alex Simpson. 2016a. Comprehensive Parametric Polymorphism: Categorical Models and Type Theory. In *Foundations of Software Science and Computation Structures - 19th International Conference, FOSSACS 2016, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2016, Eindhoven, The Netherlands, April 2-8, 2016, Proceedings*. 3–19. DOI : http://dx.doi.org/10.1007/978-3-662-49630-5_1
- Neil Ghani, Fredrik Nordvall Forsberg, and Alex Simpson. 2016b. Comprehensive Parametric Polymorphism: Categorical Models and Type Theory. In *Foundations of Software Science and Computation Structures - 19th International Conference, FOSSACS 2016, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2016, Eindhoven, The Netherlands, April 2-8, 2016, Proceedings (Lecture Notes in Computer Science)*, Bart Jacobs and Christof Löding (Eds.), Vol. 9634. Springer, 3–19. DOI : http://dx.doi.org/10.1007/978-3-662-49630-5_1
- John Hatcliff and Olivier Danvy. 1997. A computational formalization for partial evaluation. *Mathematical Structures in Computer Science* 7 (1997), 507–541.
- Nevin Heintze and Jon G. Riecke. 1998. The SLam Calculus: Programming with Secrecy and Integrity. In *POPL '98, Proceedings of the 25th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, San Diego, CA, USA, January 19-21, 1998*. 365–377. DOI : <http://dx.doi.org/10.1145/268946.268976>
- B. Jacobs. 1999. *Categorical Logic and Type Theory*. Number 141 in Studies in Logic and the Foundations of Mathematics. North Holland, Amsterdam.
- Ralf Jung, David Swasey, Filip Sieczkowski, Kasper Svendsen, Aaron Turon, Lars Birkedal, and Derek Dreyer. 2015. Iris: Monoids and Invariants as an Orthogonal Basis for Concurrent Reasoning. In *Proceedings of the 42nd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2015, Mumbai, India, January 15-17, 2015*. 637–650. DOI : <http://dx.doi.org/10.1145/2676726.2676980>
- Morten Krogh-Jespersen, Kasper Svendsen, and Lars Birkedal. 2017. A relational model of types-and-effects in higher-order concurrent separation logic. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages, POPL 2017, Paris, France, January 18-20, 2017*. 218–231. <http://dl.acm.org/citation.cfm?id=3009877>
- Paul-André Mellies and Noam Zeilberger. 2015. Functors are Type Refinement Systems. In *Proceedings of the 42nd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2015, Mumbai, India, January 15-17, 2015*, Sriram K. Rajamani and David Walker (Eds.). ACM, 3–16. DOI : <http://dx.doi.org/10.1145/2676726.2676970>
- Aleksandar Nanevski, Anindya Banerjee, and Deepak Garg. 2013. Dependent Type Theory for Verification of Information Flow and Access Control Policies. *ACM Trans. Program. Lang. Syst.* 35, 2 (2013), 6:1–6:41. DOI : <http://dx.doi.org/10.1145/2491522.2491523>
- Frank Pfenning. 2008. Church and Curry: Combining Intrinsic and Extrinsic Typing. In *Reasoning in Simple Type Theory: Festschrift in Honor of Peter B. Andrews on His 70th Birthday*, C. Benz Müller, C. Brown, J. Siekmann, and R. Statman (Eds.). College Publications, 303–338.
- Gordon Plotkin. 1973. Lambda-definability and logical relations. (1973).
- Gordon Plotkin. 1977. LCF considered as a programming language. *Theoretical Computer Science* 5, 3 (1977), 223 – 255. DOI : [http://dx.doi.org/10.1016/0304-3975\(77\)90044-5](http://dx.doi.org/10.1016/0304-3975(77)90044-5)
- Gordon D. Plotkin and Martin Abadi. 1993. A Logic for Parametric Polymorphism. In *Typed Lambda Calculi and Applications, International Conference on Typed Lambda Calculi and Applications, TLCA '93, Utrecht, The Netherlands, March 16-18, 1993, Proceedings*. 361–375. DOI : <http://dx.doi.org/10.1007/BFb0037118>
- François Pottier and Vincent Simonet. 2002. Information flow inference for ML. In *Conference Record of POPL 2002: The 29th SIGPLAN-SIGACT Symposium on Principles of Programming Languages, Portland, OR, USA, January 16-18, 2002*. 319–330. DOI : <http://dx.doi.org/10.1145/503272.503302>

- Marcelo Sousa and Isil Dillig. 2016. Cartesian hoare logic for verifying k-safety properties. In *Proceedings of the 37th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2016, Santa Barbara, CA, USA, June 13-17, 2016*. 57–69. DOI: <http://dx.doi.org/10.1145/2908080.2908092>
- R. Statman. 1985. Logical relations and the typed λ -calculus. *Information and Control* 65, 2-3 (May 1985), 85–97. [http://dx.doi.org/10.1016/s0019-9958\(85\)80001-2](http://dx.doi.org/10.1016/s0019-9958(85)80001-2)
- Gordon Stewart, Anindya Banerjee, and Aleksandar Nanevski. 2013. Dependent types for enforcement of information flow and erasure policies in heterogeneous data structures. In *15th International Symposium on Principles and Practice of Declarative Programming, PPDP '13, Madrid, Spain, September 16-18, 2013*. 145–156. DOI: <http://dx.doi.org/10.1145/2505879.2505895>
- Nikhil Swamy, Catalin Hritcu, Chantal Keller, Aseem Rastogi, Antoine Delignat-Lavaud, Simon Forest, Karthikeyan Bhargavan, Cédric Fournet, Pierre-Yves Strub, Markulf Kohlweiss, Jean Karim Zinzindohoue, and Santiago Zanella Béguelin. 2016. Dependent types and multi-monadic effects in F. In *Proceedings of the 43rd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2016, St. Petersburg, FL, USA, January 20 - 22, 2016*, Rastislav Bodík and Rupak Majumdar (Eds.). ACM, 256–270. DOI: <http://dx.doi.org/10.1145/2837614.2837655>
- William W. Tait. 1967. Intensional Interpretations of Functionals of Finite Type I. *J. Symb. Log.* 32, 2 (1967), 198–212. DOI: <http://dx.doi.org/10.2307/2271658>
- Tachio Terauchi and Alex Aiken. 2005. Secure Information Flow as a Safety Problem. In *Static Analysis Symposium*, Chris Hankin and Igor Siveroni (Eds.), Vol. 3672. 352–367.
- Niki Vazou, Eric L. Seidel, Ranjit Jhala, Dimitrios Vytiniotis, and Simon L. Peyton Jones. 2014. Refinement types for Haskell. In *Proceedings of the 19th ACM SIGPLAN international conference on Functional programming, Gothenburg, Sweden, September 1-3, 2014*, Johan Jeuring and Manuel M. T. Chakravarty (Eds.). ACM, 269–282. DOI: <http://dx.doi.org/10.1145/2628136.2628161>
- Dennis Volpano, Geoffrey Smith, and Cynthia Irvine. 1996. A sound type system for secure flow analysis. *Journal of Computer Security* 4, 3 (1996), 1–21.
- Hongwei Xi and Frank Pfenning. 1999. Dependent Types in Practical Programming. In *POPL '99, Proceedings of the 26th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, San Antonio, TX, USA, January 20-22, 1999*, Andrew W. Appel and Alex Aiken (Eds.). ACM, 214–227. DOI: <http://dx.doi.org/10.1145/292540.292560>
- Hongseok Yang. 2007. Relational separation logic. 375, 1-3 (2007), 308–334.
- Anna Zaks and Amir Pnueli. 2008. CoVaC: Compiler Validation by Program Analysis of the Cross-Product. In *Formal Methods (Lecture Notes in Computer Science)*, Jorge Cuéllar, T. S. E. Maibaum, and Kaisa Sere (Eds.), Vol. 5014. 35–51.
- Noam Zeilberger. 2016. Principles of Type Refinement. (2016). <http://noamz.org/oplss16/refinements-notes.pdf> Notes for OPLSS 2016 school.

A SEMANTICS

Semantics of HOL

Types. The interpretation for the types corresponds directly to the usual representation of pairs, lists and functions in set theory.

$$\begin{aligned} \llbracket \mathbb{B} \rrbracket &\triangleq \{\text{ff}, \text{tt}\} \\ \llbracket \mathbb{N} \rrbracket &\triangleq \mathbb{N} \\ \llbracket \text{list}_\tau \rrbracket &\triangleq \text{list}_{\llbracket \tau \rrbracket} \\ \llbracket \tau_1 \times \tau_2 \rrbracket &\triangleq \llbracket \tau_1 \rrbracket \times \llbracket \tau_2 \rrbracket \\ \llbracket \tau_1 \rightarrow \tau_2 \rrbracket &\triangleq \llbracket \tau_1 \rrbracket \rightarrow \llbracket \tau_2 \rrbracket \end{aligned}$$

Terms. The terms are given an interpretation with respect to a valuation ρ which is a partial function mapping variables to elements in the interpretation of their type. Given ρ , we use the notation $\rho[v/x]$ to denote the unique extension of ρ such that if $y = x$ then $\rho[v/x](y) = v$ and, otherwise, $\rho[v/x](y) = \rho(y)$.

$$\begin{aligned} \langle x \rangle_\rho &\triangleq \rho(x) & \langle \langle t, u \rangle \rangle_\rho &:= \langle \langle t \rangle_\rho, \langle u \rangle_\rho \rangle & \langle \pi_i t \rangle_\rho &\triangleq \pi_i(\langle t \rangle_\rho) & \langle \lambda x : \tau. t \rangle_\rho &\triangleq \lambda v : \llbracket \tau \rrbracket. \langle x \rangle_{\rho[\langle v \rangle_\rho / v]} \\ \langle c \rangle_\rho &\triangleq c & \langle S t \rangle_\rho &\triangleq S \langle t \rangle_\rho & \langle t :: u \rangle_\rho &\triangleq \langle t \rangle_\rho :: \langle u \rangle_\rho \\ \langle \text{case } t \text{ of } [] \mapsto u; _ :: _ \mapsto v \rangle_\rho &\triangleq \text{case } \langle t \rangle_\rho \text{ of } [] \mapsto \langle u \rangle_\rho; _ :: _ \mapsto \langle v \rangle_\rho \\ \langle \text{letrec } f \ x = t \rangle_\rho &\triangleq \text{fix } f \ (\langle \lambda x. t \rangle_\rho) \text{ where } \text{fix } f \ v := v[(\text{fix } f \ v) / f] \end{aligned}$$

Formulas. We assume that for predicate P of arity $\tau_1 \times \dots \times \tau_n$, we have an interpretation $\llbracket P \rrbracket \in \llbracket \tau_1 \rrbracket \times \dots \times \llbracket \tau_n \rrbracket$ that satisfies the axioms for P . The interpretation of a formula is defined as follows:

$$\begin{aligned} \langle P(t_1, \dots, t_n) \rangle_\rho &\triangleq (\llbracket t_1 \rrbracket_\rho, \dots, \llbracket t_n \rrbracket_\rho) \in \llbracket P \rrbracket \\ \langle \top \rangle_\rho &\triangleq \tilde{\top} \\ \langle \perp \rangle_\rho &\triangleq \tilde{\perp} \\ \langle \phi_1 \wedge \phi_2 \rangle_\rho &\triangleq \langle \phi_1 \rangle_\rho \tilde{\wedge} \langle \phi_2 \rangle_\rho, \mathcal{M} \\ \langle \phi_1 \Rightarrow \phi_2 \rangle_\rho &\triangleq \langle \phi_1 \rangle_\rho \tilde{\Rightarrow} \langle \phi_2 \rangle_\rho \\ \langle \forall x : \tau. \phi \rangle_\rho &\triangleq \tilde{\forall} v. v \in \llbracket \tau \rrbracket \Rightarrow \langle \phi \rangle_{\rho[v/x]} \end{aligned}$$

where we use the tilde ($\tilde{\cdot}$) to distinguish between the (R)HOL connectives and the meta-level connectives.

Soundness. We have the following result:

THEOREM A.1 (SOUNDNESS OF SET-THEORETICAL SEMANTICS). *If $\Gamma \mid \Psi \vdash \phi$, then for every valuation $\rho \models \Gamma$, $\bigwedge_{\psi \in \Psi} \langle \psi \rangle_\rho$ implies $\langle \phi \rangle_\rho$.*

PROOF. By induction on the length of the derivation of $\Gamma \mid \Psi \vdash \phi$. □

Semantics of UHOL

The intended meaning of a UHOL judgment $\Gamma \mid \Psi \vdash t : \tau \mid \phi$ is:

$$\text{for all } \mathcal{M}, \rho. \text{ s.t. } \rho \models \Gamma \text{ and } \mathcal{M} \models \Psi, \phi \\ \llbracket \bigwedge \Psi \rrbracket_{\rho, \mathcal{M}} \text{ implies } \llbracket \phi \rrbracket_{\rho[\llbracket t \rrbracket_{\rho/r}]} \mathcal{M}$$

We have the following result:

Theorem 19 (Set-theoretical soundness and consistency of UHOL). If $\Gamma \mid \Psi \vdash t : \sigma \mid \phi$, then for every valuation $\rho \models \Gamma, \bigwedge_{\psi \in \Psi} \llbracket \psi \rrbracket_{\rho}$ implies $\llbracket \phi \rrbracket_{\rho[\llbracket t \rrbracket_{\rho/r}]}$. In particular, there is no proof of $\Gamma \mid \emptyset \vdash t : \sigma \mid \perp$ in UHOL.

PROOF. It is a direct consequence of the embedding from UHOL into HOL and the soundness of HOL. \square

Semantics of RHOL

The intended meaning of a RHOL judgment $\Gamma \mid \Psi \vdash t_1 : \tau_1 \sim t_2 : \tau_2 \mid \phi$ is:

$$\text{for all } \mathcal{M}, \rho. \text{ s.t. } \rho \models \Gamma \text{ and } \mathcal{M} \models \Psi, \phi \\ \llbracket \bigwedge \Psi \rrbracket_{\rho, \mathcal{M}} \text{ implies } \llbracket \phi \rrbracket_{\rho[\llbracket t_1 \rrbracket_{\rho/r_1}][\llbracket t_2 \rrbracket_{\rho/r_2}]} \mathcal{M}$$

We have the following result:

Theorem 20 (Set-theoretical soundness and consistency of RHOL). If $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$, then for every valuation $\rho \models \Gamma, \bigwedge_{\psi \in \Psi} \llbracket \psi \rrbracket_{\rho}$ implies $\llbracket \phi \rrbracket_{\rho[\llbracket t_1 \rrbracket_{\rho/r_1}][\llbracket t_2 \rrbracket_{\rho/r_2}]}$. In particular, there is no proof of $\Gamma \mid \emptyset \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \perp$ for any Γ .

PROOF. It is a direct consequence of the embedding of RHOL into HOL and the soundness of HOL. \square

B ADDITIONAL RULES

For reasons of space, we have omitted some derivable and admissible rules in HOL, UHOL and RHOL. These are useful to prove some theorems and examples. We now discuss the most interesting among them:

HOL

The following rules are derivable in HOL:

- A cut rule can be derived from $[\Rightarrow_I]$ and $[\Rightarrow_E]$:

$$\frac{\Gamma \mid \Psi, \phi' \vdash \phi \quad \Gamma \mid \Psi \vdash \phi'}{\Gamma \mid \Psi \vdash \phi} \text{ CUT}$$

- A rule for case analysis can be derived from [LIST]:

$$\frac{\Gamma \vdash l : \text{list}_{\tau} \quad \Gamma \mid \Psi, l = [] \vdash \phi \quad \Gamma, h : \tau, t : \text{list}_{\tau} \mid \Psi, l = h :: t \vdash \phi}{\Gamma \mid \Psi \vdash \phi} \text{ DESTR - LIST}$$

- A rule for strong induction can be derived from [LIST]:

$$\frac{\Gamma \mid \Psi \vdash \phi[[]/t] \quad \Gamma, h : \tau, t : \text{list}_{\tau} \mid \Psi, \forall u : \text{list}_{\tau}. |u| \leq |t| \Rightarrow \phi[u/t] \vdash \phi[h :: t/t]}{\Gamma \mid \Psi \vdash \forall t : \text{list}_{\tau}. \phi} \text{ S - LIST}$$

- A rule for (weak) double induction can be derived by applying [LIST] twice:

$$\frac{\begin{array}{c} \Gamma \mid \Psi \vdash \phi[\square/l_1][\square/l_2] \\ \Gamma, h_1 : \tau_1, t_1 : \text{list}_{\tau_1} \mid \Psi, \phi[t_1/l_1][\square/l_2] \vdash \phi[h_1 :: t_1/l_1][\square/l_2] \\ \Gamma, h_2 : \tau_2, t_2 : \text{list}_{\tau_2} \mid \Psi, \phi[\square/l_1][t_2/l_2] \vdash \phi[\square/l_1][h_2 :: t_2/l_2] \\ \Gamma, h_1 : \tau_1, t_2 : \text{list}_{\tau_2}, h_2 : \tau_2, t_2 : \text{list}_{\tau_2} \mid \Psi, \phi[t_1/l_1][t_2/l_2] \vdash \phi[h_1 :: t_1/l_1][h_2 :: t_2/l_2] \end{array}}{\Gamma \mid \Psi \vdash \forall l_1 l_2. \phi} \text{ D-LIST}$$

- A rule for strong double induction can be derived from [D-LIST]:

$$\frac{\begin{array}{c} \Gamma \mid \Psi \vdash \phi[\square/l_1][\square/l_2] \\ \Gamma, h_1 : \tau_1, t_1 : \text{list}_{\tau_1} \mid \Psi, \forall m_1. |m_1| \leq |t_1| \Rightarrow \phi[m_1/l_1][\square/l_2] \vdash \phi[h_1 :: t_1/l_1][\square/l_2] \\ \Gamma, h_2 : \tau_2, t_2 : \text{list}_{\tau_2} \mid \Psi, \forall m_2. |m_2| \leq |t_2| \Rightarrow \phi[\square/l_1][m_2/l_2] \vdash \phi[\square/l_1][h_2 :: t_2/l_2] \\ \Gamma, h_1 : \tau_1, t_1 : \text{list}_{\tau_1}, h_2 : \tau_2, t_2 : \text{list}_{\tau_2} \mid \\ \Psi, \forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |h_2 :: t_2|) \Rightarrow \phi[m_1/l_1][m_2/l_2] \vdash \phi[h_1 :: t_1/l_1][h_2 :: t_2/l_2] \end{array}}{\Gamma \mid \Psi \vdash \forall l_1 l_2. \phi} \text{ S-D-LIST}$$

RHOL

The following version of the case rule is admissible:

$$\frac{\begin{array}{c} \Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \text{list}_{\tau_2} \mid \phi' \wedge (\mathbf{r}_1 = 0 \Leftrightarrow \mathbf{r}_2 = 0) \\ \Gamma \mid \Psi, \phi'[0/\mathbf{r}_1][0/\mathbf{r}_2] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\ \Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi'[Sx_1/\mathbf{r}_1][Sx_2/\mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2] \end{array}}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2 : \sigma_2 \mid \phi} \text{ NATCASE*}$$

and the one sided version:

$$\frac{\begin{array}{c} \Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \sigma_2 \mid \phi' \\ \Gamma \mid \Psi, \phi'[0/\mathbf{r}_1][t_2/\mathbf{r}_2] \vdash u_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \\ \Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall x_1. \phi'[Sx_1/\mathbf{r}_1] \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1] \end{array}}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{ NATCASE* -L}$$

Notice that we can always recover the initial version of the rule by instantiating ϕ' as $t_1 = \mathbf{r}_1 \wedge t_2 = \mathbf{r}_2$.

C PROOFS

Proof of Theorem 10

We will use without proof the following results:

Lemma 21. If $\Gamma \vdash \tau \leq \sigma$ in refinement types, then $|\tau| \equiv |\sigma|$.

PROOF. By induction on the derivation. □

Lemma 22. For every type τ and expression e and variable $x \notin FV(\tau, e)$, $\lfloor \tau \rfloor(e) = \lfloor \tau \rfloor(x)[e/x]$

PROOF. By structural induction. □

Now we proceed with the proof of the theorem. We do it by induction on the derivation:

$$\text{Case. } \frac{\Gamma \vdash \tau}{\Gamma \vdash \tau \leq \tau}$$

To show: $|\Gamma|, x : |\tau| \mid \lfloor \tau \rfloor(x) \vdash \lfloor \tau \rfloor(x)$. Directly by [AX].

$$\text{Case. } \frac{\Gamma \vdash \tau_1 \leq \tau_2 \quad \Gamma \vdash \tau_2 \leq \tau_3}{\Gamma \vdash \tau_1 \leq \tau_3}$$

To show: $|\Gamma|, x : |\tau_1| \mid \lfloor \Gamma \rfloor, \lfloor \tau_1 \rfloor(x) \vdash \lfloor \tau_3 \rfloor(x)$.

By induction hypothesis on the premises,

$$|\Gamma|, x : |\tau_1| \mid \lfloor \Gamma \rfloor, \lfloor \tau_1 \rfloor(x) \vdash \lfloor \tau_2 \rfloor(x)$$

and

$$|\Gamma|, x : |\tau_2| \mid \lfloor \Gamma \rfloor, \lfloor \tau_2 \rfloor(x) \vdash \lfloor \tau_3 \rfloor(x).$$

We complete the proof by [CUT]. Notice that $|\tau_1| \equiv |\tau_2| \equiv |\tau_3|$.

$$\text{Case. } \frac{\Gamma \vdash \tau_1 \leq \tau_2}{\Gamma \vdash \text{list}_{\tau_1} \leq \text{list}_{\tau_2}}$$

To show: $|\Gamma|, x : |\text{list}_{\tau_1}| \mid \lfloor \Gamma \rfloor, \lfloor \text{list}_{\tau_1} \rfloor(x) \vdash \lfloor \text{list}_{\tau_2} \rfloor(\mathbf{r})$

Expanding the definitions: $|\Gamma|, x : \text{list}_{|\tau_1|} \mid \lfloor \Gamma \rfloor, \top \vdash \top$,
which is trivial.

$$\text{Case. } \frac{\Gamma \vdash \{\mathbf{r} : \tau \mid \phi\}}{\Gamma \vdash \{\mathbf{r} : \tau \mid \phi\} \leq \tau}$$

To show: $|\Gamma|, x : |\{\mathbf{r} : \tau \mid \phi\}| \mid \lfloor \{\mathbf{r} : \tau \mid \phi\} \rfloor(x) \vdash \lfloor \tau \rfloor(x)$.

Expanding the definitions: $|\Gamma|, x : |\{\mathbf{r} : \tau \mid \phi\}| \mid \lfloor \tau \rfloor(x) \wedge \phi[x/\mathbf{r}] \vdash \lfloor \tau \rfloor(x)$

and now the proof is completed trivially by $[\wedge_E]$ and [AX].

$$\text{Case. } \frac{\Gamma \vdash \tau \leq \sigma \quad \Gamma, \mathbf{r} : \tau \vdash \phi}{\Gamma \vdash \tau \leq \{\mathbf{r} : \sigma \mid \phi\}}$$

To show: $|\Gamma|, \mathbf{r} : |\tau| \mid \lfloor \Gamma \rfloor, \lfloor \tau \rfloor(\mathbf{r}) \vdash \lfloor \{\mathbf{r} : \sigma \mid \phi\} \rfloor(\mathbf{r})$

Expanding the definition: $|\Gamma|, \mathbf{r} : |\tau| \mid \lfloor \Gamma \rfloor, \lfloor \tau \rfloor(\mathbf{r}) \vdash \lfloor \sigma \rfloor(\mathbf{r}) \wedge \phi$

By induction hypothesis on the premises we have:

$$|\Gamma|, \mathbf{r} : |\tau| \mid \lfloor \Gamma \rfloor, \lfloor \tau \rfloor(\mathbf{r}) \vdash \lfloor \sigma \rfloor(\mathbf{r})$$

and:

$$|\Gamma|, \mathbf{r} : |\tau| \mid \lfloor \Gamma \rfloor, \lfloor \tau \rfloor(\mathbf{r}) \vdash \phi$$

We complete the proof by applying the $[\wedge_I]$ rule.

$$\text{Case. } \frac{\Gamma \vdash \sigma_2 \leq \sigma_1 \quad \Gamma, x : \sigma_2 \vdash \tau_1 \leq \tau_2}{\Gamma \vdash \Pi(x : \sigma_1). \tau_1 \leq \Pi(x : \sigma_2). \tau_2}$$

To show: $|\Gamma|, f : |\Pi(x : \sigma_1). \tau_1| \mid \lfloor \Gamma \rfloor, \lfloor \Pi(x : \sigma_1). \tau_1 \rfloor(f) \vdash \lfloor \Pi(x : \sigma_2). \tau_2 \rfloor(f)$

Expanding the definitions:

$$|\Gamma|, f : |\Pi(x : \sigma_1). \tau_1| \mid \lfloor \Gamma \rfloor, \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \forall x. \lfloor \sigma_2 \rfloor(x) \Rightarrow \lfloor \tau_2 \rfloor(fx)$$

By the rules $[\forall_I]$ and $[\Rightarrow_I]$ it suffices to prove:

$$|\Gamma|, f : |\Pi(x : \sigma_1). \tau_1|, x : |\sigma_2| \mid \lfloor \Gamma \rfloor, \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx), \lfloor \sigma_2 \rfloor(x) \vdash \lfloor \tau_2 \rfloor(fx) \quad (1)$$

On the other hand, by induction hypothesis on the premises:

$$|\Gamma|, x : |\sigma_2| \mid \lfloor \Gamma \rfloor, \lfloor \sigma_2 \rfloor(x) \vdash \lfloor \sigma_1 \rfloor(x) \quad (2)$$

and

$$|\Gamma, x : |\sigma_2|, y : |\tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \lfloor \tau_1 \rfloor(y) \vdash \lfloor \tau_2 \rfloor(y) \quad (3)$$

which we can weaken respectively to:

$$|\Gamma, x : |\sigma_2|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \lfloor \sigma_1 \rfloor(x) \quad (4)$$

and

$$|\Gamma, x : |\sigma_2|, y : |\tau_1|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \lfloor \tau_1 \rfloor(y), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \lfloor \tau_2 \rfloor(y) \quad (5)$$

From (4), by doing a cut with its own premise $\forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx)$, we derive:

$$|\Gamma, x : |\sigma_2|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \lfloor \tau_1 \rfloor(fx) \quad (6)$$

From (5), by $[\Rightarrow_I]$ and $[\forall_I]$ we can derive:

$$|\Gamma, x : |\sigma_2|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \forall y. \lfloor \tau_1 \rfloor(y) \Rightarrow \lfloor \tau_2 \rfloor(y)$$

And by $[\forall_E]$

$$|\Gamma, x : |\sigma_2|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \lfloor \tau_1 \rfloor(fx) \Rightarrow \lfloor \tau_2 \rfloor(fx) \quad (7)$$

Finally, from (6) and (7) by $[\Rightarrow_E]$ we get:

$$|\Gamma, x : |\sigma_2|, f : |\Pi(x : \sigma_1). \tau_1| \mid |\Gamma|, \lfloor \sigma_2 \rfloor(x), \forall x. \lfloor \sigma_1 \rfloor(x) \Rightarrow \lfloor \tau_1 \rfloor(fx) \vdash \lfloor \tau_2 \rfloor(fx)$$

and by one last application of $[\Rightarrow_I]$ we get what we wanted to prove.

Proof of Theorem 9

By induction on the derivation:

Case. $x : \tau, \Gamma \vdash x : \tau$

To prove: $x : |\tau|, |\Gamma| \vdash \lfloor \tau \rfloor(x), |\Gamma| \vdash x : |\tau| \mid \lfloor \tau \rfloor(\mathbf{r})$. Directly by [VAR].

Case. $\frac{\Gamma, x : \tau \vdash t : \sigma}{\Gamma \vdash \lambda x. t : \Pi(x : \tau). \sigma}$

To prove: $|\Gamma| \mid |\Gamma| \vdash \lambda x. t : |\Pi(x : \tau). \sigma| \mid |\Pi(x : \tau). \sigma|(\mathbf{r})$.

Expanding the definitions:

$$|\Gamma| \mid |\Gamma| \vdash \lambda x. t : |\tau| \rightarrow |\sigma| \mid \forall x. \lfloor \tau \rfloor(x) \Rightarrow \lfloor \sigma \rfloor(\mathbf{r}x)$$

By induction hypothesis on the premise:

$$|\Gamma, x : |\tau| \mid |\Gamma|, \lfloor \tau \rfloor(x) \vdash t : |\sigma| \mid \lfloor \sigma \rfloor(\mathbf{r})$$

Directly by [ABS].

Case. $\frac{\Gamma \vdash t : \Pi(x : \tau). \sigma \quad \Gamma \vdash u : \tau}{\Gamma \vdash t u : \sigma[u/x]}$

To prove: $|\Gamma| \mid |\Gamma| \vdash t u : |\sigma[u/x]| \mid \lfloor \sigma[u/x] \rfloor(\mathbf{r})$.

Expanding the definitions:

$$|\Gamma| \mid |\Gamma| \vdash t e_2 : |\sigma| \mid \lfloor \sigma \rfloor(\mathbf{r})[u/x]$$

By induction hypothesis on the premise:

$$|\Gamma| \mid |\Gamma| \vdash t : |\tau| \rightarrow |\sigma| \mid \forall x. \lfloor \tau \rfloor(x) \Rightarrow \lfloor \sigma \rfloor(\mathbf{r}x)$$

and

$$|\Gamma| \mid |\Gamma| \vdash u : |\tau| \mid \lfloor \tau \rfloor(\mathbf{r})$$

We get the result directly by [APP].

Case. $\frac{\Gamma \vdash t : \text{list}_\tau \quad \Gamma \vdash u : \sigma \quad \Gamma \vdash v : \tau \rightarrow \text{list}_\tau \rightarrow \sigma}{\Gamma \vdash \text{case } t \text{ of } [] \mapsto u; _ :: _ \mapsto v : \sigma}$

To prove: $|\Gamma| \mid |\Gamma| \vdash \text{case } t \text{ of } [] \mapsto u; _ :: _ \mapsto v : |\sigma| \mid \lfloor \sigma \rfloor(\mathbf{r})$

By induction hypothesis on the premises:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t : |\text{list}_\tau| \mid \llbracket \text{list}_\tau \rrbracket(\mathbf{r}), \quad (1)$$

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash u : |\sigma| \mid \llbracket \sigma \rrbracket(\mathbf{r}), \quad (2)$$

and

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash v : |\tau \rightarrow \text{list}_\tau \rightarrow \sigma| \mid \llbracket \tau \rightarrow \text{list}_\tau \rightarrow \sigma \rrbracket(\mathbf{r}) \quad (3)$$

Expanding the definitions on (3) we get:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash v : |\tau| \rightarrow |\text{list}_\tau| \rightarrow |\sigma| \mid \forall x. \llbracket \tau \rrbracket(x) \Rightarrow \forall y. \llbracket \text{list}_\tau \rrbracket(y) \Rightarrow \llbracket \sigma \rrbracket(\mathbf{r} \ x \ y) \quad (4)$$

And from (1), (2) and (4) we apply [LISTCASE*] and we get the result. Notice that (2) and (4) are stronger than the premises of the rule, so we will first need to apply [SUB] to weaken them

$$\text{Case. } \frac{\Gamma \vdash \tau}{\Gamma \vdash [] : \text{list}_\tau}$$

To prove: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash [] : |\text{list}_\tau| \mid \llbracket \text{list}_\tau \rrbracket(\mathbf{r})$

Expanding the definitions: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash [] : \text{list}_{|\tau|} \mid \text{All}(\mathbf{r}, x, \llbracket \tau \rrbracket(x))$

And by the definition of All for the empty case, trivially $\text{All}([], x, \llbracket \tau \rrbracket(x))$, so we apply the [NIL] rule and we get the result.

$$\text{Case. } \frac{\Gamma \vdash h : \tau \quad \Gamma \vdash t : \text{list}_\tau}{\Gamma \vdash h :: t : \text{list}_\tau}$$

To prove: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h :: t : |\text{list}_\tau| \mid \llbracket \text{list}_\tau \rrbracket(\mathbf{r})$.

Expanding the definitions: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h :: t : \text{list}_{|\tau|} \mid \text{All}(\mathbf{r}, \lambda x. \llbracket \tau \rrbracket(x))$.

By induction hypothesis on the premises, we have:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h : |\tau| \mid \llbracket \tau \rrbracket(\mathbf{r})$$

and

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t : \text{list}_{|\tau|} \mid \text{All}(\mathbf{r}, \lambda x. \llbracket \tau \rrbracket(x)).$$

We complete the proof by the [CONS] rule and the definition of All in the inductive case.

$$\text{Case. } \frac{\Gamma \vdash \tau \leq \sigma \quad \Gamma \vdash t : \tau}{\Gamma \vdash t : \sigma}$$

To prove: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t : |\sigma| \mid \llbracket \sigma \rrbracket(\mathbf{r})$

and, since $|\sigma| \equiv |\tau|$, it is the same as writing

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t : |\tau| \mid \llbracket \tau \rrbracket(\mathbf{r})$$

By induction hypothesis on the premises:

$$|\Gamma|, x : |\tau| \mid \llbracket \Gamma \rrbracket, \llbracket \tau \rrbracket(x) \vdash \llbracket \sigma \rrbracket(x)$$

and

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t : |\tau| \mid \llbracket \tau \rrbracket(\mathbf{r})$$

The proof is completed by applying $[\Rightarrow_I]$ to the first premise, and then [SUB].

$$\text{Case. } \frac{\Gamma, x : \tau, f : \Pi(y : \{ \mathbf{r} : \tau \mid y < x \}). \sigma[y/x] \vdash t : \sigma \quad \text{Def}(f, x, t)}{\Gamma \vdash \text{letrec } f \ x = t : \Pi(x : \tau). \sigma}$$

To prove: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash \text{letrec } f \ x = t : |\Pi(x : \tau). \sigma| \mid \llbracket \Pi(x : \tau). \sigma \rrbracket(\mathbf{r})$

By induction hypothesis on the premise:

$$|\Gamma|, x : |\tau|, f : |\tau| \rightarrow |\sigma| \mid \llbracket \Gamma \rrbracket, \llbracket \tau \rrbracket(x), \forall y. \llbracket \tau \rrbracket(y) \wedge y < x \Rightarrow \llbracket \sigma[y/x] \rrbracket(fy) \vdash t : |\sigma| \mid \llbracket \sigma \rrbracket(\mathbf{r})$$

Directly by [LETREC].

Proof of Theorem 11

We can recover the lemma from the unary case:

Lemma 23. For every type τ , expressions t_1, t_2 and variables $x_1, x_2 \notin FV(\tau, t_1, t_2)$, $\llbracket \tau \rrbracket(t_1, t_2) = \llbracket \tau \rrbracket(x_1, x_2)[t_1/x_1][t_2/x_2]$

Most cases are very similar to the unary case, so we will only show the most interesting ones:

Case.
$$\frac{\Gamma \vdash T}{\Gamma \vdash [] \sim [] :: \text{list}_T}$$

To show: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash [] : |\text{list}_T| \sim [] : |\text{list}_T| \mid \llbracket \text{list}_T \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$.

There are two options. If T is a unary type, we have to prove:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash [] : |\text{list}_T| \sim [] : |\text{list}_T| \mid \bigwedge_{i \in \{1,2\}} \text{All}(\mathbf{r}_i, \lambda x. \llbracket \tau \rrbracket(x))$

And by the definition of All we can directly prove:

$\emptyset \mid \emptyset \vdash \text{All}([], \lambda x. \llbracket \tau \rrbracket(x)) \wedge \text{All}([], \lambda x. \llbracket \tau \rrbracket(x))$

If T is a relational type, we have to prove:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash [] : |\text{list}_T| \sim [] : |\text{list}_T| \mid \text{All2}(\mathbf{r}_1, \mathbf{r}_2, \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2))$

And by the definition of All2 we can directly prove:

$\emptyset \mid \emptyset \vdash \text{All2}([], [], \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2))$

Case.
$$\frac{\Gamma \vdash h_1 \sim h_2 :: T \quad \Gamma \vdash t_1 \sim t_2 :: \text{list}_T}{\Gamma \vdash h_1 :: t_1 \sim h_2 :: t_2 :: \text{list}_T}$$

To show: $|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h_1 :: t_2 : |\text{list}_T| \sim h_2 :: t_2 : |\text{list}_T| \mid \text{list}_T$.

There are two options. If T is a unary type, we have to prove:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h_1 :: t_1 : |\text{list}_T| \sim h_2 :: t_2 : |\text{list}_T| \mid \bigwedge_{i \in \{1,2\}} \text{All}(\mathbf{r}_i, \lambda x. \llbracket T \rrbracket(x))$

By induction hypothesis we have:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h_1 : |T| \sim h_2 :: t_2 : |T| \mid \bigwedge_{i \in \{1,2\}} \llbracket T \rrbracket(\mathbf{r}_i)$

and

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t_1 : |\text{list}_T| \sim t_2 : |\text{list}_T| \mid \bigwedge_{i \in \{1,2\}} \text{All}(\mathbf{r}_i, \lambda x. \llbracket T \rrbracket(x))$

And by the definition of All we can directly prove:

$\bigwedge_{i \in \{1,2\}} \llbracket T \rrbracket(h_i) \Rightarrow \bigwedge_{i \in \{1,2\}} \text{All}(t_i, \lambda x. \llbracket T \rrbracket(x)) \Rightarrow \bigwedge_{i \in \{1,2\}} \text{All}(h_i :: t_i, \lambda x. \llbracket T \rrbracket(x))$

So by the [CONS] rule, we prove the result. If T is a relational type, we have to prove:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h_1 :: t_1 : |\text{list}_T| \sim h_2 :: t_2 : |\text{list}_T| \mid \text{All2}(\mathbf{r}_1, \mathbf{r}_2, \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2))$

By induction hypothesis we have:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash h_1 : |T| \sim h_2 :: t_2 : |T| \mid \llbracket T \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$

and

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t_1 : |\text{list}_T| \sim t_2 : |\text{list}_T| \mid \text{All2}(\mathbf{r}_1, \mathbf{r}_2, \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2))$

And by the definition of All2 we can directly prove:

$\llbracket T \rrbracket(h_1, h_2) \Rightarrow \text{All2}(t_1, t_2, \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2)) \Rightarrow \text{All}(h_1 :: t_1, h_2 :: t_2, \lambda x_1. \lambda x_2. \llbracket T \rrbracket(x_1, x_2))$

So by the [CONS] rule, we prove the result.

Case.
$$\frac{\Gamma \vdash t_1 \sim t_2 :: \text{list}_T \quad \Gamma \vdash t_1 = [] \Leftrightarrow t_2 = [] \quad \Gamma \vdash u_1 \sim u_2 :: U \quad \Gamma \vdash v_1 \sim v_2 :: \Pi(h :: T). \Pi(t :: \text{list}_T). U}{\Gamma \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 :: U}$$

To show:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : |U| \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : |U| \mid \llbracket U \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$

By induction hypothesis we have:

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash t_1 = [] \Leftrightarrow t_2 = [],$

$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash u_1 : |U| \sim u_2 : |U| \mid \llbracket U \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$

and

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash v_1 : T \rightarrow \text{list}_T \rightarrow U \sim v_2 : T \rightarrow \text{list}_T \rightarrow U \mid \forall h_1 h_2. \llbracket T \rrbracket(h_1, h_2) \Rightarrow \forall t_1 t_2. \llbracket \text{list}_T \rrbracket(t_1, t_2) \Rightarrow \llbracket U \rrbracket(\mathbf{r}_1 h_1 t_1, h_2 t_2 \mathbf{r}_2)$$

By applying the [LISTCASE*] rule to the three premises we get the result.

$$\frac{\Gamma, x :: T, f :: \Pi(y :: \{y :: T \mid (y_1, y_2) < (x_1, x_2)\}). U[y/x] \vdash t_1 \sim t_2 :: U \quad \Gamma \vdash \Pi(x :: T). U \quad \mathcal{D}ef(f_1, x_1, t_1) \quad \mathcal{D}ef(f_2, x_2, t_2)}{\Gamma \vdash \text{letrec } f_1 \ x_1 = t_1 \sim \text{letrec } f_2 \ x_2 = t_2 :: \Pi(x :: T). U}$$

Case.

$$\Gamma \vdash \text{letrec } f_1 \ x_1 = t_1 \sim \text{letrec } f_2 \ x_2 = t_2 :: \Pi(x :: T). U$$

To show:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash \text{letrec } f_1 \ x_1 = t_1 : |\Pi(x :: T). U| \sim \text{letrec } f_2 \ x_2 = t_2 : |\Pi(x :: T). U| \mid \llbracket \Pi(x :: T). U \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$$

Expanding the definitions:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket \vdash \text{letrec } f_1 \ x_1 = t_1 : |T| \rightarrow |U| \sim \text{letrec } f_2 \ x_2 = t_2 : |T| \rightarrow |U| \mid \forall x_1 x_2. \llbracket T \rrbracket(x_1, x_2) \Rightarrow \llbracket U \rrbracket(\mathbf{r}_1 x_1, \mathbf{r}_2 x_2)$$

By induction hypothesis on the premise:

$$|\Gamma|, x_1, x_2 : |T|, f_1, f_2 : |T| \rightarrow |U| \mid \llbracket \Gamma \rrbracket, \llbracket T \rrbracket(x_1, x_2), \forall y_1, y_2. (\llbracket T \rrbracket(y_1, y_2) \wedge (y_1, y_2) < (x_1, x_2)) \Rightarrow \llbracket U \rrbracket(f_1 x_1, f_2 x_2) \vdash t_1 : |U| \sim t_2 : |U| \mid \llbracket U \rrbracket(\mathbf{r}_1, \mathbf{r}_2)$$

And we apply the [LETREC] rule to get the result.

Proof of Theorem 4

The easier direction is the reverse implication. To prove it, one just notices that we can trivially apply [SUB] instantiating ϕ' as a tautology that matches the structure of the types. For instance, for a base type \mathbb{N} we would use \top , for an arrow type $\mathbb{N} \rightarrow \mathbb{N}$ we would use $\forall x. \perp \Rightarrow \top$, and so on.

We now prove the direct implication by induction on the derivation of $\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi$. Suppose the last rule is:

Case. [VAR] (similarly, [NIL] and [PROJ])

The premise of the rule is already the judgment we want to prove.

$$\text{Case. [ABS]} \frac{\Gamma, x_1 : \tau_1, x_2 : \tau_2 \mid \Psi, \phi' \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \lambda x_1. t_1 : \tau_1 \rightarrow \sigma_1 \sim \lambda x_2. t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1][\mathbf{r}_2 \ x_2 / \mathbf{r}_2]}$$

By applying the induction hypothesis on the premise:

$$\Gamma, x_1 : \tau_1, x_2 : \tau_2 \mid \Psi, \phi' \vdash \phi[t_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2] \tag{1}$$

By applying $[\Rightarrow_I]$ on (1):

$$\Gamma, x_1 : \tau_1, x_2 : \tau_2 \mid \Psi \vdash \phi' \Rightarrow \phi[t_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2]$$

By applying $[\forall_I]$ twice on (2):

$$\Gamma \mid \Psi \vdash \forall x_1 x_2. \phi' \Rightarrow \phi[t_1 / \mathbf{r}_1][t_2 / \mathbf{r}_2] \tag{3}$$

Finally, by applying CONV on (3):

$$\Gamma \mid \Psi \vdash \forall x_1 x_2. \phi' \Rightarrow \phi[(\lambda x_1. t_1) \ x_1 / \mathbf{r}_1][(\lambda x_2. t_2) \ x_2 / \mathbf{r}_2]$$

Proof for [ABS-L] (and [ABS-R]) is analogous.

$$\frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 \ x_1 / \mathbf{r}_1][\mathbf{r}_2 \ x_2 / \mathbf{r}_2] \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi'}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi[u_1 / x_1][u_2 / x_2]}$$

Case. [APP]

$$\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi[u_1 / x_1][u_2 / x_2]$$

By applying the induction hypothesis on the premises we have:

$$\Gamma \mid \Psi \vdash \forall x_1 x_2. \phi'[x_1 / \mathbf{r}_1][x_2 / \mathbf{r}_2] \Rightarrow \phi[t_1 \ x_1 / \mathbf{r}_1][t_2 \ x_2 / \mathbf{r}_2] \tag{1}$$

and

$$\Gamma \mid \Psi \vdash \phi'[u_1 / \mathbf{r}_1][u_2 / \mathbf{r}_2] \tag{2}$$

By applying twice $[\forall_E]$ to (1) with u_1, u_2 :

$$\Gamma \mid \Psi \vdash \phi'[u_1/\mathbf{r}_1][u_2/\mathbf{r}_2] \Rightarrow \phi[t_1 u_1/\mathbf{r}_1][t_2 u_2/\mathbf{r}_2] \quad (3)$$

and by applying $[\Rightarrow_E]$ to (3) and (2):

$$\Gamma \mid \Psi \vdash \phi[t_1 u_1/\mathbf{r}_1][t_2 u_2/\mathbf{r}_2]$$

Proof for [APP-L] (and APP-R) is analogous, and it uses the UHOL embedding for the premise about the argument. Proofs for [CONS] and [PAIR] are very similar as well.

$$\text{Case. [SUB]} \frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \phi'[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2] \Rightarrow \phi[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}$$

Applying the inductive hypothesis on the premises we have:

$$\Gamma \mid \Psi \vdash \phi'[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2]$$

and

$$\Gamma \mid \Psi \vdash \phi[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2]$$

The proof is simply applying $[\Rightarrow_E]$.

$$\frac{\begin{array}{c} \text{Def}(f_1, x_1, e_1) \quad \text{Def}(f_2, x_2, e_2) \\ \Gamma, x_1 : I_1, x_2 : I_2, f_1 : I_1 \rightarrow \sigma, f_2 : I_2 \rightarrow \sigma_2 \mid \\ \Psi, \phi', \forall m_1 m_2. (|m_1|, |m_2|) < (|x_1|, |x_2|) \Rightarrow \phi'[m_1/x_1][m_2/x_2] \Rightarrow \phi[m_1/x_1][m_2/x_2][f_1 m_1/\mathbf{r}_1][f_2 m_2/\mathbf{r}_2] \vdash \\ e_1 : \sigma_1 \sim e_2 : \sigma_2 \mid \phi \end{array}}{\Gamma \mid \Psi \vdash \text{letrec } f_1 x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim \text{letrec } f_2 x_2 = e_2 : I_2 \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2]}$$

$$\text{Case. [LETREC]} \frac{\Gamma \mid \Psi \vdash \text{letrec } f_1 x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim \text{letrec } f_2 x_2 = e_2 : I_2 \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \text{letrec } f_1 x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim \text{letrec } f_2 x_2 = e_2 : I_2 \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2]}$$

As an example, we prove the list and nat case, but for other datatypes the proof is similar. Applying the inductive hypothesis on the premise we have:

$$\Gamma, l_1, n_2, f_1, f_2 \mid \Psi, \forall m_1 m_2. (|m_1|, |m_2|) < (|l_1|, |n_2|) \Rightarrow \phi[f_1 m_1/\mathbf{r}_1][f_2 m_2/\mathbf{r}_2] \vdash \phi[e_1/\mathbf{r}_1][e_2/\mathbf{r}_2]$$

By $[\forall_I]$ we derive:

$$\Gamma \mid \Psi \vdash \forall f_1, f_2, l_1, n_2. (\forall m_1 m_2. (|m_1|, |m_2|) < (|l_1|, |n_2|) \Rightarrow \phi[f_1 m_1/\mathbf{r}_1][f_2 m_2/\mathbf{r}_2]) \Rightarrow \phi[e_1/\mathbf{r}_1][e_2/\mathbf{r}_2]. \quad (\Phi)$$

We want to prove

$$\Gamma \mid \Psi \vdash \forall l_1 n_2. \phi[F_1 l_1/\mathbf{r}_1][F_2 n_2/\mathbf{r}_2]$$

where we use the abbreviations

$$\begin{array}{l} F_1 \quad := \quad \text{letrec } f_1 x_1 = e_1 \\ F_2 \quad := \quad \text{letrec } f_2 x_2 = e_2 \end{array}$$

We will use strong double induction over natural numbers and lists. We need to prove four premises. Since we can prove (Φ) from Γ, Ψ , we can add it to the axioms:

- (A) $\Gamma \mid \Psi, \Phi \vdash \phi[F_1 []/\mathbf{r}_1][F_2 0/\mathbf{r}_2]$
- (B) $\Gamma, h_1, t_1 \mid \Psi, \Phi, \forall m_1. |m_1| \leq |t_1| \Rightarrow \phi[F_1 m_1/\mathbf{r}_1][F_2 0/\mathbf{r}_2] \vdash \phi[F_1 (h_1 :: t_1)/\mathbf{r}_1][F_2 0/\mathbf{r}_2]$
- (C) $\Gamma, x_2 \mid \Psi, \Phi, \forall m_2. |m_2| \leq |x_2| \Rightarrow \phi[F_1 []/\mathbf{r}_1][F_2 m_2/\mathbf{r}_2] \vdash \phi[F_1 []/\mathbf{r}_1][F_2 (Sx_2)/\mathbf{r}_2]$
- (D) $\Gamma, h_1, t_1, x_2 \mid \Psi, \Phi, \forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |Sx_2|) \Rightarrow \phi[F_1 m_1/\mathbf{r}_1][F_2 m_2/\mathbf{r}_2] \vdash \phi[F_1 (h_1 :: t_1)/\mathbf{r}_1][F_2 (Sx_2)/\mathbf{r}_2]$

To prove them, we will instantiate the quantifiers in Φ with the appropriate variables.

To prove (A), we instantiate Φ at $F_1, F_2, [], 0$:

$$(\forall m_1 m_2. (|m_1|, |m_2|) < (|[], |0|) \Rightarrow \phi[F_1 m_1/\mathbf{r}_1][F_2 m_2/\mathbf{r}_2]) \Rightarrow \phi[e_1/\mathbf{r}_1][e_2/\mathbf{r}_2][[]/l_1][0/n_2][F_1/f_1][F_2/f_2]$$

and, since $(|m_1|, |m_2|) < (|[]|, |0|)$ is trivially false, then

$$\phi[e_1/r_1][e_2/r_2][[]/l_1][0/n_2][F_1/f_1][F_2/f_2]$$

and by beta-expansion and [CONV]:

$$\phi[F_1 []/r_1][F_2 0/r_2]$$

To prove (B), we instantiate Φ at $F_1, F_2, h_1 :: t_1, 0$

$$(\forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |0|) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]) \Rightarrow \phi[e_1/r_1][e_2/r_2][h_1 :: t_1/l_1][0/n_2][F_1/f_1][F_2/f_2]$$

by beta-expansion:

$$(\forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |0|) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]) \Rightarrow \phi[F_1 h_1 :: t_1/r_1][F_2 0/r_2]$$

Since $(|m_1|, |m_2|) < (|h_1 :: t_1|, |0|)$ is only satisfied if $|m_1| \leq |t_1| \wedge m_2 = 0$, we can write it as:

$$(\forall m_1 m_2. (|m_1| \leq |t_1| \wedge m_2 = 0) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]) \Rightarrow \phi[F_1 h_1 :: t_1/r_1][F_2 0/r_2]$$

On the other hand, one of the antecedents of (B) is $\forall m_1. |m_1| \leq |t_1| \Rightarrow \phi[F_1 m_1/r_1][F_2 0/r_2]$, so by $[\Rightarrow_E]$ we prove $\phi[F_1 h_1 :: t_1/r_1][F_2 0/r_2]$, which is the consequent of (B).

The proof of (C) is symmetrical to the proof of (B).

To prove (D), we instantiate Φ at $F_1, F_2, h_1 :: t_1, Sx_2$

$$(\forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |Sx_2|) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]) \Rightarrow \phi[e_1/r_1][e_2/r_2][h_1 :: t_1/l_1][Sx_2/n_2][F_1/f_1][F_2/f_2]$$

by beta-expansion:

$$(\forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |Sx_2|) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]) \Rightarrow \phi[F_1 h_1 :: t_1/r_1][F_2 (Sx_2)/r_2]$$

One of the antecedents of (D) is exactly $\forall m_1 m_2. (|m_1|, |m_2|) < (|h_1 :: t_1|, |Sx_2|) \Rightarrow \phi[F_1 m_1/r_1][F_2 m_2/r_2]$, so by $[\Rightarrow_E]$ we prove $\phi[F_1 h_1 :: t_1/r_1][F_2 (Sx_2)/r_2]$, which is the consequent of (D).

Proof of [LETREC-L] (and [LETREC-R]) is analogous, and uses simple strong induction.

$$\begin{array}{c} \Gamma \mid \Psi \vdash l_1 : \text{list}_{\tau_1} \sim l_2 : \text{list}_{\tau_2} \mid \mathbf{r}_1 = [] \Leftrightarrow \mathbf{r}_2 = [] \quad \Gamma \mid \Psi, l_1 = [], l_2 = [] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\ \Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\ \forall h_1 h_2 t_1 t_2. l_1 = h_1 :: t_1 \Rightarrow l_2 = h_2 :: t_2 \Rightarrow \phi[\mathbf{r}_1 \ h_1 \ t_1/\mathbf{r}_1][\mathbf{r}_2 \ h_2 \ t_2/\mathbf{r}_2] \end{array}$$

$$\text{Case. [CASE]} \frac{}{\Gamma \mid \Psi \vdash \text{case } l_1 \text{ of } [] \mapsto u_1; _ :: _ \mapsto v_1 : \sigma_1 \sim \text{case } l_2 \text{ of } [] \mapsto u_2; _ :: _ \mapsto v_2 : \sigma_2 \mid \phi}$$

We prove the rule for natural numbers. Applying the induction hypothesis to the premises of the rule, we have:

$$(A) \Gamma \mid \Psi \vdash t_1 = 0 \Leftrightarrow t_2 = 0$$

$$(B) \Gamma \mid \Psi, t_1 = 0, t_2 = 0 \vdash \phi[u_1/r_1][u_2/r_2]$$

$$(C) \Gamma \mid \Psi \vdash \forall x_1, x_2. t_1 = Sx_1 \Rightarrow t_2 = Sx_2 \Rightarrow \phi[v_1 \ x_1/r_1][v_2 \ x_2/r_2]$$

We want to prove:

$$\Gamma \mid \Psi \vdash \phi[(\text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1)/\mathbf{r}_1][(\text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2)/\mathbf{r}_2]$$

By applying [DESTR-NAT] twice, we get four premises:

$$(1) \Gamma \mid \Psi, t_1 = 0, t_2 = 0 \vdash \phi[(\text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1)/\mathbf{r}_1][(\text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2)/\mathbf{r}_2]$$

$$(2) \Gamma, m_2 \mid \Psi, t_1 = 0, t_2 = Sm_2 \vdash \phi[(\text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1)/\mathbf{r}_1][(\text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2)/\mathbf{r}_2]$$

$$(3) \Gamma, m_1 \mid \Psi, t_1 = Sm_1, t_2 = 0 \vdash \phi[(\text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1)/\mathbf{r}_1][(\text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2)/\mathbf{r}_2]$$

$$(4) \Gamma, m_1, m_2 \mid \Psi, t_1 = Sm_1, t_2 = Sm_2 \vdash \phi[(\text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1)/\mathbf{r}_1][(\text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2)/\mathbf{r}_2]$$

We can prove (2) and (3) by deriving a contradiction with [NC] and (A). After beta-reducing in (1) and (4) we can easily derive them from (B) and (C) respectively.

Proof of [CASE-L] (and [CASE-R]) is analogous.

Proof of Lemma 8

By the embedding into HOL, we have:

- $\Gamma \mid \Psi \vdash \phi[t_1/\mathbf{r}]$
- $\Gamma \mid \Psi \vdash \phi'[t_2/\mathbf{r}]$

and by the $[\wedge_I]$ rule,

$$\Gamma \mid \Psi \vdash \phi[t_1/\mathbf{r}] \wedge \phi'[t_2/\mathbf{r}].$$

Finally, by undoing the embedding:

$$\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi.$$

Proof of Lemma 13

By induction on the derivation of $\tau \searrow \ell$.

$$\text{Case. } \frac{\ell \sqsubseteq \ell'}{\mathbb{T}_{\ell'}(\tau) \searrow \ell}$$

Since $\ell \not\sqsubseteq a$ (given) and $\ell \sqsubseteq \ell'$ (premise), it must be the case that $\ell' \not\sqsubseteq a$. Hence, by definition, $\llbracket \mathbb{T}_{\ell'}(\tau) \rrbracket_a(x, y) = \top$.

$$\text{Case. } \frac{\tau \searrow \ell}{\mathbb{T}_{\ell'}(\tau) \searrow \ell}$$

We consider two cases:

If $\ell' \not\sqsubseteq a$, then $\llbracket \mathbb{T}_{\ell'}(\tau) \rrbracket_a(x, y) = \top$ by definition.

If $\ell' \sqsubseteq a$, then $\llbracket \mathbb{T}_{\ell'}(\tau) \rrbracket_a(x, y) = \llbracket \tau \rrbracket_a(x, y)$ by definition. By i.h. on the premise, we have $\llbracket \tau \rrbracket_a(x, y) \equiv \top$. Composing, $\llbracket \mathbb{T}_{\ell'}(\tau) \rrbracket_a(x, y) \equiv \top$.

$$\text{Case. } \frac{\tau_1 \searrow \ell \quad \tau_2 \searrow \ell}{\tau_1 \times \tau_2 \searrow \ell}$$

By i.h. on the premises, we have $\llbracket \tau_i \rrbracket_a(x, y) \equiv \top$ for $i = 1, 2$ and all x, y . Therefore, $\llbracket \tau_1 \times \tau_2 \rrbracket_a(x, y) \triangleq \llbracket \tau_1 \rrbracket_a(\pi_1(x), \pi_1(y)) \wedge \llbracket \tau_2 \rrbracket_a(\pi_2(x), \pi_2(y)) \equiv \top \wedge \top \equiv \top$.

$$\text{Case. } \frac{\tau_2 \searrow \ell}{\tau_1 \rightarrow \tau_2 \searrow \ell}$$

By i.h. on the premise, we have $\llbracket \tau_2 \rrbracket_a(x, y) \equiv \top$ for all x, y . Hence, $\llbracket \tau_1 \rightarrow \tau_2 \rrbracket_a(x, y) \triangleq (\forall v, w. \llbracket \tau_1 \rrbracket_a(v, w) \Rightarrow \llbracket \tau_2 \rrbracket_a(x v, y w)) \equiv (\forall v, w. \llbracket \tau_1 \rrbracket_a(v, w) \Rightarrow \top) \equiv \top$.

Proof of Theorem 14

By induction on the given derivation of $\Gamma \vdash e : \tau$.

$$\text{Case. } \frac{}{\Gamma \vdash \text{tt} : \mathbb{B}}$$

To show: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash \text{tt} : \mathbb{B} \sim \text{tt} : \mathbb{B} \mid (\mathbf{r}_1 = \text{tt} \wedge \mathbf{r}_2 = \text{tt}) \vee (\mathbf{r}_1 = \text{ff} \wedge \mathbf{r}_2 = \text{ff})$.

By rule TRUE, it suffices to show $(\text{tt} = \text{tt} \wedge \text{tt} = \text{tt}) \vee (\text{tt} = \text{ff} \wedge \text{tt} = \text{ff})$ in HOL, which is trivial.

Case. $\frac{\Gamma \vdash e : \mathbb{B} \quad \Gamma \vdash e_t : \tau \quad \Gamma \vdash e_f : \tau}{\Gamma \vdash \text{case } e \text{ of tt} \mapsto e_t; \text{ff} \mapsto e_f : \tau}$

To show: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash (\text{case } |e|_1 \text{ of tt} \mapsto |e_t|_1; \text{ff} \mapsto |e_f|_1) : |\tau| \sim (\text{case } |e|_2 \text{ of tt} \mapsto |e_t|_2; \text{ff} \mapsto |e_f|_2) : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$.

By i.h. on the first premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e|_1 : \mathbb{B} \sim |e|_2 : \mathbb{B} \mid (\mathbf{r}_1 = \text{tt} \wedge \mathbf{r}_2 = \text{tt}) \vee (\mathbf{r}_1 = \text{ff} \wedge \mathbf{r}_2 = \text{ff})$

By i.h. on the second premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e_t|_1 : |\tau| \sim |e_t|_2 : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$

By i.h. on the third premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e_f|_1 : |\tau| \sim |e_f|_2 : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$

Applying rule BOOLCASE to the past three statements yields the required result.

Case. $\frac{}{\Gamma, x : \tau \vdash x : \tau}$

To show: $|\Gamma|, x_1 : |\tau|, x_2 : |\tau| \mid \lfloor \Gamma \rfloor_a, \lfloor \tau \rfloor_a(x_1, x_2) \vdash x_1 : |\tau| \sim x_2 : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$.

This follows immediately from rule VAR.

Case. $\frac{\Gamma, x : \tau_1 \vdash e : \tau_2}{\Gamma \vdash \lambda x. e : \tau_1 \rightarrow \tau_2}$

To show: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash \lambda x_1. |e|_1 : |\tau_1| \rightarrow |\tau_2| \sim \lambda x_2. |e|_2 : |\tau_1| \rightarrow |\tau_2| \mid \forall x_1, x_2. \lfloor \tau_1 \rfloor_a(x_1, x_2) \Rightarrow \lfloor \tau_2 \rfloor_a(\mathbf{r}_1 x_1, \mathbf{r}_2 x_2)$.

By i.h. on the premise: $|\Gamma|, x_1 : |\tau_1|, x_2 : |\tau_2| \mid \lfloor \Gamma \rfloor_a, \lfloor \tau_1 \rfloor_a(x_1, x_2) \vdash |e|_1 : |\tau_2| \sim |e|_2 : |\tau_2| \mid \lfloor \tau_2 \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$.

Applying rule ABS immediately yields the required result.

Case. $\frac{\Gamma \vdash e : \tau_1 \rightarrow \tau_2 \quad \Gamma \vdash e' : \tau_1}{\Gamma \vdash e e' : \tau_2}$

To show: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e|_1 |e'|_1 : |\tau_2| \sim |e|_2 |e'|_2 : |\tau_2| \mid \lfloor \tau_2 \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$.

By i.h. on the first premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e|_1 : |\tau_1| \rightarrow |\tau_2| \sim |e|_2 : |\tau_1| \rightarrow |\tau_2| \mid \forall x_1, x_2. \lfloor \tau_1 \rfloor_a(x_1, x_2) \Rightarrow \lfloor \tau_2 \rfloor_a(\mathbf{r}_1 x_1, \mathbf{r}_2 x_2)$

By i.h. on the second premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e'|_1 : |\tau_1| \sim |e'|_2 : |\tau_1| \mid \lfloor \tau_1 \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$

Applying rule APP immediately yields the required result.

Case. $\frac{\Gamma \vdash e : \tau \quad \Gamma \vdash e' : \tau'}{\Gamma \vdash \langle e, e' \rangle : \tau \times \tau'}$

To show: $|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash \langle |e|_1, |e'|_1 \rangle : |\tau| \times |\tau'| \sim \langle |e|_2, |e'|_2 \rangle : |\tau| \times |\tau'| \mid \lfloor \tau \rfloor_a(\pi_1(\mathbf{r}_1), \pi_1(\mathbf{r}_2)) \wedge \lfloor \tau' \rfloor_a(\pi_2(\mathbf{r}_1), \pi_2(\mathbf{r}_2))$.

By i.h. on the first premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \lfloor \tau \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$

By i.h. on the second premise:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash |e'|_1 : |\tau'| \sim |e'|_2 : |\tau'| \mid \lfloor \tau' \rfloor_a(\mathbf{r}_1, \mathbf{r}_2)$

The required result follows from the rule PAIR. We only need to show the third premise of the rule, i.e., the following in HOL:

$$\forall x_1 x_2 y_1 y_2. \lfloor \tau \rfloor_a(x_1, x_2) \Rightarrow \lfloor \tau' \rfloor_a(y_1, y_2) \Rightarrow (\lfloor \tau \rfloor_a(\pi_1 \langle x_1, y_1 \rangle, \pi_1 \langle x_2, y_2 \rangle) \wedge \lfloor \tau' \rfloor_a(\pi_2 \langle x_1, y_1 \rangle, \pi_2 \langle x_2, y_2 \rangle))$$

Since $\pi_1\langle x_1, y_1 \rangle = x_1$, etc., this implication simplifies to:

$$\forall x_1 x_2 y_1 y_2. \llbracket \tau \rrbracket_a(x_1, x_2) \Rightarrow \llbracket \tau' \rrbracket_a(y_1, y_2) \Rightarrow (\llbracket \tau \rrbracket_a(x_1, x_2) \wedge \llbracket \tau' \rrbracket_a(y_1, y_2))$$

which is an obvious tautology.

$$\text{Case. } \frac{\Gamma \vdash e : \tau \times \tau'}{\Gamma \vdash \pi_1(e) : \tau}$$

To show: $|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash \pi_1(|e|_1) : |\tau| \sim \pi_1(|e|_2) : |\tau| \mid \llbracket \tau \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$.

By i.h. on the premise:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \times |\tau'| \sim |e|_2 : |\tau| \times |\tau'| \mid \llbracket \tau \rrbracket_a(\pi_1(\mathbf{r}_1), \pi_1(\mathbf{r}_2)) \wedge \llbracket \tau' \rrbracket_a(\pi_2(\mathbf{r}_1), \pi_2(\mathbf{r}_2))$$

By rule SUB:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \times |\tau'| \sim |e|_2 : |\tau| \times |\tau'| \mid \llbracket \tau \rrbracket_a(\pi_1(\mathbf{r}_1), \pi_1(\mathbf{r}_2))$$

By rule PROJ₁, we get the required result.

$$\text{Case. } \frac{\Gamma \vdash e : \tau}{\Gamma \vdash \eta_\ell(e) : \mathbb{T}_\ell(\tau)}$$

To show: $|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$.

By i.h. on the premise: $|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \llbracket \tau \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$

(1)

If $\ell \sqsubseteq a$, then $\llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2) \triangleq \llbracket \tau \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$, so the required result is the same as (1).

If $\ell \not\sqsubseteq a$, then $\llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2) \triangleq \top$ and the required result follows from rule SUB applied to (1).

$$\text{Case. } \frac{\Gamma \vdash e : \mathbb{T}_\ell(\tau) \quad \Gamma, x : \tau \vdash e' : \tau' \quad \tau' \searrow \ell}{\Gamma \vdash \text{bind}(e, x.e') : \tau'}$$

To show: $|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash (\lambda x. |e'|_1) |e|_1 : |\tau'| \sim (\lambda x. |e'|_2) |e|_2 : |\tau'| \mid \llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$.

By i.h. on the first premise:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

(1)

By i.h. on the second premise:

$$|\Gamma|, x_1 : |\tau|, x_2 : |\tau| \mid \llbracket \Gamma \rrbracket_a, \llbracket \tau \rrbracket_a(x_1, x_2) \vdash |e'|_1 : |\tau'| \sim |e'|_2 : |\tau'| \mid \llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

(2)

We consider two cases:

Subcase. $\ell \sqsubseteq a$. Here, $\llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2) \triangleq \llbracket \tau \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$, so (1) can be rewritten to:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \llbracket \tau \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

(3)

Applying rule ABS to (2) yields:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash \lambda x_1. |e'|_1 : |\tau| \rightarrow |\tau'| \sim \lambda x_2. |e'|_2 : |\tau| \rightarrow |\tau'| \mid \forall x_1 x_2. \llbracket \tau \rrbracket_a(x_1, x_2) \Rightarrow \llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

(4)

Applying rule APP to (4) and (3) yields:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash (\lambda x_1. |e'|_1) |e|_1 : |\tau'| \sim (\lambda x_2. |e'|_2) |e|_2 : |\tau'| \mid \llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

which is what we wanted to prove.

Subcase. $\ell \not\sqsubseteq a$. Here, $\llbracket \mathbb{T}_\ell(\tau) \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2) \triangleq \top$, so (1) can be rewritten to:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash |e|_1 : |\tau| \sim |e|_2 : |\tau| \mid \top$$

(5)

Applying rule ABS to (2) yields:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash \lambda x_1. |e'|_1 : |\tau| \rightarrow |\tau'| \sim \lambda x_2. |e'|_2 : |\tau| \rightarrow |\tau'| \mid \forall x_1 x_2. \llbracket \tau \rrbracket_a(x_1, x_2) \Rightarrow \llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2)$$

By Lemma 13 applied to the subcase assumption $\ell \not\sqsubseteq a$ and the premise $\tau' \searrow \ell$, we have $\llbracket \tau' \rrbracket_a(\mathbf{r}_1, \mathbf{r}_2) \equiv \top$.

So, by rule SUB:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash \lambda x_1. |e'|_1 : |\tau| \rightarrow |\tau'| \sim \lambda x_2. |e'|_2 : |\tau| \rightarrow |\tau'| \mid \forall x_1 x_2. \llbracket \tau \rrbracket_a(x_1, x_2) \Rightarrow \top$$

Since $(\forall x_1 x_2. \llbracket \tau \rrbracket_a(x_1, x_2) \Rightarrow \top) \equiv \top \equiv (\forall x_1, x_2. \top \Rightarrow \top)$, we can use SUB again to get:

$$|\Gamma| \mid \llbracket \Gamma \rrbracket_a \vdash \lambda x_1. |e'|_1 : |\tau| \rightarrow |\tau'| \sim \lambda x_2. |e'|_2 : |\tau| \rightarrow |\tau'| \mid \forall x_1, x_2. \top \Rightarrow \top$$

(6)

Applying rule APP to (6) and (5) yields:

$|\Gamma| \mid \lfloor \Gamma \rfloor_a \vdash (\lambda x_1. |e'|_1) |e|_1 : |\tau'| \sim (\lambda x_2. |e'|_2) |e|_2 : |\tau'| \mid \top$
which is the same as our goal since $\lfloor \tau' \rfloor_a(\mathbf{r}_1, \mathbf{r}_2) \equiv \top$.

Proof of Theorem 15

By induction on the derivation of $\Delta; \Phi; \Omega \vdash_k^l t : A$. We will show few cases.

Case. $\frac{}{\Delta; \Phi_a; \Omega, x : A \vdash_0^0 x : A}$

We can conclude by the following derivation:

$$\frac{\frac{}{\lfloor \Omega \rfloor, x : \lfloor A \rfloor_v, \Delta \mid \Phi_a, \lfloor \Omega \rfloor, \lfloor A \rfloor_v(x) \vdash x : \lfloor A \rfloor_v \mid \lfloor A \rfloor_v(\mathbf{r})} \text{VAR} \quad \frac{}{\lfloor \Omega \rfloor, x : \lfloor A \rfloor_v, \Delta \mid \Phi_a, \lfloor \Omega \rfloor, \lfloor A \rfloor_v(x) \vdash 0 : \mathbb{N} \mid 0 \leq \mathbf{r} \leq 0} \text{NAT}}{\lfloor \Omega \rfloor, x : \lfloor A \rfloor_v, \Delta \mid \Phi_a, \lfloor \Omega \rfloor, \lfloor A \rfloor_v(x) \vdash (x, 0) : \lfloor A \rfloor_v \times \mathbb{N} \mid \lfloor A \rfloor_v(\pi_1 \mathbf{r}) \wedge 0 \leq \pi_2 \mathbf{r} \leq 0} \text{NAT}$$

where the additional proof conditions that is needed for the [PAIR-L] rule can be easily proved in HOL.

Case. $\frac{}{\Delta; \Phi_a; \Omega \vdash_0^0 n : \text{int}}$

Then we can conclude by the following derivation:

$$\frac{\frac{}{\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash n : \mathbb{N} \mid \top} \text{NAT} \quad \frac{}{\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash 0 : \mathbb{N} \mid 0 \leq \mathbf{r} \leq 0} \text{NAT}}{\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash (n, 0) : \mathbb{N} \times \mathbb{N} \mid 0 \leq \pi_2 \mathbf{r} \leq 0} \text{PAIR-L}$$

where the additional proof conditions that is needed for the [PAIR-L] rule can be easily proved in HOL.

Case. $\frac{\Delta; \Phi_a; x : A_1, \Omega \vdash_k^l t : A_2}{\Delta; \Phi_a; \Omega \vdash_0^0 \lambda x. t : A_1 \xrightarrow{\text{exec}(k, l)} A_2}$

By induction hypothesis we have $\lfloor \Omega \rfloor, x : \lfloor A_1 \rfloor_v, \Delta \mid \Phi, \lfloor \Omega \rfloor, \lfloor A_1 \rfloor_v(x) \vdash \langle t \rangle : \lfloor A_2 \rfloor_e \mid \lfloor A_2 \rfloor_e^{k, l}(\mathbf{r})$ and we can conclude by the following derivation:

$$\frac{\frac{\lfloor \Omega \rfloor, x : \lfloor A_1 \rfloor_v, \Delta \mid \Phi, \lfloor \Omega \rfloor, \lfloor A_1 \rfloor_v(x) \vdash \langle t \rangle : \lfloor A_2 \rfloor_e \mid \lfloor A_2 \rfloor_e^{k, l}(\mathbf{r})}{\lfloor \Omega \rfloor, \Delta \mid \Phi, \lfloor \Omega \rfloor \vdash \lambda x. \langle t \rangle : \lfloor A_1 \rfloor_v \rightarrow \lfloor A_2 \rfloor_e \mid \forall x. \lfloor A_1 \rfloor_v(x) \Rightarrow \lfloor A_2 \rfloor_e^{k, l}(\mathbf{r}x)} \text{ABS} \quad \frac{}{\lfloor \Omega \rfloor, \Delta \mid \Phi, \lfloor \Omega \rfloor \vdash 0 : \mathbb{N} \mid 0 \leq \mathbf{r} \leq 0} \text{NAT}}{\lfloor \Omega \rfloor, \Delta \mid \Phi, \lfloor \Omega \rfloor \vdash (\lambda x. \langle t \rangle, 0) : (\lfloor A_1 \rfloor_v \rightarrow \lfloor A_2 \rfloor_e) \times \mathbb{N} \mid \forall x. \lfloor A_1 \rfloor_v(x) \Rightarrow \lfloor A_2 \rfloor_e^{k, l}((\pi_1 \mathbf{r})x) \wedge 0 \leq \pi_2 \mathbf{r} \leq 0} \text{PAIR-L}$$

where the additional proof conditions that is needed for the [PAIR-L] rule can be easily proved in HOL.

Case $\frac{\Delta; \Phi_a; \Omega \vdash_{k_1}^{l_1} t_1 : A_1 \xrightarrow{\text{exec}(k, l)} A_2 \quad \Delta; \Phi_a; \Omega \vdash_{k_2}^{l_2} t_2 : A_1}{\Delta; \Phi_a; \Omega \vdash_{k_1+k_2+k+c_{app}}^{l_1+l_2+l+c_{app}} t_1 t_2 : A_2}$

By induction hypothesis and unfolding some some definitions we have

$$\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash \langle t_1 \rangle : (\lfloor A_1 \rfloor_v \rightarrow (\lfloor A_2 \rfloor_v \times \mathbb{N})) \times \mathbb{N} \mid \forall h. \lfloor A_1 \rfloor_v(h) \Rightarrow (\lfloor A_2 \rfloor_v(\pi_1((\pi_1 \mathbf{r})h)) \wedge k \leq \pi_2((\pi_1 \mathbf{r})h) \leq l) \wedge k_1 \leq \pi_2(\mathbf{r}) \leq l_1$$

and $\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash \langle t_2 \rangle : \lfloor A_1 \rfloor_v \times \mathbb{N} \mid \lfloor A_1 \rfloor_v(\pi_1 \mathbf{r}) \wedge k_2 \leq \pi_2(\mathbf{r}) \leq l_2$. So, we can prove:

$$\lfloor \Omega \rfloor, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash \text{let } x = \langle t_1 \rangle \text{ in let } y = \langle t_2 \rangle \text{ in } \pi_1(x) \pi_1(y) : \lfloor A_2 \rfloor_v \times \mathbb{N} \mid \lfloor A_2 \rfloor_v(\pi_1 \mathbf{r}) \wedge k \leq \pi_2(\mathbf{r}) \leq l \wedge k_1 \leq \pi_2(x) \leq l_1 \wedge k_2 \leq \pi_2(y) \mathbf{r} \leq l_2$$

This combined with the definition of the cost-passing translation $\langle t_1 t_2 \rangle \triangleq \text{let } x = \langle t_1 \rangle \text{ in let } y = \langle t_2 \rangle \text{ in let } z = \pi_1(x) \pi_1(y) \text{ in } (\pi_1(z), \pi_2(x) + \pi_2(y) + \pi_2(z) + c_{app})$ allows us to prove as required the following:

$$\langle \Omega \rangle, \Delta \mid \Phi_a, \lfloor \Omega \rfloor \vdash \langle t_1 t_2 \rangle : \langle \llbracket A_2 \rrbracket \rangle_v \times \mathbb{N} \mid \llbracket A_2 \rrbracket_v(\pi_1(\mathbf{r})) \wedge k + k_1 + k_2 + c_{app} \leq \pi_2(\mathbf{r}) \leq l + l_1 + l_2 + c_{app}.$$

Proof of Theorem 16

To prove Theorem 16, we need three lemmas.

LEMMA C.1. *Suppose $\Delta; \Phi \vdash \tau$ wf.³ Then, the following hold:*

- (1) $\Delta \mid \Phi \vdash \forall xy. \llbracket \tau \rrbracket_v(x, y) \Rightarrow \llbracket \bar{\tau} \rrbracket_v(x) \wedge \llbracket \bar{\tau} \rrbracket_v(y)$
- (2) $\Delta \mid \Phi \vdash \forall xy. \llbracket \tau \rrbracket_e^t(x, y) \Rightarrow \llbracket \bar{\tau} \rrbracket_e^{0, \infty}(x) \wedge \llbracket \bar{\tau} \rrbracket_e^{0, \infty}(y)$

Also, (3) $\llbracket \Gamma \rrbracket \Rightarrow \llbracket \bar{\Gamma}_1 \rrbracket \wedge \llbracket \bar{\Gamma}_2 \rrbracket$ where $\bar{\Gamma}_1$ and $\bar{\Gamma}_2$ are obtained by replacing each variable x in $\bar{\Gamma}$ with x_1 and x_2 , respectively.

PROOF. (1) and (2) follow by a simultaneous induction on the given judgment. (3) follows immediately from (1). \square

LEMMA C.2. *If $\Delta; \Phi_a; \Gamma \vdash e_1 \ominus e_2 \lesssim t : \tau$ in RelCost, then $\Delta; \Phi; \bar{\Gamma} \vdash_0^\infty e_i : \bar{\tau}$ for $i \in \{1, 2\}$ in RelCost.*

PROOF. By induction on the given derivation. \square

LEMMA C.3. *If $\Delta; \Phi \models \tau_1 \sqsubseteq \tau_2$, then $\Delta; \Phi \vdash \forall xy. \llbracket \tau_1 \rrbracket_v(x, y) \Rightarrow \llbracket \tau_2 \rrbracket_v(x, y)$.*

PROOF. By induction on the given derivation of $\Delta; \Phi \models \tau_1 \sqsubseteq \tau_2$. \square

PROOF OF THEOREM 16. The proof is by induction on the given derivation of $\Delta; \Phi; \Gamma \vdash t_1 \ominus t_2 \lesssim k : \tau$. We show only a few representative cases here.

$$\frac{i :: S, \Delta; \Phi_a; \Gamma \vdash e \ominus e' \lesssim t : \tau \quad i \notin \text{FIV}(\Phi_a; \Gamma)}{\text{R-I LAM}}$$

Case: $\Delta; \Phi_a; \Gamma \vdash \Lambda e \ominus \Lambda e' \lesssim 0 : \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau$

To show: $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash (\lambda_{-} \langle e \rangle_1, 0) : (\mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e) \times \mathbb{N} \sim (\lambda_{-} \langle e' \rangle_2, 0) : (\mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e) \times \mathbb{N} \mid \llbracket \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau \rrbracket_e^0(\mathbf{r}_1, \mathbf{r}_2)$.

Expand $\llbracket \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau \rrbracket_e^0(\mathbf{r}_1, \mathbf{r}_2)$ to $\llbracket \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau \rrbracket_v(\pi_1 \mathbf{r}_1, \pi_2 \mathbf{r}_2) \wedge \pi_2 \mathbf{r}_1 - \pi_2 \mathbf{r}_2 \leq 0$, and apply the rule [PAIR] to reduce to two proof obligations:

- (A) $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash \lambda_{-} \langle e \rangle_1 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \sim \lambda_{-} \langle e' \rangle_2 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \mid \llbracket \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau \rrbracket_v(\mathbf{r}_1, \mathbf{r}_2)$
- (B) $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash 0 : \mathbb{N} \sim 0 : \mathbb{N} \mid \mathbf{r}_1 - \mathbf{r}_2 \leq 0$

(B) follows immediately by rule [ZERO]. To prove (A), expand $\llbracket \forall i \stackrel{\text{diff}(t)}{\vdash} S. \tau \rrbracket_v(\mathbf{r}_1, \mathbf{r}_2)$ and apply rule $[\wedge_1]$. We get three proof obligations.

(C) $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash \lambda_{-} \langle e \rangle_1 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \sim \lambda_{-} \langle e' \rangle_2 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \mid \llbracket \forall i \stackrel{\text{exec}(0, \infty)}{\vdash} S. \bar{\tau} \rrbracket_v(\mathbf{r}_1)$

(D) $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash \lambda_{-} \langle e \rangle_1 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \sim \lambda_{-} \langle e' \rangle_2 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \mid \llbracket \forall i \stackrel{\text{exec}(0, \infty)}{\vdash} S. \bar{\tau} \rrbracket_v(\mathbf{r}_2)$

(E) $\llbracket \Gamma \rrbracket, \Delta \mid \Phi_a, \llbracket \Gamma \rrbracket \vdash \lambda_{-} \langle e \rangle_1 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \sim \lambda_{-} \langle e' \rangle_2 : \mathbb{N} \rightarrow \langle \llbracket \tau \rrbracket \rangle_e \mid \forall z_1 z_2. \top \Rightarrow \forall i. \llbracket \tau \rrbracket_e^t(\mathbf{r}_1 z_1, \mathbf{r}_2 z_2)$

To prove (C), apply Lemma C.2 to the given derivation (not just the premise), obtaining a RelCost derivation for $\Delta; \Phi_a; \bar{\Gamma} \vdash_0^\infty \Lambda e : (\forall i \stackrel{\text{exec}(0, \infty)}{\vdash} S. \bar{\tau})$. Applying Theorem 15 to this yields $(\bar{\Gamma}), \Delta \mid \Phi_a, \llbracket \bar{\Gamma} \rrbracket \vdash (\lambda_{-} \langle e \rangle, 0) : (\mathbb{N} \rightarrow \langle \llbracket \bar{\tau} \rrbracket \rangle_e) \times \mathbb{N} \mid \llbracket \forall i \stackrel{\text{exec}(0, \infty)}{\vdash} S. \bar{\tau} \rrbracket_e^{0, \infty}(\mathbf{r})$ in UHOL, which is the same as $(\bar{\Gamma}), \Delta \mid \Phi_a, \llbracket \bar{\Gamma} \rrbracket \vdash (\lambda_{-} \langle e \rangle, 0) : (\mathbb{N} \rightarrow \langle \llbracket \bar{\tau} \rrbracket \rangle_e) \times$

³This judgment simply means that τ is well-formed in the context $\Delta; \Phi$. It is defined in the original RelCost paper (Çiçek et al. 2017).

$\mathbb{N} \mid \lfloor \forall i \stackrel{\text{exec}(0,\infty)}{\vdots} S. \bar{\tau} \rfloor_v(\pi_1 \mathbf{r}) \wedge 0 \leq \pi_2 \mathbf{r} \leq \infty$. Applying rule [PROJ₁], we get $(\bar{\Gamma}), \Delta \mid \Phi_a, \lfloor \bar{\Gamma} \rfloor \vdash \pi_1(\lambda_{\cdot}(\langle e \rangle), 0) : \mathbb{N} \rightarrow (\|\bar{\tau}\|)_e \mid \lfloor \forall i \stackrel{\text{exec}(0,\infty)}{\vdots} S. \bar{\tau} \rfloor_v(\mathbf{r})$. By subject conversion, $(\bar{\Gamma}), \Delta \mid \Phi_a, \lfloor \bar{\Gamma} \rfloor \vdash \lambda_{\cdot}(\langle e \rangle) : \mathbb{N} \rightarrow (\|\bar{\tau}\|)_e \mid \lfloor \forall i \stackrel{\text{exec}(0,\infty)}{\vdots} S. \bar{\tau} \rfloor_v(\mathbf{r})$.

Renaming variables, we get $(\bar{\Gamma})_1, \Delta \mid \Phi_a, \lfloor \bar{\Gamma}_1 \rfloor \vdash \lambda_{\cdot}(\langle e \rangle)_1 : \mathbb{N} \rightarrow (\|\bar{\tau}\|)_e \mid \lfloor \forall i \stackrel{\text{exec}(0,\infty)}{\vdots} S. \bar{\tau} \rfloor_v(\mathbf{r})$.

Now note that by definition, $\|\Gamma\| \supseteq (\bar{\Gamma})_1$ and by Lemma C.1(3), $\lfloor \Gamma \rfloor \Rightarrow \lfloor \bar{\Gamma}_1 \rfloor$. Hence, we also get $\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash \lambda_{\cdot}(\langle e \rangle)_1 : \mathbb{N} \rightarrow (\|\bar{\tau}\|)_e \mid \lfloor \forall i \stackrel{\text{exec}(0,\infty)}{\vdots} S. \bar{\tau} \rfloor_v(\mathbf{r})$. (C) follows immediately by rule [UHOL-L].

(D) has a similar proof.

To prove (E), apply the rule [ABS], getting the obligation:

$$\|\Gamma\|, \Delta, z_1, z_2 : \mathbb{N} \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e' \rangle)_2 : (\|\tau\|)_e \mid \forall i. \lfloor \tau \rfloor_e^t(\mathbf{r}_1, \mathbf{r}_2)$$

Since z_1, z_2 do not appear anywhere else, we can strengthen the context to remove them, thus reducing to:

$$\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e' \rangle)_2 : (\|\tau\|)_e \mid \forall i. \lfloor \tau \rfloor_e^t(\mathbf{r}_1, \mathbf{r}_2)$$

Next, we transpose to HOL using Theorem 4. We get the obligation:

$$\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash \forall i. \lfloor \tau \rfloor_e^t(\langle e \rangle_1, \langle e' \rangle_2)$$

This is equivalent to:

$$\|\Gamma\|, \Delta, i : S \mid \Phi_a, \lfloor \Gamma \rfloor \vdash \lfloor \tau \rfloor_e^t(\langle e \rangle_1, \langle e' \rangle_2)$$

The last statement follows immediately from i.h. on the premise, followed by transposition to HOL using Theorem 4.

$$\Delta; \Phi_a; \Gamma \vdash e \ominus e \lesssim t : \tau \quad \forall x \in \text{dom}(\Gamma). \Delta; \Phi_a \models \Gamma(x) \sqsubseteq \square \Gamma(x) \quad \text{NOCHANGE}$$

Case: $\Delta; \Phi_a; \Gamma, \Gamma'; \Omega \vdash e \ominus e \lesssim 0 : \square \tau$

To show: $\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \lfloor \square \tau \rfloor_e^0(\mathbf{r}_1, \mathbf{r}_2)$.

Expanding the definition of $\lfloor \square \tau \rfloor_e^0$, this is equivalent to:

$$\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \lfloor \tau \rfloor_v(\pi_1 \mathbf{r}_1, \pi_2 \mathbf{r}_2) \wedge (\pi_1 \mathbf{r}_1 = \pi_1 \mathbf{r}_2) \wedge (\pi_2 \mathbf{r}_1 - \pi_2 \mathbf{r}_2 \leq 0)$$

Using rule [\wedge_1], we reduce this to two obligations:

$$(A) \|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \lfloor \tau \rfloor_v(\pi_1 \mathbf{r}_1, \pi_2 \mathbf{r}_2)$$

$$(B) \|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid (\pi_1 \mathbf{r}_1 = \pi_1 \mathbf{r}_2) \wedge (\pi_2 \mathbf{r}_1 - \pi_2 \mathbf{r}_2 \leq 0)$$

By i.h. on the first premise,

$$\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \lfloor \tau \rfloor_v(\pi_1 \mathbf{r}_1, \pi_2 \mathbf{r}_2) \wedge (\pi_2 \mathbf{r}_1 - \pi_2 \mathbf{r}_2 \leq t)$$

By rule [SUB],

$$\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \lfloor \tau \rfloor_v(\pi_1 \mathbf{r}_1, \pi_2 \mathbf{r}_2)$$

which is the same as (A).

To prove (B), apply Lemma C.3 to the second premise to get for every $x \in \text{dom}(\Gamma)$ that $\Delta \mid \Phi_a \vdash \lfloor \Gamma(x) \rfloor_v(x_1, x_2) \Rightarrow \lfloor \square \Gamma(x) \rfloor_v(x_1, x_2)$. Since $\lfloor \square \Gamma(x) \rfloor_v(x_1, x_2) \Rightarrow x_1 = x_2$ and from $\lfloor \Gamma \rfloor$ we know that $\lfloor \Gamma(x) \rfloor_v(x_1, x_2)$, it follows that $\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash x_1 = x_2$. Since this holds for every $x \in \text{dom}(\Gamma)$, it follows immediately that $\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 = (\langle e \rangle)_2$. By Theorem 4, $\|\Gamma\|, \Delta \mid \Phi_a, \lfloor \Gamma \rfloor \vdash (\langle e \rangle)_1 : (\|\tau\|)_e \sim (\langle e \rangle)_2 : (\|\tau\|)_e \mid \mathbf{r}_1 = \mathbf{r}_2$. (B) follows immediately by rule [SUB].

□

D EXAMPLES

Factorial

This example shows that the two following implementations of factorial, with and without accumulator, are equivalent:

$$\begin{aligned} \text{fact}_1 &\triangleq \text{letrec } f_1 \text{ } n_1 = \text{case } n_1 \text{ of } 0 \mapsto 1; S \mapsto \lambda x_1. Sx_1 * (f_1 x_1) \\ \text{fact}_2 &\triangleq \text{letrec } f_2 \text{ } n_2 = \lambda \text{acc}. \text{case } n_2 \text{ of } 0 \mapsto \text{acc}; S \mapsto \lambda x_2. f_2 x_2 (Sx_2 * \text{acc}) \end{aligned}$$

Our goal is to prove that:

$$\emptyset \mid \emptyset \vdash \text{fact}_1 : \mathbb{N} \rightarrow \mathbb{N} \sim \text{fact}_2 : \mathbb{N} \rightarrow \mathbb{N} \rightarrow \mathbb{N} \mid \forall n_1 n_2. n_1 = n_2 \Rightarrow \forall \text{acc}. (\mathbf{r}_1 \text{ } n_1) * \text{acc} = \mathbf{r}_2 \text{ } n_2 \text{ } \text{acc}$$

Since both programs do the same number of iterations, we can do synchronous reasoning for the recursion at the head of the programs. However, the bodies of the functions have different types since fact_2 receives an extra argument, the accumulator. Therefore, we will need a one-sided application of [ABS-R], before we can go back to reasoning synchronously. We will then apply the [CASE] rule, knowing that both terms reduce to the same branch, since $n_1 = n_2$. On the zero branch, we will need to prove the trivial equality $1 * \text{acc} = \text{acc}$. On the successor branch, we will need to prove that $Sx * (\text{fact } x) * \text{acc} = \text{fact}_2 x_2 (Sx_2 * \text{acc})$, knowing by induction hypothesis that such a property holds for every m less than x .

Now we will expand on the details. We start the proof applying the [LETREC] rule, which has 2 premises:

- (1) Both functions are well-defined
- (2) $n_1 = n_2, \forall y_1 y_2. (y_1, y_2) < (n_1, n_2) \Rightarrow y_1 = y_2 \Rightarrow \forall \text{acc}. (f_1 y_1) * \text{acc} = f_2 y_2 \text{ } \text{acc} \vdash \text{case } n_1 \text{ of } 0 \mapsto 1; S \mapsto \lambda x_1. Sx_1 * (f_1 x_1) \sim \text{case } n_2 \text{ of } 0 \mapsto \text{acc}; S \mapsto \lambda x_2. f_2 x_2 (Sx_2 * \text{acc}) \mid n_1 = n_2 \Rightarrow \forall \text{acc}. \mathbf{r}_1 * \text{acc} = \mathbf{r}_2 \text{ } \text{acc}$

We assume that the first premise is provable.

To prove the second premise, we start by applying ABS-R, which leaves the following proof obligation:

$$\begin{aligned} &n_1 = n_2, \forall y_1 y_2. (y_1, y_2) < (n_1, n_2) \Rightarrow y_1 = y_2 \Rightarrow \forall \text{acc}. (f_1 y_1) * \text{acc} = f_2 y_2 \text{ } \text{acc}, n_1 = n_2 \vdash \\ &\text{case } n_1 \text{ of } 0 \mapsto 1; S \mapsto \lambda x_1. Sx_1 * (f_1 x_1) \sim \text{case } n_2 \text{ of } 0 \mapsto \text{acc}; S \mapsto \lambda x_2. f_2 x_2 (Sx_2 * \text{acc}) \mid \mathbf{r}_1 * \text{acc} = \mathbf{r}_2 \end{aligned}$$

Now we can apply [CASE], and we have 3 premises, where Ψ denotes the axioms of the previous judgment:

- $\Psi \vdash n_1 \sim n_2 \mid \mathbf{r}_1 = 0 \Leftrightarrow \mathbf{r}_2 = 0$
- $\Psi, n_1 = 0, n_2 = 0 \vdash 1 \sim \text{acc} \mid \mathbf{r}_1 * \text{acc} = \mathbf{r}_2$
- $\Psi \vdash \lambda x_1. Sx_1 * (f_1 x_1) \sim \lambda x_2. f_2 x_2 (Sx_2 * \text{acc}) \mid \forall x_1 x_2. n_1 = Sx_1 \Rightarrow n_2 = Sx_2 \Rightarrow (\mathbf{r}_1 x_1) * \text{acc} = \mathbf{r}_2 x_2$

Premise 1 is a direct consequence of $n_1 = n_2$. Premise 2 is a trivial arithmetic identity. To prove premise 3, we first apply the ABS rule:

$$\Psi, n_1 = Sx_1, n_2 = Sx_2 \vdash Sx_1 * (f_1 x_1) \sim f_2 x_2 (Sx_2 * \text{acc}) \mid \mathbf{r}_1 * \text{acc} = \mathbf{r}_2$$

and then by Theorem 4 we can finish the proof in HOL by deriving.

$$\Psi, n_1 = Sx_1, n_2 = Sx_2 \vdash Sx_1 * (f_1 x_1) * \text{acc} = f_2 x_2 (Sx_2 * \text{acc})$$

From the premises we can first prove that $(x_1, x_2) < (n_1, n_2)$ so by the inductive hypothesis from the [LETREC] rule, and the $[\Rightarrow_E]$ rule, we get

$$\forall \text{acc}. (f_1 x_1) * \text{acc} = f_2 x_2 \text{ } \text{acc},$$

which we then instantiate with $Sx_1 * \text{acc}$ to get

$$(f_1 x_1) * Sx_1 * \text{acc} = f_2 x_2 (Sx_1 * \text{acc}).$$

On the other hand, from the hypotheses we also have $x_1 = x_2$, so by [CONV] we finally prove

$$(f_1 x_1) * Sx_1 * \text{acc} = f_2 x_2 (Sx_2 * \text{acc})$$

List reversal

A related example for lists is the equivalence of reversal with and without accumulator. The structure of the proof is the same as in the factorial example, but we will briefly show it to illustrate how the LISTCASE rule is used. The functions are written:

$$\begin{aligned} \text{rev}_1 &\triangleq \text{letrec } f_1 \text{ } l_1 = \text{case } l_1 \text{ of } [] \mapsto []; - :: - \mapsto \lambda h_1. \lambda t_1. (f_1 \ t_1) ++ [x_1] \\ \text{rev}_2 &\triangleq \text{letrec } f_2 \text{ } l_2 = \lambda \text{acc}. \text{case } l_2 \text{ of } [] \mapsto \text{acc}; - :: - \mapsto \lambda h_2. \lambda t_2. f_2 \ t_2 \ (h_2 :: \text{acc}) \end{aligned}$$

We want to prove they are related by the following judgment:

$$\emptyset \mid \emptyset \vdash \text{rev}_1 : \text{list}_\tau \rightarrow \text{list}_\tau \sim \text{rev}_2 : \text{list}_\tau \rightarrow \text{list}_\tau \mid \forall l_1, l_2. l_1 = l_2 \Rightarrow \forall \text{acc}. (\mathbf{r}_1 \ l_1) ++ \text{acc} = \mathbf{r}_2 \ l_2 \ \text{acc}$$

By the [LETREC] rule, we have to prove 2 premises:

- (1) Both functions are well-defined.
- (2) $l_1 = l_2, \forall m_1 m_2. (|m_1|, |m_2|) < (|l_1|, |l_2|) \Rightarrow m_1 = m_2 \Rightarrow \forall \text{acc}. (f_1 \ m_1) ++ \text{acc} = f_2 \ m_2 \ \text{acc} \vdash \text{case } l_1 \text{ of } [] \mapsto []; - :: - \mapsto \lambda h_1. \lambda t_1. (f_1 \ t_1) ++ [x_1] \sim \lambda \text{acc}. \text{case } l_2 \text{ of } [] \mapsto \text{acc}; - :: - \mapsto \lambda h_2. \lambda t_2. f_2 \ t_2 \ (h_2 :: \text{acc}) \mid \forall \text{acc}. \mathbf{r}_1 ++ \text{acc} = \mathbf{r}_2 \ \text{acc}$

For the second premise, similarly as in factorial, we apply ABS-R. We have the following premise, where Ψ denotes the axioms in the previous judgment:

$$\Psi \vdash \text{case } l_1 \text{ of } [] \mapsto []; - :: - \mapsto \lambda h_1. \lambda t_1. (f_1 \ t_1) ++ [x_1] \sim \text{case } l_2 \text{ of } [] \mapsto \text{acc}; - :: - \mapsto \lambda h_2. \lambda t_2. f_2 \ t_2 \ (h_2 :: \text{acc}) \mid \mathbf{r}_1 ++ \text{acc} = \mathbf{r}_2$$

and then LISTCASE, which has three premises:

- $\Psi \vdash l_1 \sim l_2 \mid \mathbf{r}_1 = [] \Leftrightarrow \mathbf{r}_2 = []$
- $\Psi, l_1 = [], l_2 = [] \vdash [] \sim \text{acc} \mid \mathbf{r}_1 ++ \text{acc} = \mathbf{r}_2$
- $\Psi \vdash \lambda h_1. \lambda t_1. (f_1 \ t_1) ++ [x_1] \sim \lambda h_2. \lambda t_2. f_2 \ t_2 \ (h_2 :: \text{acc}) \mid \forall h_1 t_1 h_2 t_2. l_1 = h_1 :: t_1 \Rightarrow l_2 = h_2 :: t_2 \Rightarrow \mathbf{r}_1 ++ \text{acc} = \mathbf{r}_2$

We complete the proof in a similar way as in the factorial example.

Proof of Theorem 17

We will use without proof two unary lemmas:

Lemma 24. • | • $\vdash \text{take} : \text{list}_{\mathbb{N}} \rightarrow \mathbb{N} \rightarrow \text{list}_{\mathbb{N}} \mid \forall l n. |r \ l \ n| = \min(n, |l|)$

Lemma 25. • | • $\vdash \text{map} : \text{list}_{\mathbb{N}} \rightarrow (\mathbb{N} \rightarrow \mathbb{N}) \rightarrow \text{list}_{\mathbb{N}} \mid \forall l f. |r \ l \ f| = |l|$

We want to prove

$$l_1 = l_2, n_1 = n_2, g_1 = g_2 \vdash \text{map}(\text{take } l_1 \ n_1) \ g_1 \sim \text{take}(\text{map } l_2 \ g_2) \ n_2 \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2 \wedge |\mathbf{r}_1| = \min(n_1, |l_1|) \wedge |\mathbf{r}_2| = \min(n_2, |l_2|)$$

where $\mathbf{r}_1 \sqsubseteq \mathbf{r}_2$ is the prefix ordering and is defined as an inductive predicate:

$$\forall l. [] \sqsubseteq l \qquad \forall h l_1 l_2. l_1 \sqsubseteq l_2 \Rightarrow h :: l_1 \sqsubseteq h :: l_2$$

By the helping lemmas and Lemma 8, it suffices to prove just the first conjunct:

$$l_1 = l_2, n_1 = n_2, g_1 = g_2 \vdash \text{map}(\text{take } l_1 \ n_1) \ g_1 \sim \text{take}(\text{map } l_2 \ g_2) \ n_2 \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2$$

The derivation begins by applying the APP-R rule. We get the following judgment on n_2 :

$$l_1 = l_2, n_1 = n_2, g_1 = g_2 \vdash n_2 \mid \mathbf{r} \geq |\text{take } l_1 \ n_1| \tag{1}$$

and a main premise:

$$l_1 = l_2, n_1 = n_2, g_1 = g_2 \vdash \text{map}(\text{take } l_1 \ n_1) \ g_1 \sim \text{take}(\text{map } l_2 \ g_2) \mid \forall x_2. x_2 \geq |\text{take } l_1 \ n_1| \Rightarrow \mathbf{r}_1 \sqsubseteq (\mathbf{r}_2 \ x_2) \quad (2)$$

Notice that we have chosen the premise $x_2 \geq |\text{take } l_1 \ n_1|$ because we are trying to prove $\mathbf{r}_1 \sqsubseteq (\mathbf{r}_2 \ x_2)$, which is only true if we take a larger prefix on the right than on the left. The judgment (1) is easily proven from the fact that $|\text{take } l_1 \ n_1| = \min(n_1, |l_1|) \leq n_1 = n_2$, which we get from the lemmas. To prove (2) we first apply APP-L with a trivial condition $g_1 = g_2$ on g_1 . Then we apply APP and we have two premises:

$$\begin{aligned} \text{(A)} \quad & \Psi \vdash \text{take } l_1 \ n_1 \sim \text{map } l_2 \ g_2 \mid \mathbf{r}_1 \sqsubseteq_{g_2} \mathbf{r}_2 \\ \text{(B)} \quad & \Psi \vdash \text{map} \sim \text{take} \mid \forall m_1 m_2. m_1 \sqsubseteq_{g_2} m_2 \Rightarrow (\forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |m_1| \Rightarrow (\mathbf{r}_1 \ m_1 \ g_1) \sqsubseteq (\mathbf{r}_2 \ m_2 \ x_2)) \end{aligned}$$

where \sqsubseteq_g is defined as an inductive predicate parametrized by g :

$$\forall l. [] \sqsubseteq_g l \qquad \forall h l_1 l_2. l_1 \sqsubseteq_g l_2 \Rightarrow h :: l_1 \sqsubseteq_g (gh) :: l_2$$

We first show how to prove (A). We start by applying APP with a trivial condition for the arguments to get:

$$\Psi \vdash \text{take } l_1 \sim \text{map } l_2 \mid \forall x_1 g_2. (\mathbf{r}_1 \ x_1) \sqsubseteq_{g_2} (\mathbf{r}_2 \ g_2)$$

We then apply APP, which has two premises, one of them equating l_1 and l_2 . The other one is:

$$\Psi \vdash \text{take} \sim \text{map} \mid \forall m_1 m_2. m_1 = m_2 \Rightarrow \forall x_1 g_2. (\mathbf{r}_1 \ m_1 \ x_1) \sqsubseteq_{g_2} (\mathbf{r}_2 \ m_2 \ g_2)$$

To complete this branch of the proof, we apply LETREC. We need to prove the following premise:

$$\Psi, m_1 = m_2, \forall k_1 k_2. (k_1, k_2) < (m_1, m_2) \Rightarrow k_1 = k_2 \Rightarrow \forall x_1 g_2. (f_1 \ k_1 \ x_1) \sqsubseteq_{g_2} (f_2 \ k_2 \ g_2) \vdash \lambda n_1. e_1 \sim \lambda g_2. e_2 \mid \forall x_1 g_2. (\mathbf{r}_1 \ x_1) \sqsubseteq_{g_2} (\mathbf{r}_2 \ g_2)$$

Where e_1, e_2 abbreviate the bodies of the functions:

$$\begin{aligned} e_1 &\triangleq \text{case } m_1 \text{ of } [] \mapsto [] \\ &\quad ; - :: - \mapsto \lambda h_1 t_1. \text{case } x_1 \text{ of } 0 \mapsto [] \\ &\quad \quad ; S \mapsto \lambda y_1. h_1 :: f_1 \ t_1 \ y_1 \\ e_2 &\triangleq \text{case } m_2 \text{ of } [] \mapsto [] \\ &\quad ; - :: - \mapsto \lambda h_2 t_2. (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \end{aligned}$$

If we apply ABS we get a premise:

$$\Psi, m_1 = m_2, \forall k_1 k_2. (k_1, k_2) < (m_1, m_2) \Rightarrow k_1 = k_2 \Rightarrow \forall x_1 g_2. (f_1 \ k_1 \ x_1) \sqsubseteq_{g_2} (f_2 \ k_2 \ g_2) \vdash e_1 \sim e_2 \mid \mathbf{r}_1 \sqsubseteq_f \mathbf{r}_2$$

And now we can apply a synchronous CASE rule, since we have a premise $m_1 = m_2$. This yields 3 proof obligations, where Ψ' is the set of axioms in the previous judgment:

$$\begin{aligned} \text{(A.1)} \quad & \Psi' \vdash m_1 \sim m_2 \mid \mathbf{r}_1 = [] \Leftrightarrow \mathbf{r}_2 = [] \\ \text{(A.2)} \quad & \Psi' \vdash [] \sim [] \mid \mathbf{r}_1 \sqsubseteq_f \mathbf{r}_2 \\ \text{(A.3)} \quad & \Psi' \vdash \lambda h_1 t_1. \text{case } x_1 \text{ of } 0 \mapsto [] ; S \mapsto \lambda y_1. h_1 :: f_1 \ t_1 \ y_1 \sim \\ & \quad \lambda h_2 t_2. (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \mid \forall h_1 t_1 h_2 t_2. m_1 = h_1 :: t_1 \Rightarrow m_2 = h_2 :: t_2 \Rightarrow (\mathbf{r}_1 \ h_1 \ t_1) \sqsubseteq_{g_2} (\mathbf{r}_2 \ h_2 \ t_2) \end{aligned}$$

Premises (A.1) and (A.2) are trivial. To prove (A.3) we first apply ABS twice:

$$\Psi', m_1 = h_1 :: t_1, m_2 = h_2 :: t_2 \vdash \text{case } n_1 \text{ of } 0 \mapsto [] ; S \mapsto \lambda y_1. h_1 :: f_1 \ t_1 \ y_1 \sim (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \mid \mathbf{r}_1 \sqsubseteq_{g_2} \mathbf{r}_2$$

Next, we apply CASE-L, which has the following two premises:

$$\begin{aligned} \text{(A.3.i)} \quad & \Psi', m_1 = h_1 :: t_1, m_2 = h_2 :: t_2, n_1 = 0 \vdash [] \sim (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \mid \mathbf{r}_1 \sqsubseteq_{g_2} \mathbf{r}_2 \\ \text{(A.3.ii)} \quad & \Psi', m_1 = h_1 :: t_1, m_2 = h_2 :: t_2 \vdash \lambda y_1. h_1 :: f_1 \ t_1 \ y_1 \sim (g_2 \ h_2) :: (f_2 \ t_2 \ g_2) \mid \forall y_1. n_1 = S y_1 \Rightarrow (\mathbf{r}_1 \ y_1) \sqsubseteq_{g_2} \mathbf{r}_2 \end{aligned}$$

Premise (A.3.i) can be directly derived in HOL from the definition of \sqsubseteq_{g_2} . To prove (A.3.ii) we need to make use of our inductive hypothesis:

$$\forall k_1 k_2. (k_1, k_2) < (m_1, m_2) \Rightarrow k_1 = k_2 \Rightarrow \forall x_1 g_2. (f_1 k_1 x_1) \sqsubseteq_{g_2} (f_2 k_2 g_2)$$

In particular, from the premises $m_1 = h_1 :: t_1$ and $m_2 = h_2 :: t_2$ we can deduce $(t_1, t_2) < (m_1, m_2)$. Additionally, from the premise $m_1 = m_2$ we prove $t_1 = t_2$. Therefore, from the inductive hypothesis we derive $\forall x_1 g_2. (f_1 t_1 x_1) \sqsubseteq_{g_2} (f_2 t_2 g_2)$, and by definition of \sqsubseteq_{g_2} , and the fact that $h_1 = h_2$, for every y we can prove $h_1 :: (f_1 t_1 y) \sqsubseteq_{g_2} (g_2 h_2) :: f_2 t_2$. By Theorem 4, we can prove (A.3.ii).

We will now show how to prove (B) :

$$\Psi \vdash \text{map} \sim \text{take} \mid \forall m_1 m_2. m_1 \sqsubseteq_{g_2} m_2 \Rightarrow (\forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |m_1| \Rightarrow (\mathbf{r}_1 m_1 g_1) \sqsubseteq (\mathbf{r}_2 m_2 x_2))$$

On this branch we will also use LETREC. We have to prove a premise:

$$\Psi, \Phi \vdash \lambda g_1. e_2 \sim \lambda x_2. e_1 \mid \forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |m_1| \Rightarrow (\mathbf{r}_1 g_1) \sqsubseteq (\mathbf{r}_2 x_2)$$

where

$$\Phi \triangleq \forall k_1 k_2. (k_1, k_2) < (m_1, m_2) \Rightarrow k_1 \sqsubseteq_{g_2} k_2 \Rightarrow (\forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |k_1| \Rightarrow (\mathbf{r}_1 k_1 g_1) \sqsubseteq (\mathbf{r}_2 k_2 x_2))$$

We start by applying ABS. Our goal is to prove:

$$\Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2 \vdash \begin{array}{l} \text{case } m_1 \text{ of } [] \mapsto [] \\ ; - :: - \mapsto \lambda h_1 t_1. (g_1 h_1) :: (f_1 t_1 g_1) \end{array} \sim \begin{array}{l} \text{case } m_2 \text{ of } [] \mapsto [] \\ ; - :: - \mapsto \lambda h_2 t_2. \text{case } x_2 \text{ of } 0 \mapsto [] \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2 \\ ; S \mapsto \lambda y_2. h_2 :: f_2 t_2 y_2 \end{array}$$

Notice that we have α -renamed the variables to have the appropriate subscript. Now we want to apply a CASE rule, but the lists over which we are matching are not necessarily of the same length. Therefore, we use the asynchronous LISTCASE-A rule. We have to prove four premises:

$$(B.1) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = [], m_2 = [] \vdash [] \sim [] \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2$$

$$(B.2) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = [] \vdash [] \sim []$$

$$\lambda h_2 t_2. \text{case } x_2 \text{ of } 0 \mapsto [] ; S \mapsto \lambda y_2. h_2 :: f_2 t_2 y_2 \mid \forall h_2 t_2. m_2 = h_2 :: t_2 \Rightarrow \mathbf{r}_1 \sqsubseteq (\mathbf{r}_2 h_2 t_2)$$

$$(B.3) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_2 = [] \vdash \lambda h_1 t_1. (g_1 h_1) :: (f_1 t_1 g_1) \sim [] \mid \forall h_1 t_1. m_1 = h_1 :: t_1 \Rightarrow (\mathbf{r}_1 h_1 t_1) \sqsubseteq \mathbf{r}_2$$

$$(B.4) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2 \vdash \lambda h_1 t_1. (g_1 h_1) :: (f_1 t_1 g_1) \sim$$

$$\lambda h_2 t_2. \text{case } x_2 \text{ of } 0 \mapsto [] ; S \mapsto \lambda y_2. h_2 :: f_2 t_2 y_2 \mid$$

$$\forall h_1 t_1 h_2 t_2. m_1 = h_1 :: t_1 \Rightarrow m_2 = h_2 :: t_2 \Rightarrow (\mathbf{r}_1 h_1 t_1) \sqsubseteq (\mathbf{r}_2 h_2 t_2)$$

Premises (B.1) and (B.2) are trivially derived from the definition of the \sqsubseteq predicate. To prove premise (B.3) we see that we have premises $m_1 \sqsubseteq_{g_2} m_2$, $m_2 = []$, and $m_1 = h_1 :: t_1$, from which we can derive a contradiction.

It remains to prove (B.4). To do so, we apply ABS twice and then NATCASE-R, which has two premises:

$$(B.4.i) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = h_1 :: t_1, m_2 = h_1 :: t_1, x_2 = 0 \vdash (g_1 h_1) :: (f_1 t_1 g_1) \sim [] \mid \mathbf{r}_1 \sqsubseteq \mathbf{r}_2$$

$$(B.4.ii) \Psi, \Phi, x_2 \geq |m_1|, g_1 = g_2, m_1 = h_1 :: t_1, m_2 = h_1 :: t_1 \vdash (g_1 h_1) :: (f_1 t_1 g_1) \sim \lambda y_2. h_2 :: f_2 t_2 y_2 \mid$$

$$\forall y_2. x_2 = S y_2 \Rightarrow \mathbf{r}_1 \sqsubseteq (\mathbf{r}_2 y_2)$$

To prove (B.4.i) we derive a contradiction between the premises. From $x_2 = 0$ and the premise $x_2 \geq |m_1|$ we derive $m_1 = []$ and, together with $m_1 = h_1 :: t_1$ we arrive at a contradiction by applying NC.

To prove (B.4.ii) we need to use the induction hypothesis. From $m_1 = h_1 :: t_1$, $m_2 = h_1 :: t_1$ we can prove that $|t_1| < |m_1|$ and $|t_2| < |m_2|$, so we can do a CUT with the i.h. and derive:

$$t_1 \sqsubseteq_{g_2} t_2 \Rightarrow (\forall g_1. g_1 = g_2 \Rightarrow \forall x_2. x_2 \geq |t_1| \Rightarrow (f_1 t_1 g_1) \sqsubseteq (f_2 t_2 x_2))$$

By assumption, $m_1 \sqsubseteq_{g_2} m_2$, so $t_1 \sqsubseteq_{g_2} t_2$. Moreover, also by assumption $g_1 = g_2$, and $Sy_2 = x_2 \geq |m_1| = S|t_1|$, so $y_2 \geq |t_1|$. So if we instantiate the i.h. with g_1 and y_2 , and apply CUT again, we can prove:

$$(f_1 t_1 g_1) \sqsubseteq (f_2 t_2 y_2)$$

On the other hand, since $h_1 :: t_1 \sqsubseteq_{g_2} h_2 :: t_2$, then (by elimination of \sqsubseteq_{g_2}) we can derive $g_1 h_1 = h_2$ and by definition of \sqsubseteq , $(g_1 h_1) :: (f_1 t_1 g_1) \sqsubseteq h_2 :: (f_2 t_2 y_2)$. So we can apply Theorem 4 and prove (B.4.ii). This ends the proof. \square

Proof of Theorem 18

We need two straightforward lemmas in UHOL. The lemmas state that sorting preserves the length and minimum element of a list.

Lemma 26. Let $\tau \triangleq \text{list}_{\mathbb{N}} \rightarrow \text{list}_{\mathbb{N}}$. Then, (1) $\bullet \mid \bullet \vdash \text{insert} : \mathbb{N} \rightarrow \tau \mid \forall x l. |\pi_1(\mathbf{r} x l)| = 1 + |l|$, and (2) $\bullet \mid \bullet \vdash \text{isort} : \tau \mid \forall x. |\pi_1(\mathbf{r} x)| = |x|$.

Lemma 27. Let $\tau \triangleq \text{list}_{\mathbb{N}} \rightarrow \text{list}_{\mathbb{N}}$. Then, (1) $\bullet \mid \bullet \vdash \text{insert} : \mathbb{N} \rightarrow \tau \mid \forall x l. \text{lmin}(\pi_1(\mathbf{r} x l)) = \min(x, \text{lmin}(l))$, and (2) $\bullet \mid \bullet \vdash \text{isort} : \tau \mid \forall x. \text{lmin}(\pi_1(\mathbf{r} x)) = \text{lmin}(x)$.

PROOF OF THEOREM 18. We prove the theorem using LETREC. We actually show the following stronger theorem, which yields a stronger induction hypothesis in the proof.

$\bullet \mid \bullet \vdash \text{isort} : \tau \sim \text{isort} : \tau \mid \forall x_1 x_2. (\text{sorted}(x_1) \wedge |x_1| = |x_2|) \Rightarrow (\pi_2(\mathbf{r}_1 x_1) \leq \pi_2(\mathbf{r}_2 x_2)) \wedge \underline{(\mathbf{r}_1 x_1 = \text{isort } x_1) \wedge (\mathbf{r}_2 x_2 = \text{isort } x_2)}$

Let ι denote the inductive hypothesis:

$$\begin{aligned} \iota &\triangleq \forall m_1 m_2. (|m_1|, |m_2|) < (|x_1|, |x_2|) \Rightarrow (\text{sorted}(m_1) \wedge |m_1| = |m_2|) \\ &\Rightarrow \pi_2(\text{isort}_1 m_1) \leq \pi_2(\text{isort}_2 m_2) \wedge (\text{isort}_1 m_1 = \text{isort } m_1) \wedge (\text{isort}_2 m_2 = \text{isort } m_2) \end{aligned}$$

and e denote the body of the function `isort`:

$$\begin{aligned} e &\triangleq \text{case } l \text{ of } [] \mapsto ([], 0); \\ &\quad _ :: _ \mapsto \lambda h t. \text{ let } s = \text{isort } t \\ &\quad \quad \text{let } s' = \text{insert } h (\pi_1 s) \text{ in} \\ &\quad \quad (\pi_1 s', (\pi_2 s) + (\pi_2 s')) \end{aligned}$$

By LETREC, it suffices to prove the following (we omit simple types for easier reading; they play no essential role in the proof).

$$\text{isort}_1, \text{isort}_2, x_1, x_2 \mid \text{sorted}(x_1), |x_1| = |x_2|, \iota \vdash e[\text{isort}_1/\text{isort}][x_1/l] \sim e[\text{isort}_2/\text{isort}][x_2/l] \mid \left(\begin{array}{l} \pi_2 \mathbf{r}_1 \leq \pi_2 \mathbf{r}_2 \\ \wedge \mathbf{r}_1 = \text{isort } x_1 \\ \wedge \mathbf{r}_2 = \text{isort } x_2 \end{array} \right)$$

Following the structure of e , we next apply the rule LISTCASE. This yields the following two main proof obligations, corresponding to the two case branches (the third proof obligation, $x_1 = [] \Leftrightarrow x_2 = []$ follows immediately from the assumption $|x_1| = |x_2|$).

$$\text{isort}_1, \text{isort}_2, x_1, x_2 \mid \text{sorted}(x_1), |x_1| = |x_2|, \iota, x_1 = x_2 = [] \vdash ([], 0) \sim ([], 0) \mid (\pi_2 \mathbf{r}_1 \leq \pi_2 \mathbf{r}_2) \wedge (\mathbf{r}_1 = \text{isort } x_1) \wedge (\mathbf{r}_2 = \text{isort } x_2) \quad (1)$$

$$\begin{array}{l} \text{isort}_1, \text{isort}_2, x_1, x_2, h_1, t_1, h_2, t_2 \mid \\ \text{sorted}(x_1), |x_1| = |x_2|, \\ \iota, \underline{x_1 = h_1 :: t_1}, \underline{x_2 = h_2 :: t_2} \end{array} \quad \begin{array}{l} \vdash \text{ let } s = \text{isort}_1 t_1 \\ \text{let } s' = \text{insert } h_1 (\pi_1 s) \text{ in} \\ (\pi_1 s', (\pi_2 s) + (\pi_2 s')) \end{array} \quad \sim \quad \begin{array}{l} \text{let } s = \text{isort}_2 t_2 \\ \text{let } s' = \text{insert } h_2 (\pi_1 s) \text{ in} \\ (\pi_1 s', (\pi_2 s) + (\pi_2 s')) \end{array} \quad \left| \begin{array}{l} \pi_2 \mathbf{r}_1 \leq \pi_2 \mathbf{r}_2 \\ \wedge \mathbf{r}_1 = \text{isort } x_1 \\ \wedge \mathbf{r}_2 = \text{isort } x_2 \end{array} \right. \quad (2)$$

(1) is immediate: By Theorem 4, it suffices to show that $(\pi_2([], 0) \leq \pi_2([], 0)) \wedge (([], 0) = \text{isort } x_1) \wedge (([], 0) = \text{isort } x_2)$. Since $x_1 = x_2 = []$ by assumption here, this is equivalent to $(\pi_2([], 0) \leq \pi_2([], 0)) \wedge (([], 0) = \text{isort } []) \wedge (([], 0) = \text{isort } [])$, which is trivial by direct computation.

To prove (2), we expand the outermost occurrences of let in both to function applications using the definition $\text{let } x = e_1 \text{ in } e_2 \triangleq (\lambda x. e_2) e_1$. Applying the rules APP and ABS, it suffices to prove the following for any ϕ of our choice.

$$\text{isort } t_1, \text{isort } t_2, x_1, x_2, h_1, t_1, h_2, t_2 \left| \begin{array}{l} \text{sorted}(x_1), |x_1| = |x_2|, \\ \iota, x_1 = h_1 :: t_1, x_2 = h_2 :: t_2 \end{array} \right. \vdash \text{isort } t_1 \ t_1 \ \sim \ \text{isort } t_2 \ t_2 \left| \phi \quad (3)$$

$$\begin{array}{l} \text{isort } t_1, \text{isort } t_2, x_1, x_2, h_1, t_1, h_2, t_2, s_1, s_2 \mid \\ \text{sorted}(x_1), |x_1| = |x_2|, \\ \iota, x_1 = h_1 :: t_1, x_2 = h_2 :: t_2 \\ \underline{\phi[s_1/r_1][s_2/r_2]} \end{array} \vdash \begin{array}{l} \text{let } s' = \text{insert } h_1 (\pi_1 s_1) \text{ in} \\ (\pi_1 s', (\pi_2 s_1) + (\pi_2 s')) \end{array} \sim \begin{array}{l} \text{let } s' = \text{insert } h_2 (\pi_1 s_2) \text{ in} \\ (\pi_1 s', (\pi_2 s_2) + (\pi_2 s')) \end{array} \left| \begin{array}{l} \pi_2 \mathbf{r}_1 \leq \pi_2 \mathbf{r}_2 \\ \wedge \mathbf{r}_1 = \text{isort } x_1 \\ \wedge \mathbf{r}_2 = \text{isort } x_2 \end{array} \right. \quad (4)$$

We choose ϕ as follows:

$$\phi \triangleq \pi_2 \mathbf{r}_1 \leq \pi_2 \mathbf{r}_2 \wedge \mathbf{r}_1 = \text{isort}(t_1) \wedge \mathbf{r}_2 = \text{isort}(t_2) \wedge |\pi_1 \mathbf{r}_1| = |\pi_1 \mathbf{r}_2| \wedge \text{lmin}(t_1) = \text{lmin}(\pi_1 \mathbf{r}_1)$$

Proof of (3): By Theorem 4, it suffices to prove the following five statements in HOL under the context of (3). These statements correspond to the five conjuncts of ϕ .

$$\pi_2(\text{isort } t_1 \ t_1) \leq \pi_2(\text{isort } t_2 \ t_2) \quad (5)$$

$$\text{isort } t_1 \ t_1 = \text{isort } t_1 \quad (6)$$

$$\text{isort } t_1 \ t_2 = \text{isort } t_2 \quad (7)$$

$$|\pi_1(\text{isort } t_1 \ t_1)| = |\pi_1(\text{isort } t_2 \ t_2)| \quad (8)$$

$$\text{lmin}(t_1) = \text{lmin}(\pi_1(\text{isort } t_1 \ t_1)) \quad (9)$$

(5)–(7) follow from the induction hypothesis ι instantiated with $m_1 := t_1, m_2 := t_2$. Note that because $x_1 = h_1 :: t_1$ and $x_2 = h_2 :: t_2$, we can prove (in HOL) that $(|t_1|, |t_2|) < (|x_1|, |x_2|)$. Since, $|x_1| = |x_2|$, $x_1 = h_1 :: t_1$ and $x_2 = h_2 :: t_2$, we can also prove that $|t_1| = |t_2|$. Finally, from the axiomatic definition of sorted and the assumption $\text{sorted}(x_1)$ it follows that $\text{sorted}(t_1)$. These together allow us to instantiate the i.h. ι and immediately derive (5)–(7).

To prove (8), we use (6) and (7), which reduces (8) to $|\pi_1(\text{isort } t_1)| = |\pi_1(\text{isort } t_2)|$. To prove this, we apply Theorem 1 to Lemma 26, yielding $\forall x. |\pi_1(\text{isort } x)| = |x|$. Hence, we can further reduce our goal to proving $|t_1| = |t_2|$, which we already did above.

To prove (9), we use (6), which reduces (9) to $\text{lmin}(t_1) = \text{lmin}(\pi_1(\text{isort } t_1))$. This follows immediately from Theorem 1 applied to Lemma 27.

This proves (3).

Proof of (4): We expand the definition of let and apply the rules APP and ABS to reduce (4) to proving the following for any ϕ' .

$$\text{isort}_{t_1}, \text{isort}_{t_2}, x_1, x_2, \left. \begin{array}{l} \text{sorted}(x_1), |x_1| = |x_2|, \\ \iota, x_1 = h_1 :: t_1, x_2 = h_2 :: t_2, \vdash \text{insert } h_1 (\pi_1 s_1) \sim \text{insert } h_2 (\pi_1 s_2) \\ \phi[s_1/r_1][s_2/r_2] \end{array} \right| \phi' \quad (10)$$

$$\begin{array}{l} \text{isort}_{t_1}, \text{isort}_{t_2}, x_1, x_2, h_1, t_1, h_2, t_2, s_1, s_2, s'_1, s'_2 \mid \\ \text{sorted}(x_1), |x_1| = |x_2|, \\ \iota, x_1 = h_1 :: t_1, x_2 = h_2 :: t_2 \\ \phi[s_1/r_1][s_2/r_2], \phi'[s'_1/r_1][s'_2/r_2] \end{array} \quad \vdash (\pi_1 s'_1, (\pi_2 s_1) + (\pi_2 s'_1)) \sim (\pi_1 s'_2, (\pi_2 s_2) + (\pi_2 s'_2)) \quad \left. \begin{array}{l} \pi_2 r_1 \leq \pi_2 r_2 \\ \wedge r_1 = \text{isort } x_1 \\ \wedge r_2 = \text{isort } x_2 \end{array} \right| \quad (11)$$

We pick the following ϕ' :

$$\phi' \triangleq \pi_2 r_1 \leq \pi_2 r_2 \wedge r_1 = \text{insert } h_1 (\pi_1 s_1) \wedge r_2 = \text{insert } h_2 (\pi_1 s_2)$$

Proof of (10): We start by applying Theorem 4. This yields three subgoals in HOL, corresponding to the three conjuncts in ϕ' :

$$\pi_2(\text{insert } h_1 (\pi_1 s_1)) \leq \pi_2(\text{insert } h_2 (\pi_1 s_2)) \quad (12)$$

$$\text{insert } h_1 (\pi_1 s_1) = \text{insert } h_1 (\pi_1 s_1) \quad (13)$$

$$\text{insert } h_2 (\pi_1 s_2) = \text{insert } h_2 (\pi_1 s_2) \quad (14)$$

(13) and (14) are trivial, so we only have to prove (12). Since $s_1 = \text{isort } t_1$ and $s_2 = \text{isort } t_2$ are conjuncts in the assumption $\phi[s_1/r_1][s_2/r_2]$, (12) is equivalent to:

$$\pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))) \leq \pi_2(\text{insert } h_2 (\pi_1(\text{isort } t_2))) \quad (15)$$

To prove this, we split cases on the shapes of $\pi_1(\text{isort } t_1)$ and $\pi_1(\text{isort } t_2)$. From the conjuncts in $\phi[s_1/r_1][s_2/r_2]$, it follows immediately that $|\pi_1(\text{isort } t_1)| = |\pi_1(\text{isort } t_2)|$. Hence, only two cases apply:

Case: $\pi_1(\text{isort } t_1) = \pi_1(\text{isort } t_2) = []$. In this case, by direct computation, $\pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))) = \pi_2(\text{insert } h_1 []) = \pi_2([h_1], 0) = 0$. Similarly, and $\pi_2(\text{insert } h_2 (\pi_1(\text{isort } t_2))) = 0$. So, the result follows trivially.

Case: $\pi_1(\text{isort } t_1) = h'_1 :: t'_1$ and $\pi_1(\text{isort } t_2) = h'_2 :: t'_2$. We first argue that $h_1 \leq h'_1$. Note that from the second and fifth conjuncts in $\phi[s_1/r_1][s_2/r_2]$, it follows that $\text{lmin}(t_1) = \text{lmin}(\pi_1(\text{isort } t_1))$. Since $\pi_1(\text{isort } t_1) = h'_1 :: t'_1$, we further get $\text{lmin}(t_1) = \text{lmin}(\pi_1(\text{isort } t_1)) = \text{lmin}(h'_1 :: t'_1) = \min(h'_1, \text{lmin}(t'_1)) \leq h'_1$. Finally, from the axiomatic definition of $\text{sorted}(x_1)$ and $x_1 = h_1 :: t_1$, we derive $h_1 \leq \text{lmin}(t_1)$. Combining, we get $h_1 \leq \text{lmin}(t_1) \leq h'_1$.

Next, $\pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))) = \pi_2(\text{insert } h_1 (h'_1 :: t'_1))$. Expanding the definition of insert and using $h_1 \leq h'_1$, we immediately get $\pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))) = \pi_2(\text{insert } h_1 (h'_1 :: t'_1)) = \pi_2(h_1 :: h'_1 :: t'_1, 1) = 1$. On the other hand, it is fairly easy to prove (by case analyzing the result of $h_2 \leq h'_2$) that $\pi_2(\text{insert } h_2 (\pi_1(\text{isort } t_2))) = \pi_2(\text{insert } h_2 (h'_2 :: t'_2)) \geq 1$. Hence, $\pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))) = 1 \leq \pi_2(\text{insert } h_2 (\pi_1(\text{isort } t_2)))$.

This proves (15) and, hence, (12) and (10).

Proof of (11): By Theorem 4, it suffices to show the following in HOL, under the assumptions of (11):

$$\pi_2(\pi_1 s'_1, (\pi_2 s_1) + (\pi_2 s'_1)) \leq \pi_2(\pi_1 s'_2, (\pi_2 s_2) + (\pi_2 s'_2)) \quad (16)$$

$$(\pi_1 s'_1, (\pi_2 s_1) + (\pi_2 s'_1)) = \text{isort } x_1 \quad (17)$$

$$(\pi_1 s'_2, (\pi_2 s_2) + (\pi_2 s'_2)) = \text{isort } x_2 \quad (18)$$

By computation, (16) is equivalent to $(\pi_2 s_1) + (\pi_2 s'_1) \leq (\pi_2 s_2) + (\pi_2 s'_2)$. Using the definition of ϕ , it is easy to see that $\pi_2 s_1 \leq \pi_2 s_2$ is a conjunct in the assumption $\phi[s_1/\mathbf{r}_1][s_2/\mathbf{r}_2]$. Similarly, using the definition of ϕ' , $\pi_2 s'_1 \leq \pi_2 s'_2$ is a conjunct in the assumption $\phi'[s'_1/\mathbf{r}_1][s'_2/\mathbf{r}_2]$. (16) follows immediately from these.

To prove (17), note that since $x_1 = h_1 :: t_1$, expanding the definition of isort , we get

$$\text{isort } x_1 = (\pi_1(\text{insert } h_1 (\pi_1(\text{isort } t_1))), \pi_2(\text{isort } t_1) + \pi_2(\text{insert } h_1 (\pi_1(\text{isort } t_1))))$$

Matching with the left side of (17), it suffices to show that $s'_1 = \text{insert } h_1 (\pi_1(\text{isort } t_1))$ and $s_1 = \text{isort } t_1$. These are immediate: $s_1 = \text{isort } t_1$ is a conjunct in the assumption $\phi[s_1/\mathbf{r}_1][s_2/\mathbf{r}_2]$, while $s'_1 = \text{insert } h_1 (\pi_1(\text{isort } t_1))$ follows trivially from this and the conjunct $s'_1 = \text{insert } h_1 (\pi_1 s_1)$ in $\phi'[s'_1/\mathbf{r}_1][s'_2/\mathbf{r}_2]$. This proves (17).

The proof of (18) is similar to that of (17).

This proves (11) and, hence, (4). □

E FULL RHOL RULES

The full set of RHOL rules is in the following figures:

$\frac{\Gamma, x_1 : \tau_1, x_2 : \tau_2 \mid \Psi, \phi' \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \lambda x_1. t_1 : \tau_1 \rightarrow \sigma_1 \sim \lambda x_2. t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1][\mathbf{r}_2 \ x_2/\mathbf{r}_2]} \text{ ABS}$	
$\frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \tau_2 \rightarrow \sigma_2 \mid \forall x_1, x_2. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1][\mathbf{r}_2 \ x_2/\mathbf{r}_2] \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi'}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim t_2 u_2 : \sigma_2 \mid \phi[u_1/x_1][u_2/x_2]} \text{ APP}$	
$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[0/\mathbf{r}_1][0/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash 0 : \mathbb{N} \sim 0 : \mathbb{N} \mid \phi} \text{ ZERO}$	$\frac{\Gamma \mid \Psi \vdash t_1 : \mathbb{N} \sim t_2 : \mathbb{N} \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi[Sx_1/\mathbf{r}_1][Sx_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash St_1 : \mathbb{N} \sim St_2 : \mathbb{N} \mid \phi} \text{ SUCC}$
$\frac{\Gamma \mid \Psi \vdash \phi[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \quad \Gamma \vdash x_1 : \sigma_1 \quad \Gamma \vdash x_1 : \sigma_1}{\Gamma \mid \Psi \vdash x_1 : \sigma_1 \sim x_2 : \sigma_2 \mid \phi} \text{ VAR}$	$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\text{tt}/\mathbf{r}_1][\text{tt}/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \text{tt} : \mathbb{B} \sim \text{tt} : \mathbb{B} \mid \phi} \text{ TRUE}$
$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\text{ff}/\mathbf{r}_1][\text{ff}/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \text{ff} : \mathbb{B} \sim \text{ff} : \mathbb{B} \mid \phi} \text{ FALSE}$	$\frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[[]/\mathbf{r}_1][[]/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash [] : \text{list}_{\sigma_1} \sim [] : \text{list}_{\sigma_2} \mid \phi} \text{ NIL}$
$\frac{\Gamma \mid \Psi \vdash h_1 : \sigma_1 \sim h_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash t_1 : \text{list}_{\sigma_1} \sim t_2 : \text{list}_{\sigma_2} \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1 y_2. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi''[y_1/\mathbf{r}_1][y_2/\mathbf{r}_2] \Rightarrow \phi[x_1 :: y_1/\mathbf{r}_1][x_2 :: y_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash h_1 :: t_1 : \text{list}_{\sigma_1} \sim h_2 :: t_2 : \text{list}_{\sigma_2} \mid \phi} \text{ CONS}$	
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim u_2 : \tau_2 \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1 y_2. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi''[y_1/\mathbf{r}_1][y_2/\mathbf{r}_2] \Rightarrow \phi[\langle x_1, y_1 \rangle/\mathbf{r}_1][\langle x_2, y_2 \rangle/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \langle t_1, u_1 \rangle : \sigma_1 \times \tau_1 \sim \langle t_2, u_2 \rangle : \sigma_2 \times \tau_2 \mid \phi} \text{ PAIR}$	
$\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \times \tau_2 \mid \phi[\pi_i(\mathbf{r}_1)/\mathbf{r}_1][\pi_i(\mathbf{r}_2)/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \pi_i(t_1) : \sigma_1 \sim \pi_i(t_2) : \sigma_2 \mid \phi} \text{ PROJ}_i$	

Fig. 12. Core two-sided rules

$$\begin{array}{c}
\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \phi'[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2] \Rightarrow \phi[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{SUB} \\
\\
\frac{\Gamma \mid \Psi' \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi \quad \Gamma \mid \Psi' \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi'}{\Gamma \mid \Psi' \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi \wedge \phi'} \wedge_1 \\
\\
\frac{\Gamma \mid \Psi', \phi'[t_1/\mathbf{r}_1][t_2/\mathbf{r}_2] \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi' \vdash t_1 : \sigma_2 \sim t_2 : \sigma_2 \mid \phi' \Rightarrow \phi} \Rightarrow_1 \\
\\
\frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \mid \phi[\mathbf{r}/\mathbf{r}_1][t_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_1 \mid \phi} \text{UHOL-L}
\end{array}$$

Fig. 13. Structural rules

$$\begin{array}{c}
 \frac{\Gamma, x_1 : \tau_1 \mid \Psi, \phi' \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \lambda x_1. t_1 : \tau_1 \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall x_1. \phi' \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1]} \text{ABS-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \tau_1 \rightarrow \sigma_1 \sim u_2 : \sigma_2 \mid \forall x_1. \phi'[x_1/\mathbf{r}_1] \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1] \quad \Gamma \mid \Psi \vdash u_1 : \sigma_1 \mid \phi'[u_1/x_1]}{\Gamma \mid \Psi \vdash t_1 u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi} \text{APP-L} \\
 \\
 \frac{\Gamma \vdash t_2 : \sigma_2 \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \phi[0/\mathbf{r}_1][t_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash 0 : \mathbb{N} \sim t_2 : \sigma_2 \mid \phi} \text{ZERO-L} \quad \frac{\Gamma \mid \Psi \vdash t_1 : \mathbb{N} \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi[Sx_1/\mathbf{r}_1][x_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash St_1 : \mathbb{N} \sim t_2 : \sigma_2 \mid \phi} \text{SUCC-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\text{tt}/\mathbf{r}_1][t_2/\mathbf{r}_2] \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash \text{tt} : \mathbb{B} \sim t_2 : \sigma_2 \mid \phi} \text{TRUE-L} \quad \frac{\Gamma \mid \Psi \vdash_{\text{HOL}} \phi[\text{ff}/\mathbf{r}_1][t_2/\mathbf{r}_2] \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash \text{ff} : \mathbb{B} \sim t_2 : \sigma_2 \mid \phi} \text{FALSE-L} \\
 \\
 \frac{\phi[x_1/\mathbf{r}_1] \in \Psi \quad \mathbf{r}_2 \notin FV(\phi) \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash x_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{VAR-L} \quad \frac{\Gamma \mid \Psi \vdash \phi[[]/\mathbf{r}_1][t_2/\mathbf{r}_2] \quad \Gamma \vdash t_2 : \sigma_2}{\Gamma \mid \Psi \vdash [] : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi} \text{NIL-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash h_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash t_1 : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi''[y_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi[x_1 :: y_1/\mathbf{r}_1][x_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash h_1 :: t_1 : \text{list}_{\sigma_1} \sim t_2 : \sigma_2 \mid \phi} \text{CONS-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi' \quad \Gamma \mid \Psi \vdash u_1 : \tau_1 \sim t_2 : \sigma_2 \mid \phi'' \quad \Gamma \mid \Psi \vdash_{\text{HOL}} \forall x_1 x_2 y_1. \phi'[x_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi''[y_1/\mathbf{r}_1][x_2/\mathbf{r}_2] \Rightarrow \phi[\langle x_1, y_1 \rangle/\mathbf{r}_1][x_2/\mathbf{r}_2]}{\Gamma \mid \Psi \vdash \langle t_1, u_1 \rangle : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \mid \phi} \text{PAIR-L} \\
 \\
 \frac{\Gamma \mid \Psi \vdash t_1 : \sigma_1 \times \tau_1 \sim t_2 : \sigma_2 \mid \phi[\pi_1(\mathbf{r}_1)/\mathbf{r}_1]}{\Gamma \mid \Psi \vdash \pi_1(t_1) : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{PROJ}_1\text{-L}
 \end{array}$$

Fig. 14. Core one-sided rules

$$\begin{array}{c}
\frac{\Gamma \mid \Psi \vdash t_1 : \mathbb{B} \sim t_2 : \mathbb{B} \mid (r_1 = \text{tt} \wedge r_2 = \text{tt}) \vee (r_1 = \text{ff} \wedge r_2 = \text{ff}) \\
\Gamma \mid \Psi, t_1 = \text{tt}, t_2 = \text{tt} \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 = \text{ff}, t_2 = \text{ff} \vdash v_1 : \sigma_1 \sim v_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of tt} \mapsto u_1; \text{ff} \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of tt} \mapsto u_2; \text{ff} \mapsto v_2 : \sigma_2 \mid \phi} \text{ BOOLCASE} \\
\\
\frac{\Gamma \mid \Psi \vdash t_1 : \mathbb{N} \sim t_2 : \mathbb{N} \mid r_1 = 0 \Leftrightarrow r_2 = 0 \\
\Gamma \mid \Psi, t_1 = 0, t_2 = 0 \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_1 x_2. t_1 = Sx_1 \Rightarrow t_2 = Sx_2 \Rightarrow \phi[r_1 x_1/r_1][r_2 x_2/r_2]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2 : \sigma_2 \mid \phi} \text{ NATCASE} \\
\\
\frac{\Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \text{list}_{\tau_2} \mid r_1 = [] \Leftrightarrow r_2 = [] \\
\Gamma \mid \Psi, t_1 = [], t_2 = [] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_1 h_2 l_1 l_2. t_1 = h_1 :: l_1 \Rightarrow t_2 = h_2 :: l_2 \Rightarrow \phi[r_1 h_1 l_1/r_1][r_2 h_2 l_2/r_2]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : \sigma_2 \mid \phi} \text{ LISTCASE}
\end{array}$$

Fig. 15. Synchronous case rules

$$\begin{array}{c}
\frac{\Gamma \vdash t_1 : \mathbb{B} \\
\Gamma \mid \Psi, t_1 = \text{tt} \vdash u_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 = \text{ff} \vdash v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of tt} \mapsto u_1; \text{ff} \mapsto v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{ BOOLCASE - L} \\
\\
\frac{\Gamma \vdash t_1 : \mathbb{N} \\
\Gamma \mid \Psi, t_1 = 0 \vdash u_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall x_1. t_1 = Sx_1 \Rightarrow \phi[r_1 x_1/r_1]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{ NATCASE - L} \\
\\
\frac{\Gamma \vdash t_1 : \text{list}_{\tau} \\
\Gamma \mid \Psi, t_1 = [] \vdash u_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \tau \rightarrow \text{list}_{\tau} \rightarrow \sigma_1 \sim t_2 : \sigma_2 \mid \forall h_1 l_1. t_1 = h_1 :: l_1 \Rightarrow \phi[r_1 h_1 l_1/r_1]}{\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi} \text{ LISTCASE - L}
\end{array}$$

Fig. 16. One-sided case rules

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \mathbb{B} \sim t_2 : \mathbb{B} \mid \top \\
\Gamma \mid \Psi, t_1 = \text{tt}, t_2 = \text{tt} \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 \neq \text{tt}, t_2 = \text{tt} \vdash v_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 = \text{tt}, t_2 \neq \text{tt} \vdash u_1 : \sigma_1 \sim v_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 \neq \text{tt}, t_2 \neq \text{tt} \vdash v_1 : \sigma_1 \sim v_2 : \sigma_2 \mid \phi \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of tt} \mapsto u_1; \text{ff} \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of tt} \mapsto u_2; \text{ff} \mapsto v_2 : \sigma_2 \mid \phi \quad \text{BBCASE - A}
\end{array}$$

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \mathbb{B} \sim t_2 : \mathbb{N} \mid \top \\
\Gamma \mid \Psi, t_1 = \text{tt}, t_2 = 0 \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 \neq \text{tt}, t_2 = 0 \vdash v_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 = \text{tt} \vdash u_1 : \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_2. t_2 = Sx_2 \Rightarrow \phi[\mathbf{r}_2 \ x_2/\mathbf{r}_2] \\
\Gamma \mid \Psi, t_1 \neq \text{tt} \vdash v_1 : \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_2. t_2 = Sx_2 \Rightarrow \phi[\mathbf{r}_2 \ x_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of tt} \mapsto u_1; \text{ff} \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2 : \sigma_2 \mid \phi \quad \text{BNCASE - A}
\end{array}$$

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \mathbb{B} \sim t_2 : \text{list}_{\tau_2} \mid \top \\
\Gamma \mid \Psi, t_1 = \text{tt}, t_2 = [] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 \neq \text{tt}, t_2 = [] \vdash v_1 : \sigma_1 \sim u_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_1 = \text{tt} \vdash u_1 : \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \forall h_2 l_2. t_2 = h_2 :: l_2 \Rightarrow \phi[\mathbf{r}_2 \ h_2 \ l_2/\mathbf{r}_2] \\
\Gamma \mid \Psi, t_1 \neq \text{tt} \vdash v_1 : \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \forall h_2 l_2. t_2 = h_2 :: l_2 \Rightarrow \phi[\mathbf{r}_2 \ h_2 \ l_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of tt} \mapsto u_1; \text{ff} \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : \sigma_2 \mid \phi \quad \text{BLCASE - A}
\end{array}$$

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \mathbb{N} \sim t_2 : \mathbb{N} \mid \top \\
\Gamma \mid \Psi, t_1 = 0, t_2 = 0 \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_2 = 0 \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim u_2 : \sigma_2 \mid \forall x_1. t_1 = Sx_1 \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1] \\
\Gamma \mid \Psi, t_1 = 0 \vdash u_1 : \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_2. t_2 = Sx_2 \Rightarrow \phi[\mathbf{r}_2 \ x_2/\mathbf{r}_2] \\
\Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_1 x_2. t_1 = Sx_1 \Rightarrow t_2 = Sx_2 \Rightarrow \phi[\mathbf{r}_1 \ x_1/\mathbf{r}_1][\mathbf{r}_2 \ x_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2 : \sigma_2 \mid \phi \quad \text{NNCASE - A}
\end{array}$$

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \text{list}_{\tau_2} \mid \top \\
\Gamma \mid \Psi, t_1 = [], t_2 = [] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi, t_2 = [] \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim u_2 : \sigma_2 \mid \forall h_1 l_1. t_1 = h_1 :: l_1 \Rightarrow \phi[\mathbf{r}_1 \ h_1 \ l_1/\mathbf{r}_1] \\
\Gamma \mid \Psi, t_1 = [] \vdash u_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_2. t_2 = h_2 :: l_2 \Rightarrow \phi[\mathbf{r}_2 \ h_2 \ l_2/\mathbf{r}_2] \\
\Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_1 h_2 l_1 l_2. t_1 = h_1 :: l_1 \Rightarrow t_2 = h_2 :: l_2 \Rightarrow \phi[\mathbf{r}_1 \ h_1 \ l_1/\mathbf{r}_1][\mathbf{r}_2 \ h_2 \ l_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : \sigma_2 \mid \phi \quad \text{LLCASE - A}
\end{array}$$

Fig. 17. Asynchronous case rules (selected)

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \mathbb{N} \sim t_2 : \mathbb{N} \mid \phi' \wedge \mathbf{r}_1 = 0 \Leftrightarrow \mathbf{r}_2 = 0 \\
\Gamma \mid \Psi, \phi'[0/\mathbf{r}_1][0/\mathbf{r}_2] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \mathbb{N} \rightarrow \sigma_1 \sim v_2 : \mathbb{N} \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi'[Sx_1/\mathbf{r}_1][Sx_2/\mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } 0 \mapsto u_1; S \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } 0 \mapsto u_2; S \mapsto v_2 : \sigma_2 \mid \phi \quad \text{NATCASE*}
\end{array}$$

$$\begin{array}{c}
\Gamma \mid \Psi \vdash t_1 : \text{list}_{\tau_1} \sim t_2 : \text{list}_{\tau_2} \mid \phi' \wedge \mathbf{r}_1 = [] \Leftrightarrow \mathbf{r}_2 = [] \\
\Gamma \mid \Psi, \phi' [[]/\mathbf{r}_1][[]/\mathbf{r}_2] \vdash u_1 : \sigma_1 \sim u_2 : \sigma_2 \mid \phi \\
\Gamma \mid \Psi \vdash v_1 : \tau_1 \rightarrow \text{list}_{\tau_1} \rightarrow \sigma_1 \sim v_2 : \tau_2 \rightarrow \text{list}_{\tau_2} \rightarrow \sigma_2 \mid \\
\forall h_1 h_2 l_1 l_2. \phi'[h_1 :: l_1/\mathbf{r}_1][h_2 :: l_2/\mathbf{r}_2] \Rightarrow \phi[\mathbf{r}_1 h_1 l_1/\mathbf{r}_1][\mathbf{r}_2 h_2 l_2/\mathbf{r}_2] \\
\hline
\Gamma \mid \Psi \vdash \text{case } t_1 \text{ of } [] \mapsto u_1; - :: - \mapsto v_1 : \sigma_1 \sim \text{case } t_2 \text{ of } [] \mapsto u_2; - :: - \mapsto v_2 : \sigma_2 \mid \phi \quad \text{LISTCASE*}
\end{array}$$

Fig. 18. Alternative case rules

$$\begin{array}{c}
\mathcal{D}ef(f_1, x_1, e_1) \quad \mathcal{D}ef(f_2, x_2, e_2) \\
\Gamma, x_1 : I_1, x_2 : I_2, f_1 : I_1 \rightarrow \sigma, f_2 : I_2 \rightarrow \sigma_2 \mid \Psi, \phi', \\
\forall m_1 m_2. (|m_1|, |m_2|) < (|x_1|, |x_2|) \Rightarrow \phi'[m_1/x_1][m_2/x_2] \Rightarrow \phi[m_1/x_1][m_2/x_2][f_1 m_1/\mathbf{r}_1][f_2 m_2/\mathbf{r}_2] \vdash \\
e_1 : \sigma_1 \sim e_2 : \sigma_2 \mid \phi \\
\hline
\Gamma \mid \Psi \vdash \text{letrec } f_1 x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim \text{letrec } f_2 x_2 = e_2 : I_2 \rightarrow \sigma_2 \mid \forall x_1 x_2. \phi' \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1][\mathbf{r}_2 x_2/\mathbf{r}_2] \quad \text{LETREC}
\end{array}$$

$$\begin{array}{c}
\mathcal{D}ef(f_1, x_1, e_1) \\
\Gamma, x_1 : I_1, f_1 : I_1 \rightarrow \sigma \mid \Psi, \phi', \\
\forall m_1. |m_1| < |x_1| \Rightarrow \phi'[m_1/x_1] \Rightarrow \phi[m_1/x_1][m_2/x_2][f_1 m_1/\mathbf{r}_1][t_2/\mathbf{r}_2] \vdash e_1 : \sigma_1 \sim t_2 : \sigma_2 \mid \phi \\
\hline
\Gamma \mid \Psi \vdash \text{letrec } f_1 x_1 = e_1 : I_1 \rightarrow \sigma_2 \sim t_2 : \sigma_2 \mid \forall x_1. \phi' \Rightarrow \phi[\mathbf{r}_1 x_1/\mathbf{r}_1] \quad \text{LETREC - L}
\end{array}$$

where $I_1, I_2 \in \{\mathbb{N}, \text{list}_\tau\}$

Fig. 19. Recursion rules