Microstructural differences between the catalyst and the standard \mathbf{V}^{5+} phases of VPO

- A. Liskowski¹, D.S. Su¹, R. Schlögl¹, J. Lopez-Sanchez², J. K. Bartley², G. J. Hutchings²
- Fritz Haber Institute of the MPG, Department of Inorganic Chemistry, Faradayweg 4-6,
 D-14195 Berlin, Germany
- 2. Department of Chemistry, Cardiff University, P.O. Box 912, Cardiff CF10 3TB, UK

Vanadium phosphorus oxides, (VPO) are commercially used as catalysts for the synthesis of maleic anhydride, (MA) from the partial oxidation of n-butane. The phase constitution and the morphology of the catalyst are found to be dependent on the preparation routes and the applied solvent. The final catalyst consists of the main V^{4+} phase, $(VO)_2P_2O_7$ and a mixture of pentavalent phases: α_I -VOPO₄, α_{II} -VOPO₄, γ -VOPO₄ [1]. These phases are crucial for the conversion and selectivity rate of the final catalyst. It is believed that only a specific combination of V^{4+} and V^{5+} phase leads to the high catalytic performance [2]. In this work we present a comprehensive characterisation of the standard V^{5+} phases: α_I -VOPO₄, α_{II} -VOPO₄, α_{II} -VOPO₄, α_{II} -VOPO₄, α_{II} -VOPO₄ and γ -VOPO₄ and the real VPO catalyst.

A combination of methods are applied: scanning electron microscopy (SEM) for the information of morphology, energy dispersive x-ray analysis (EDX) for qualitative and quantitative elemental analysis (both on a Hitachi S-4000 SEM); X-ray diffraction (XRD) for phase analysis (on a Stoe Powder Diffractometer with the position sensitive detector); TEM for microstructural analysis – operating in low magnification, high resolution images mode, diffraction patterns and EELS analysis – (on Philips CM 200 FEG electron microscope). Samples suitable for TEM investigations were prepared by dispersing the catalyst powder onto a carbon film supported copper mesh grid.

Scanning electron images clearly show that the morphology of the α_{II} -VOPO₄, (Fig. 1) is dominated by large (ca. 5-10 μ m) and flat plates with small particles on the surface, while the β -VOPO₄, (Fig. 2) is composed of a series of square- and rectangular-like particles with the size varying from 0.5 μ m to 2 μ m. γ -VOPO₄, (Fig. 3) is made up of dense agglomerates of plate- and needle-like crystallites (where the size ranges from 0.2 μ m to 4 μ m). The activated catalyst, (Fig. 4) prepared from V₂O₅ and H₄P₂O₇ contains particles of different shapes and sizes. Diversity of the surface morphologies is influenced by the preparation procedure (starting material and its morphology, calcination temperature, environment of the process – oxygen, n-butane/air mixture or air).

Typical HR image from the catalyst is reproduced in Fig. 5. Sharp lattice fringes were obtained from [100] projection of vanadium pyrophosphate; the fringes resolved have a spacing of d=0.626 nm and the angle between them is 82°, therefore they correspond to (012) and (0-12) lattice planes of $(VO)_2P_2O_7$. The image in Fig. 6 was recorded from a very beam sensitive region of α_{II} -VOPO₄ sample. It shows an [001] projection in which the (110) and (1-10) lattice planes of α_{II} -phosphate phase are resolved. The measured fringes have a spacing of d=0.424 nm and the angle between them

is 90 degrees. More detailed results from TEM, SEM and XRD will be presented and microstructural differences between V^{5+} phosphates and the real catalyst will be compared.

Reference:

- [1] F.J. Cabello Sanchez, J.A Lopez-Sanchez, R. Wells, C. Rhodes, A. Isfahani, G.J. Hutchings, Catalysis Letters, 2001, Vol. 77
- [2] C.J. Kiely, A. Burrows, G.J. Hutchings, K.E. Bere, J.C. Volta, A. Tuel, M. Abon, Faraday Discuss., 1996, 105

Acknowledgements: The work at FHI is partly supported by SFB 546 of the Deutsche Forschungsgemeinschaft (DFG).




Fig. 3. SEM image of γ-VOPO₄

270

Fig. 5. HR image from [100] projection of (VO)₂P₂O₇

Fig. 4. SEM image of the catalyst




Fig. 6. HR image from [001] projection of α_{II} -VOPO₄